STATE OF CALIFORNIA STATE WATER RESOURCES CONTROL BOARD

ORDER WQ 2013-0085 - UST

In the Matter of Underground Storage Tank Case Closure

Pursuant to Health and Safety Code Section 25299.39.2 and the Low Threat Underground Storage Tank Case Closure Policy

BY THE EXECUTIVE DIRECTOR1:

Pursuant to Health and Safety Code section 25299.39.2, the Manager of the Underground Storage Tank Cleanup Fund (Fund) recommends closure of the underground storage tank (UST) case at the site listed below.² The name of the Fund claimant, the Fund claim number, the site name and the applicable site address are as follows:

Andy's Unocal
Claim No. 2776
Andy's Unocal
13231 Brookhurst Street, Garden Grove
Orange County Environmental Health Department

I. STATUTORY AND PROCEDURAL BACKGROUND

Section 25299.39.2 directs the Fund manager to review the case history of claims that have been active for five years or more (five-year review), unless there is an objection from the UST owner or operator. This section further authorizes the Fund Manager to make recommendations to the State Water Resources Control Board (State Water Board) for closure of a five-year-review case if the UST owner or operator approves. In response to a recommendation by the Fund Manager, the State Water Board, or in certain cases the State Water Board Executive Director, may close a case or require the closure of a UST case. Closure of a UST case is appropriate where the corrective action ensures the protection of

¹ State Water Board Resolution No. 2012-0061 delegates to the Executive Director the authority to close or require the closure of any UST case if the case meets the criteria found in the State Water Board's Low Threat Underground Storage Tank Case Closure Policy adopted by State Water Board Resolution No. 2012-0016.

² Unless otherwise noted, all references are to the Health and Safety Code.

human health, safety, and the environment and where the corrective action is consistent with:

- 1) Chapter 6.7 of Division 20 of the Health and Safety Code and implementing regulations;
- 2) Any applicable waste discharge requirements or other orders issued pursuant to Division 7 of the Water Code; 3) All applicable state policies for water quality control; and 4) All applicable water quality control plans.

The Fund Manager has completed a five-year review of the UST case identified above, and recommends that this case be closed. The recommendation is based upon the facts and circumstances of this particular UST case. A UST Case Closure Review Summary Report has been prepared for the case identified above and the bases for determining compliance with the Water Quality Control Policy for Low-Threat Underground Storage Tank Case Closures (Low-Threat Closure Policy or Policy) are explained in the Case Closure Review Summary Report.

A. Low-Threat Closure Policy

In State Water Board Resolution No. 2012-0016, the State Water Board adopted the Low Threat Closure Policy. The Policy became effective on August 17, 2012. The Policy establishes consistent statewide case closure criteria for certain low-threat petroleum UST sites. In the absence of unique attributes or site-specific conditions that demonstrably increase the risk associated with residual petroleum constituents, cases that meet the general and media-specific criteria in the Low-Threat Closure Policy pose a low threat to human health, safety and the environment and are appropriate for closure under Health and Safety Code section 25296.10. The Policy provides that if a regulatory agency determines that a case meets the general and media-specific criteria of the Policy, then the regulatory agency shall notify responsible parties and other specified interested persons that the case is eligible for case closure. Unless the regulatory agency revises its determination based on comments received on the proposed case closure, the Policy provides that the agency shall issue a closure letter as specified in Health and Safety Code section 25296.10. The closure letter may only be issued after the expiration of the 60-day comment period, proper destruction or maintenance of monitoring wells or borings, and removal of waste associated with investigation and remediation of the site.

Health and Safety Code section 25299.57, subdivision (I)(1) provides that claims for reimbursement of corrective action costs that are received by the Fund more than 365 days after the date of a closure letter or a Letter of Commitment, whichever occurs later, shall not be reimbursed unless specified conditions are satisfied. A Letter of Commitment has already been issued on the claim subject to this order and the respective Fund claimant, so the 365-day

timeframe for the submittal of claims for corrective action costs will start upon the issuance of the closure letter.

II. FINDINGS

Based upon the UST Case Closure Review Summary Report prepared for the case attached hereto, the State Water Board finds that corrective action taken to address the unauthorized release of petroleum at the UST release site identified as:

Claim No. 2776

Andy's Unocal

ensures protection of human health, safety and the environment and is consistent with Chapter 6.7 of Division 20 of the Health and Safety Code and implementing regulations, the Low-Threat Closure Policy and other water quality control policies and applicable water quality control plans.

Pursuant to the Low-Threat Closure Policy, notification has been provided to all entities that are required to receive notice of the proposed case closure, a 60-day comment period has been provided to notified parties, and any comments received have been considered by the Board in determining that the case should be closed.

The UST case identified above may be the subject of orders issued by the Regional Water Quality Control Water Board (Regional Water Board) pursuant to Division 7 of the Water Code. Any orders that have been issued by the Regional Water Board pursuant to Division 7 of the Water Code, or directives issued by a Local Oversight Program agency for this case should be rescinded to the extent they are inconsistent with this Order.

III. ORDER

IT IS THEREFORE ORDERED that:

A. The UST case identified in Section II of this Order, meeting the general and mediaspecific criteria established in the Low-Threat Closure Policy, be closed in accordance with the following conditions and after the following actions are complete. Prior to the issuance of a closure letter, the Fund claimant is ordered to:

- 1. Properly destroy monitoring wells and borings unless the owner of real property on which the well or boring is located certifies that the wells or borings will be maintained in accordance with local or state requirements;
- 2. Properly remove from the site and manage all waste piles, drums, debris, and other investigation and remediation derived materials in accordance with local or state requirements; and
- 3. Within six months of the date of this Order, submit documentation to the regulatory agency overseeing the UST case identified in Section II of this Order that the tasks in subparagraphs (1) and (2) have been completed.
- B. The tasks in subparagraphs (1) and (2) of paragraph (A) are ordered pursuant to Health and Safety Code section 25296.10 and failure to comply with these requirements may result in the imposition of civil penalties pursuant to Health and Safety Code section 25299, subdivision (d)(1). Penalties may be imposed administratively by the State Water Board or Regional Water Board.
- C. Within 30 days of receipt of proper documentation from the Fund claimant that requirements in subparagraphs (1) and (2) of paragraph (A) are complete, the regulatory agency that is responsible for oversight of the UST case identified in Section II of this Order shall notify the State Water Board that the tasks have been satisfactorily completed.
- D. Within 30 days of notification from the regulatory agency that the tasks are complete pursuant to paragraph (C), the Deputy Director of the Division of Financial Assistance shall issue a closure letter consistent with Health and Safety Code section 25296.10, subdivision (g) and upload the closure letter and UST Case Closure Review Summary Report to GeoTracker.
- E. As specified in Health and Safety Code section 25299.39.2, subdivision (a) (2), corrective action costs incurred after a recommendation of closure shall be limited to \$10,000 per year unless the Board or its delegated representative agrees that corrective action in excess of that amount is necessary to meet closure requirements, or additional corrective actions are necessary pursuant to section 25296.10, subdivisions (a) and (b). Pursuant to section 25299.57, subdivision (I) (1), and except in specified circumstances,

- all claims for reimbursement of corrective action costs must be received by the Fund within 365 days of issuance of the closure letter in order for the costs to be considered.
- F. Any Regional Water Board or Local Oversight Program Agency directive or order that directs corrective action or other action inconsistent with case closure for the UST case identified in Section II is rescinded, but only to the extent the Regional Water Board order or Local Oversight Program Agency directive is inconsistent with this Order.

Executive Director

5





State Water Resources Control Board

UST CASE CLOSURE REVIEW SUMMARY REPORT

Agency Information

Agency Name: Orange County Environmental Health Department (County)	Address: 1241 East Dyer Road, Suite 120 Santa Ana, CA 92705				
Agency Caseworker: Kevin Lambert	Case No.: 89UTY095				

Case Information

USTCF Claim No.: 2776	GeoTracker Global ID: T0605900976			
Site Name: Andy's Unocal	Site Address: 13231 Brookhurst Street, Garden Grove, CA 92844			
Responsible Party (RP): Andy's Unocal Attn: Don Thio	Address: Private Residence			
USTCF Expenditures to Date: \$1,399,509	Number of Years Case Open: 23			

URL: http://geotracker.waterboards.ca.gov/profile_report.asp?global_id=T0605900976

Summary

The Low-Threat Underground Storage Tank (UST) Case Closure Policy (Policy) contains general and media-specific criteria, and cases that meet those criteria are appropriate for closure pursuant to the Policy. This case meets all of the required criteria of the Policy. A summary evaluation of compliance with the Policy is shown in **Attachment 1: Compliance with State Water Board Policies and State Law**. The Conceptual Site Model upon which the evaluation of the case has been made is described in **Attachment 2: Summary of Basic Case Information (Conceptual Site Model)**. Highlights of the case follow:

This case is currently a used car dealership. The Site was an active commercial petroleum fueling facility until 1990. An unauthorized leak was reported in May 1989 based soil samples collected during a site investigation. The USTs (two gasoline, one diesel and one waste oil) were removed in April 1993. Approximately 160 gallons of free product were recovered between August 1991 and January 1994. Approximately 827.5 tons of impacted soil were excavated and removed from the Site in 1996. Soil vapor extraction was performed at the Site from November 2000 to August 2010. Air sparging was conducted at the Site from July 2001 to January 2011. Groundwater pump-and-treat remediation was performed at the Site from August 2001 to March 2006. Since 1990, eight groundwater monitoring wells have been installed and have been monitored regularly. According to groundwater data, water quality objectives have been achieved for all constituents.

The petroleum release is limited to the soil and shallow groundwater. According to data available in GeoTracker, there are no supply wells regulated by California Department of Public Health or surface water bodies within 250 feet of the defined plume boundary. No other water supply wells have been identified within 250 feet of the defined plume boundary in files reviewed. Water is provided to water users at and near the Site by the City of Garden Grove Public Works.

The affected groundwater is not currently being used as a source of drinking water, and it is highly unlikely that the affected groundwater will be used as a source of drinking water in the foreseeable future. Other designated beneficial uses of impacted groundwater are not threatened and it is highly unlikely that they will be, considering these factors in the context of the site setting. Remaining petroleum hydrocarbon constituents are limited and stable, and concentrations are decreasing. Corrective actions have been implemented and additional corrective actions are not necessary. Any remaining petroleum hydrocarbon constituents do not pose a significant risk to human health, safety or the environment.

Rationale for Closure under the Policy

- General Criteria: The case meets all eight Policy general criteria.
- Groundwater Specific Criteria: The case meets Policy Criterion 1 by Class 1. The contaminant plume that exceeds water quality objectives is less than 100 feet in length. There is no free product. The nearest water supply well or surface water body is greater than 250 feet from the defined plume boundary.
- Vapor Intrusion to Indoor Air: The case meets Policy Criterion 2a by scenario 3a. The maximum benzene concentration in groundwater is less than 100 micrograms per liter (µg/L). The minimum depth to groundwater is greater than 5 feet, overlain by soil containing less than 100 milligrams per kilogram (mg/kg) of TPH.
- Direct Contact and Outdoor Air Exposure: The case meets Policy Criterion 3a. Maximum concentrations in soil are less than those in Policy Table 1 for Residential and Commercial/Industrial use and the concentration limits for a Utility Worker are not exceeded.

Objections to Closure and Responses

None. The County case worker indicated that the County considered the Site ready for closure (February 25, 2013 telephone communication).

Determination

Based on the review performed in accordance with Health & Safety Code Section 25299.39.2 subdivision (a), the Fund Manager has determined that closure of the case is appropriate.

Recommendation for Closure

Based on available information, residual petroleum hydrocarbons at the Site do not pose a significant risk to human health, safety, or the environment, and the case meets the requirements of the Policy. Accordingly, the Fund Manager recommends that the case be closed. The State Water Board is conducting public notification as required by the Policy. Orange County has the regulatory responsibility to supervise the abandonment of monitoring wells.

Lisa Babcock, P.G. 3939, C.E.G. 1235

Prepared by: Mohammed Khan, P.E. License # CH 4550

ATTACHMENT 1: COMPLIANCE WITH STATE WATER BOARD POLICIES AND STATE LAW

The case complies with the State Water Resources Control Board policies and state law. Section 25296.10 of the Health and Safety Code requires that sites be cleaned up to protect human health, safety, and the environment. Based on available information, any residual petroleum constituents at the Site do not pose significant risk to human health, safety, or the environment.

The case complies with the requirements of the Low-Threat Underground Storage Tank (UST) Case Closure Policy as described below.¹

· · · · · · · · · · · · · · · · · · ·
☑ Yes □ No
□ Yes ℤ No
□ Yes □ No ☒ NA
franciscon odi
☑ Yes □ No
☑ Yes □ No
☑ Yes □ No
☑ Yes □ No □ NA
☑ Yes □ No

¹ Refer to the Low-Threat Underground Storage Tank Case Closure Policy for closure criteria for low-threat petroleum UST sites.

Has secondary source been removed to the extent practicable?	☑ Yes □ No
Has soil or groundwater been tested for MTBE and results reported in accordance with Health and Safety Code Section 25296.15?	☑ Yes □ No
Nuisance as defined by Water Code section 13050 does not exist at the Site?	☑ Yes □ No
Are there unique site attributes or site-specific conditions that demonstrably increase the risk associated with residual petroleum constituents?	□ Yes ☑ No
Media-Specific Criteria	is detraction ac
Candidate sites must satisfy all three of these media-specific criteria:	m substant and
1. Groundwater:	household yighted
To satisfy the media-specific criteria for groundwater, the contaminant plume that exceeds water quality objectives must be stable or decreasing in areal extent, and meet all of the additional characteristics of one of the five classes of sites:	noutry authorized in the second in the secon
Is the contaminant plume that exceeds water quality objectives stable or decreasing in areal extent?	☑ Yes □ No □ NA
Does the contaminant plume that exceeds water quality objectives meet all of the additional characteristics of one of the five classes of sites?	☑ Yes □ No □ NA
If YES, check applicable class: 図1 □2 □3 □4 □5	and the second second
For sites with releases that have not affected groundwater, do mobile	☐ Yes ☐ No ☒ NA
constituents (leachate, vapors, or light non-aqueous phase liquids)	
contain sufficient mobile constituents to cause groundwater to exceed the groundwater criteria?	Geograpi Orlinia
2. Petroleum Vapor Intrusion to Indoor Air:	
The site is considered low-threat for vapor intrusion to indoor air if site-specific conditions satisfy all of the characteristics of one of the three classes of sites (a through c) or if the exception for active commercial fueling facilities applies.	System?
	eikoneso mili vorti
Is the Site an active commercial petroleum fueling facility? Exception: Satisfaction of the media-specific criteria for petroleum vapor intrusion to indoor air is not required at active commercial petroleum fueling facilities, except in cases where release characteristics can be reasonably believed to pose an unacceptable health risk.	□ Yes ☑ No
a. Do site-specific conditions at the release site satisfy all of the	of the triples in
applicable characteristics and criteria of scenarios 1 through 3 or all of the applicable characteristics and criteria of scenario 4?	☑Yes □ No □ NA
If YES, check applicable scenarios: □ 1 □ 2 ☑ 3 □ 4	wet uit a eler
	The second second second

b.	Has a site-specific risk assessment for the vapor intrusion pathway been conducted and demonstrates that human health is protected to the satisfaction of the regulatory agency?	□ Yes □ No □	X NA
C.	As a result of controlling exposure through the use of mitigation measures or through the use of institutional or engineering controls, has the regulatory agency determined that petroleum vapors migrating from soil or groundwater will have no significant risk of adversely affecting human health?	□ Yes □ No □	X NA
	Direct Contact and Outdoor Air Exposure:	r in i uarmo	
	e Site is considered low-threat for direct contact and outdoor air exposure ite-specific conditions satisfy one of the three classes of sites (a through	Several U.S	
a.	Are maximum concentrations of petroleum constituents in soil less than or equal to those listed in Table 1 for the specified depth below ground surface (bgs)?	☑ Yes □ No □	□ NA
b.	Are maximum concentrations of petroleum constituents in soil less than levels that a site specific risk assessment demonstrates will have no significant risk of adversely affecting human health?	☐ Yes ☐ No I	⊠ NA
c.	As a result of controlling exposure through the use of mitigation measures or through the use of institutional or engineering controls, has the regulatory agency determined that the	□ Yes □ No I	X NA
÷	concentrations of petroleum constituents in soil will have no significant risk of adversely affecting human health?	G.	

ATTACHMENT 2: SUMMARY OF BASIC CASE INFORMATION (Conceptual Site Model)

Site Location/History

- The Site is currently a used car dealership located on the northwest corner of the intersection of Brookhurst Street and Central Avenue in Garden Grove. The Site was an active Unocalbrand petroleum fueling facility until 1990.
- The Site is bounded by Central Avenue and a residential apartment complex to the south, an apartment building to the west, a small strip mall to the north, Brookhurst Street and a furniture store to the east.
- Site map showing the location of the former USTs, monitoring wells and groundwater level
 contours as well as properties located in the immediate vicinity of the Site is provided at the
 end of this closure review summary (modified from Frey Environmental, Inc., January 2012).
- Nature of Contaminants of Concern: Petroleum hydrocarbons only.
- Source: UST system.
- Date reported: May 1989.
- Status of Release: USTs removed.
- Free Product: It was reported in 1990 that 1.83 feet of free product were measured in monitoring MW-1. Trace amounts of free product were detected occasionally in monitoring wells MW-2, MW-4, MW-5, and MW-7 until end of 2000. Free product has not been reported in Site monitoring wells since 2001.

Tank Information

Tank No.	Size in Gallons	Contents	Closed in Place/ Removed/Active	Date	
1	10,000	Gasoline	Removed	April 1993	
2	10,000	Gasoline	Removed	April 1993	
3	10,000	Diesel	Removed	April 1993	
4	280	Waste Oil	Removed	April 1993	

Receptors

- GW Basin: Coastal Plain of Orange County.
- Beneficial Uses: Municipal and Domestic Supply.
- Land Use Designation: Commercial.
- Public Water System: City of Garden Grove, Public Works Department.
- Distance to Nearest Supply Well: According to data available in GeoTracker, there are no
 public supply wells regulated by the California Department of Public Health within 250 feet of
 the defined plume boundary. No other water supply wells were identified within 250 feet of the
 defined plume boundary in the files reviewed.
- Distance to Nearest Surface Water: There is no identified surface water within 250 feet of the defined plume boundary.

Geology/Hydrogeology

- Stratigraphy: The Site is underlain by interbedded and intermixed sand, silt, and clay.
- Maximum Sample Depth: 37 feet below ground surface (bgs).
- Minimum Groundwater Depth: 5.18 feet bgs at monitoring well GEW1.
- Maximum Groundwater Depth: 31.00 feet bgs at monitoring well MW-5.
- Current Average Depth to Groundwater: Approximately 10 feet bgs.

- Saturated Zones(s) Studied: Approximately 7 37 feet bgs.
- Appropriate Screen Interval: Yes.
- Groundwater Flow Direction: The groundwater flow direction beneath the Site was estimated to be to the east-southeast at an approximate gradient of 0.004 feet per foot (January 2012).

Monitoring Well Information

Well Designation	Date Installed	Screen Interval (feet bgs)	Depth to Water (feet bgs) (11/30/2011)	
MW-2	January 1990	7 - 37	9.98	
MW-3	January 1990	7 - 37	11.36	
MW-4	January 1990	7 - 37	10.15	
MW-5	January 1990	7 - 37	10.45	
MW-6	March 1997	7 - 37	10.60	
MW-7	March 1997	7 - 37	9.53	
GEW1	November 1999	5.5 - 20.5	9.70	
RW1*	April 1996	Horizontal Well	10.65	

^{*:} RW1 is a dual-nested, horizontal groundwater and vapor recovery well

Remediation Summary

- Free Product: Approximately 160 gallons of free product were recovered from Site wells MW-1, MW-2, and MW-5 between August 1991 and January 1994.
- Soil Excavation: Approximately 827.5 tons of impacted soil were excavated and removed from the Site in 1996. The 1996 excavation extended the 1993 UST removal excavation vertically to 15 feet bgs. In addition, the original excavation was extended northward to include the area occupied by the former fuel dispenser islands to a depth of about 12 feet bgs (Frey, April 2012).
- In-Situ Soil Remediation: Soil vapor extraction was initiated at the Site on November 9, 2000, and terminated on August 10, 2010.
- Groundwater Remediation: Air sparging was conducted at the Site from July 2001 to January 2011. Groundwater pump-and-treat remediation was performed at the Site from August 2001 to March 2006.

Most Roent Concentrations of Petroleum Constituents in Soil

Constituent	Maximum 0-5 feet bgs [mg/kg and (date)]	Maximum 5-10 feet bgs [mg/kg and (date)]		
Benzene	<0.0050 (10/24/11)	<0.0050 (10/24/11)		
Ethylbenzene	<0.0050 (10/24/11)	<0.0050 (10/24/11)		
Naphthalene	<0.050 (10/24/11)	<0.050 (10/24/11)		
PAHs	NA	NA		

NA: Not Analyzed, Not Applicable or Data Not Available mg/kg: Milligrams per kilogram, parts per million <: Not detected at or above stated reporting limit PAHs: Polycyclic aromatic hydrocarbons

Most Recent Concentrations of Petroleum Constituents in Groundwater

Sample	Sample Date	TPHg (µg/L)	Benzene (µg/L)	Toluene (µg/L)	Ethyl- Benzene (µg/L)	Xylenes (μg/L)	MTBE (µg/L)	TBA (µg/L)
MW-2	11/30/2011	<100	<0.50	<1.0	<1.0	<1.0	<1.0	<10
MW-3	11/30/2011	<100	<0.50	<1.0	<1.0	<1.0	<1.0	<10
MW-4	11/30/2011	<100	<0.50	<1.0	<1.0	<1.0	<1.0	<10
MW-5	11/30/2011	190	<0.50	<1.0	<1.0	<1.0	<1.0	<10
MW-6	11/30/2011	<100	<0.50	<1.0	<1.0	<1.0	<1.0	<10
MW-7	11/30/2011	<100	<0.50	<1.0	<1.0	<1.0	<1.0	<10
GEW1	11/30/2011	<100	<0.50	<1.0	<1.0	<1.0	<1.0	<10
RW1	11/30/2011	<100	<0.50	<1.0	<1.0	<1.0	<1.0	<10
WQOs			1	150	300	1,750	. 5ª	1,200 ^b

μg/L: Micrograms per liter, parts per billion

<: Not detected at or above stated reporting limit TPHg: Total petroleum hydrocarbons as gasoline

MTBE: Methyl tert-butyl ether TBA: Tert-butyl alcohol

WQOs: Water Quality Objectives, Regional Water Board Basin Plan


--: Regional Water Board Basin Plan does not have a numeric water quality objective for TPHg

a: Secondary maximum contaminant level (MCL)
b: California Department of Public Health, Response Level


Groundwater Trends

Since 1990, eight groundwater monitoring wells have been installed and have been monitored regularly. Benzene trends of select wells are shown below:

Source Area Well




Downgradient Well




Evaluation of Current Risk

- Estimate of Hydrocarbon Mass in Soil: None reported for Site.
- Soil/Groundwater tested for methyl tert-butyl ether (MTBE): Yes, see table above.
- Oxygen Concentrations in Soil Vapor: None reported.
- Plume Length: <100 feet.
- Plume Stable or Decreasing: Yes.
- Contaminated Zone(s) Used for Drinking Water: No.
- Groundwater Risk from Residual Petroleum Hydrocarbons: The case meets Policy Criterion 1 by Class 1. The plume that exceeds water quality objectives is less than 100 feet in length. There is no free product. The nearest water supply well or surface water body is greater than 250 feet from the defined plume boundary.
- Indoor Vapor Risk from Residual Petroleum Hydrocarbons: The case meets Policy Criterion 2a by Scenario 3a. The maximum benzene concentration in groundwater is less than 100 μg/L. The minimum depth to groundwater is greater than 5 feet, overlain by soil containing less than 100 mg/kg of TPH.
- Direct Contact and Outdoor Air Exposure Risk from Residual Petroleum Hydrocarbons: The
 case meets Policy Criterion 3a. Maximum concentrations in soil are less than those in Policy
 Table 1 for Residential as well as Commercial/Industrial use, and the concentration limits for a
 Utility Worker are not exceeded.



Page 10 of 11



Page 11 of 11