# STATE OF CALIFORNIA STATE WATER RESOURCES CONTROL BOARD

#### ORDER WQ 2014-0059 - UST

### In the Matter of Underground Storage Tank Case Closure

Pursuant to Health and Safety Code Section 25299.39.2 and the Low Threat Underground Storage Tank Case Closure Policy

## BY THE EXECUTIVE DIRECTOR1:

Pursuant to Health and Safety Code section 25299.39.2, the Manager of the Underground Storage Tank Cleanup Fund (Fund) recommends closure of the underground storage tank (UST) case at the site listed below. The name of the Fund claimant, the Fund claim number, the site name and the applicable site address are as follows:

Orange Avenue Associates Claim No. 9792 Orange Avenue Associates 2540B South Orange Street Santa Ana

Santa Ana Regional Water Quality Control Board

#### I. STATUTORY AND PROCEDURAL BACKGROUND

Section 25299.39.2 directs the Fund manager to review the case history of claims that have been active for five years or more (five-year review), unless there is an objection from the UST owner or operator. This section further authorizes the Fund Manager to make recommendations to the State Water Resources Control Board (State Water Board) for closure of a five-year-review case if the UST owner or operator approves. In response to a recommendation by the Fund Manager, the State Water Board, or in certain cases the State Water Board Executive Director, may close a case or require the closure of a UST case. Closure of a UST case is appropriate where the corrective action ensures the protection of human health, safety, and the environment and where the corrective action is consistent with:

<sup>&</sup>lt;sup>1</sup> State Water Board Resolution No. 2012-0061 delegates to the Executive Director the authority to close or require the closure of any UST case if the case meets the criteria found in the State Water Board's Low Threat Underground Storage Tank Case Closure Policy adopted by State Water Board Resolution No. 2012-0016.

<sup>&</sup>lt;sup>2</sup> Unless otherwise noted, all references are to the Health and Safety Code.

- 1) Chapter 6.7 of Division 20 of the Health and Safety Code and implementing regulations;
- 2) Any applicable waste discharge requirements or other orders issued pursuant to Division 7 of the Water Code; 3) All applicable state policies for water quality control; and 4) All applicable water quality control plans.

The Fund Manager has completed a five-year review of the UST case identified above, and recommends that this case be closed. The recommendation is based upon the facts and circumstances of this particular UST case. A UST Case Closure Review Summary Report has been prepared for the case identified above and the bases for determining compliance with the Water Quality Control Policy for Low-Threat Underground Storage Tank Case Closures (Low-Threat Closure Policy or Policy) are explained in the Case Closure Review Summary Report.

### A. Low-Threat Closure Policy

In State Water Board Resolution No. 2012-0016, the State Water Board adopted the Low Threat Closure Policy. The Policy became effective on August 17, 2012. The Policy establishes consistent statewide case closure criteria for certain low-threat petroleum UST sites. In the absence of unique attributes or site-specific conditions that demonstrably increase the risk associated with residual petroleum constituents, cases that meet the general and media-specific criteria in the Low-Threat Closure Policy pose a low threat to human health, safety and the environment and are appropriate for closure under Health and Safety Code section 25296.10. The Policy provides that if a regulatory agency determines that a case meets the general and media-specific criteria of the Policy, then the regulatory agency shall notify responsible parties and other specified interested persons that the case is eligible for case closure. Unless the regulatory agency revises its determination based on comments received on the proposed case closure, the Policy provides that the agency shall issue a closure letter as specified in Health and Safety Code section 25296.10. The closure letter may only be issued after the expiration of the 60-day comment period, proper destruction or maintenance of monitoring wells or borings, and removal of waste associated with investigation and remediation of the site.

Health and Safety Code section 25299.57, subdivision (I)(1) provides that claims for reimbursement of corrective action costs that are received by the Fund more than 365 days after the date of a closure letter or a Letter of Commitment, whichever occurs later, shall not be reimbursed unless specified conditions are satisfied. A Letter of Commitment has already been issued on the claim subject to this order and the respective Fund claimant, so the 365-day timeframe for the submittal of claims for corrective action costs will start upon the issuance of the closure letter.

#### II. FINDINGS

Based upon the UST Case Closure Review Summary Report prepared for the case attached hereto, the State Water Board finds that corrective action taken to address the unauthorized release of petroleum at the UST release site identified as:

## Claim No. 9792 Orange Avenue Associates

ensures protection of human health, safety and the environment and is consistent with Chapter 6.7 of Division 20 of the Health and Safety Code and implementing regulations, the Low-Threat Closure Policy and other water quality control policies and applicable water quality control plans.

The unauthorized release from the UST consisted only of petroleum. This order directs closure for the petroleum UST case at the site.

Pursuant to the Low-Threat Closure Policy, notification has been provided to all entities that are required to receive notice of the proposed case closure, a 60-day comment period has been provided to notified parties, and any comments received have been considered by the Board in determining that the case should be closed.

Pursuant to section 21080.5 of the Public Resources Code, environmental impacts associated with the adoption of this Order were analyzed in the substitute environmental document (SED) the State Water Board approved on May 1, 2012. The SED concludes that all environmental effects of adopting and implementing the Low threat Closure Policy are less than significant, and environmental impacts as a result of complying with the Policy are no different from the impacts that are reasonably foreseen as a result of the Policy itself. A Notice of Decision was filed August 17, 2012. No new environmental impacts or any additional reasonably foreseeable impacts beyond those that were not addressed in the SED will result from adopting this Order.

The UST case identified above may be the subject of orders issued by the Regional Water Quality Control Board (Regional Water Board) pursuant to Division 7 of the Water Code. Any orders that have been issued by the Regional Water Board pursuant to Division 7 of the Water Code, or directives issued by a Local Oversight Program agency for this case should be rescinded to the extent they are inconsistent with this Order.

#### III. ORDER

## IT IS THEREFORE ORDERED that:

- A. The UST case identified in Section II of this Order, meeting the general and mediaspecific criteria established in the Low-Threat Closure Policy, be closed in accordance with the following conditions and after the following actions are complete. Prior to the issuance of a closure letter, the Fund claimant is ordered to:
  - 1. Properly destroy monitoring wells and borings unless the owner of real property on which the well or boring is located certifies that the wells or borings will be maintained in accordance with local or state requirements;
  - 2. Properly remove from the site and manage all waste piles, drums, debris, and other investigation and remediation derived materials in accordance with local or state requirements; and
  - 3. Within six months of the date of this Order, submit documentation to the regulatory agency overseeing the UST case identified on page 1 of this Order that the tasks in subparagraphs (1) and (2) have been completed.
- B. The tasks in subparagraphs (1) and (2) of paragraph (A) are ordered pursuant to Health and Safety Code section 25296.10 and failure to comply with these requirements may result in the imposition of civil penalties pursuant to Health and Safety Code section 25299, subdivision (d)(1). Penalties may be imposed administratively by the State Water Board or Regional Water Board.
- C. Within 30 days of receipt of proper documentation from the Fund claimant that requirements in subparagraphs (1) and (2) of paragraph (A) are complete, the regulatory agency that is responsible for oversight of the UST case identified in Section II of this Order shall notify the State Water Board that the tasks have been satisfactorily completed.
- D. Within 30 days of notification from the regulatory agency that the tasks are complete pursuant to paragraph (C), the Deputy Director of the Division of Financial Assistance shall issue a closure letter consistent with Health and Safety Code section 25296.10,

subdivision (g) and upload the closure letter and UST Case Closure Review Summary Report to GeoTracker.

- E. As specified in Health and Safety Code section 25299.39.2, subdivision (a) (2), corrective action costs incurred after a recommendation of closure shall be limited to \$10,000 per year unless the Board or its delegated representative agrees that corrective action in excess of that amount is necessary to meet closure requirements, or additional corrective actions are necessary pursuant to section 25296.10, subdivisions (a) and (b). Pursuant to section 25299.57, subdivision (I) (1), and except in specified circumstances, all claims for reimbursement of corrective action costs must be received by the Fund within 365 days of issuance of the closure letter in order for the costs to be considered.
- F. Any Regional Water Board or Local Oversight Program Agency directive or order that directs corrective action or other action inconsistent with case closure for the UST case identified in Section II is rescinded, but only to the extent the Regional Water Board order or Local Oversight Program Agency directive is inconsistent with this Order.

**Executive Director** 

#### DRAFT

# STATE OF CALIFORNIA STATE WATER RESOURCES CONTROL BOARD

#### **ORDER WQ 2014-00XX - UST**

## In the Matter of Underground Storage Tank Case Closure

Pursuant to Health and Safety Code Section 25299.39.2 and the Low Threat Underground Storage Tank Case Closure Policy

## BY THE EXECUTIVE DIRECTOR1:

Pursuant to Health and Safety Code section 25299.39.2, the Manager of the Underground Storage Tank Cleanup Fund (Fund) recommends closure of the underground storage tank (UST) case at the site listed below.<sup>2</sup> The name of the Fund claimant, the Fund claim number, the site name and the applicable site address are as follows:

Orange Avenue Associates Claim No. 9792 Orange Avenue Associates 2540B South Orange Street Santa Ana

Santa Ana Regional Water Quality Control Board

#### I. STATUTORY AND PROCEDURAL BACKGROUND

Section 25299.39.2 directs the Fund manager to review the case history of claims that have been active for five years or more (five-year review), unless there is an objection from the UST owner or operator. This section further authorizes the Fund Manager to make recommendations to the State Water Resources Control Board (State Water Board) for closure of a five-year-review case if the UST owner or operator approves. In response to a recommendation by the Fund Manager, the State Water Board, or in certain cases the State Water Board Executive Director, may close a case or require the closure of a UST case. Closure of a UST case is appropriate where the corrective action ensures the protection of human health, safety, and the environment and where the corrective action is consistent with:

<sup>&</sup>lt;sup>1</sup> State Water Board Resolution No. 2012-0061 delegates to the Executive Director the authority to close or require the closure of any UST case if the case meets the criteria found in the State Water Board's Low Threat Underground Storage Tank Case Closure Policy adopted by State Water Board Resolution No. 2012-0016.

<sup>&</sup>lt;sup>2</sup> Unless otherwise noted, all references are to the Health and Safety Code.

- 1) Chapter 6.7 of Division 20 of the Health and Safety Code and implementing regulations;
- 2) Any applicable waste discharge requirements or other orders issued pursuant to Division 7 of the Water Code; 3) All applicable state policies for water quality control; and 4) All applicable water quality control plans.

The Fund Manager has completed a five-year review of the UST case identified above, and recommends that this case be closed. The recommendation is based upon the facts and circumstances of this particular UST case. A UST Case Closure Review Summary Report has been prepared for the case identified above and the bases for determining compliance with the Water Quality Control Policy for Low-Threat Underground Storage Tank Case Closures (Low-Threat Closure Policy or Policy) are explained in the Case Closure Review Summary Report.

## A. Low-Threat Closure Policy

In State Water Board Resolution No. 2012-0016, the State Water Board adopted the Low Threat Closure Policy. The Policy became effective on August 17, 2012. The Policy establishes consistent statewide case closure criteria for certain low-threat petroleum UST sites. In the absence of unique attributes or site-specific conditions that demonstrably increase the risk associated with residual petroleum constituents, cases that meet the general and media-specific criteria in the Low-Threat Closure Policy pose a low threat to human health, safety and the environment and are appropriate for closure under Health and Safety Code section 25296.10. The Policy provides that if a regulatory agency determines that a case meets the general and media-specific criteria of the Policy, then the regulatory agency shall notify responsible parties and other specified interested persons that the case is eligible for case closure. Unless the regulatory agency revises its determination based on comments received on the proposed case closure, the Policy provides that the agency shall issue a closure letter as specified in Health and Safety Code section 25296.10. The closure letter may only be issued after the expiration of the 60-day comment period, proper destruction or maintenance of monitoring wells or borings, and removal of waste associated with investigation and remediation of the site.

Health and Safety Code section 25299.57, subdivision (I)(1) provides that claims for reimbursement of corrective action costs that are received by the Fund more than 365 days after the date of a closure letter or a Letter of Commitment, whichever occurs later, shall not be reimbursed unless specified conditions are satisfied. A Letter of Commitment has already been issued on the claim subject to this order and the respective Fund claimant, so the 365-day timeframe for the submittal of claims for corrective action costs will start upon the issuance of the closure letter.





## **State Water Resources Control Board**

## **UST CASE CLOSURE REVIEW SUMMARY REPORT**

**Agency Information** 

Agency Name: Santa Ana Regional Water Quality Control Board (Regional Water Board)	Address: 3737 Main Street Suite 500 Riverside, CA 92501
Agency Caseworker: Rose Scott	Case No.: 83002768T

## **Case Information**

USTCF Claim No.: 9792	GeoTracker Global ID: T0605901909			
Site Name: Orange Avenue Associates	Site Address: 2540B South Orange Street			
D	Santa Ana, CA 92707			
Responsible Party: Orange Avenue Associates	Address: 232 West Cerritos Avenue			
110-0	Anaheim, CA 92805			
USTCF Expenditures to Date: \$11,116	Number of Years Case Open: 22			

## URL: http://geotracker.waterboards.ca.gov/profile report.asp?global id=T0605901909

## Summary

The Low-Threat Underground Storage Tank (UST) Case Closure Policy (Policy) contains general and media-specific criteria, and cases that meet those criteria are appropriate for closure pursuant to the Policy. This case meets all of the required criteria of the Policy. A summary evaluation of compliance with the Policy is shown in **Attachment 1: Compliance with State Water Board Policies and State Law**. The Conceptual Site Model upon which the evaluation of the case has been made is described in **Attachment 2: Summary of Basic Case Information (Conceptual Site Model)**. Highlights of the case follow:

This case is an active warehouse. An unauthorized release was reported in July 1994 following the removal of two USTs, one gasoline and one diesel. Approximately 400 tons of impacted soil were removed and disposed offsite in 1999. The excavated area was backfilled with clean soil and then paved with asphalt. No active remediation has occurred at the Site. Since 1999, six groundwater monitoring wells have been installed and irregularly monitored. According to groundwater data, water quality objectives have been achieved or nearly achieved for all constituents except for benzene and MTBE.

The petroleum release is limited to the soil and shallow groundwater. According to data available in GeoTracker, there are no supply wells regulated by the California Department of Public Health or surface water bodies within 250 feet of the defined plume boundary. No other water supply wells have been identified within 250 feet of the defined plume boundary in files reviewed. Water is provided to water users near the Site by Metropolitan Water District of Southern California. The affected groundwater is not currently being used as a source of drinking water, and it is highly unlikely that the affected groundwater will be used as a source of drinking water in the foreseeable future. Other designated beneficial uses of impacted groundwater are not threatened, and it is highly unlikely that they will be, considering these factors in the context of the site setting.

Orange Avenue Associates 2540B S Orange Street, Santa Ana Claim No: 9792

Remaining petroleum hydrocarbon constituents are limited and stable and concentrations are decreasing. Corrective actions have been implemented and additional corrective actions are not necessary. Any remaining petroleum hydrocarbon constituents do not pose a significant risk to human health, safety or the environment.

## Rationale for Closure under the Policy

General Criteria: The case meets all eight Policy general criteria.

 Groundwater Specific Criteria: The case meets Policy Criterion 1 by Class 1. The contaminant plume that exceeds water quality objectives is less than 100 feet in length. There is no free product. The nearest water supply well or surface water body is greater than 250 feet from the defined plume boundary.

- Vapor Intrusion to Indoor Air: The case meets Policy Criterion 2b. Although no document titled "Risk Assessment" was located in the files reviewed, a professional assessment of site-specific risk from exposure through the vapor intrusion pathway shows that maximum concentrations of petroleum constituents will have no significant risk of adversely affecting human health. The building where monitoring well MW-5 is reporting high groundwater benzene concentration has floors covered by 3 to 4 inch of concrete which restricts the potential for vapor intrusion to indoor air. In addition, the building houses electric motor and other heavy machinery shops. Such working environment requires sufficient ventilation and other safety measures to mitigate harmful exhaust and dust. These added measures also mitigate any vapor intrusion to indoor air risk from the groundwater benzene impact.
- Direct Contact and Outdoor Air Exposure: The case meets Policy Criterion 3a. Maximum concentrations in soil are less than those in Policy Table 1 for Commercial/Industrial use, and the concentration limits for a Utility Worker are not exceeded.

Objections to Closure and Responses

The Regional Water Board, in their Geotracker case review, objects to UST case closure because:

The groundwater impacts at the Site are not defined. RESPONSE: The extent of groundwater contamination is confined near the source area and there are no nearby receptors. The case meets all Policy criteria and does not pose a significant risk to human health.

## Determination

Based on the review performed in accordance with Health & Safety Code Section 25299.39.2 subdivision (a), the Fund Manager has determined that closure of the case is appropriate.

**Recommendation for Closure** 

Based on available information, residual petroleum hydrocarbons at the Site do not pose a significant risk to human health, safety, or the environment, and the case meets the requirements of the Policy. Accordingly, the Fund Manager recommends that the case be closed. The State Water Board is conducting public notification as required by the Policy. Orange County has the regulatory responsibility to supervise the abandonment of monitoring wells.

Lisa Babcock, P.G. 3939, C.E.G. 1235

Prepared by: Mark Owens, P.E.

## ATTACHMENT 1: COMPLIANCE WITH STATE WATER BOARD POLICIES AND STATE LAW

The case complies with the State Water Resources Control Board policies and state law. Section 25296.10 of the Health and Safety Code requires that sites be cleaned up to protect human health, safety, and the environment. Based on available information, any residual petroleum constituents at the Site do not pose significant risk to human health, safety, or the environment.

The case complies with the requirements of the Low-Threat Underground Storage Tank (UST) Case Closure Policy as described below.<sup>1</sup>

Is corrective action consistent with Chapter 6.7 of the Health and Safety Code and implementing regulations?  The corrective action provisions contained in Chapter 6.7 of the Health and Safety Code and the implementing regulations govern the entire corrective action process at leaking UST sites. If it is determined, at any stage in the corrective action process, that UST site closure is appropriate, further compliance with corrective action requirements is not necessary. Corrective action at this site has been consistent with Chapter 6.7 of the Health and Safety Code and implementing regulations and, since this case meets applicable case-closure requirements, further corrective action is not necessary, unless the activity is necessary for case closure.	☑ Yes □ No
Have waste discharge requirements or any other orders issued pursuant to Division 7 of the Water Code been issued at this case?	□ Yes ☒ No
If so, was the corrective action performed consistent with any order?	□ Yes □ No ☒ NA
General Criteria General criteria that must be satisfied by all candidate sites:	*
Is the unauthorized release located within the service area of a public water system?	Yes □ No
Does the unauthorized release consist only of petroleum?	☑ Yes □ No
Has the unauthorized ("primary") release from the UST system been stopped?	☑ Yes □ No
Has free product been removed to the maximum extent practicable?	□ Yes □ No ℤ NA
Has a conceptual site model that assesses the nature, extent, and mobility of the release been developed?	☑ Yes □ No

<sup>&</sup>lt;sup>1</sup> Refer to the Low-Threat Underground Storage Tank Case Closure Policy for closure criteria for low-threat petroleum UST sites. http://www.waterboards.ca.gov/board\_decisions/adopted\_orders/resolutions/2012/rs2012\_0016atta.pdf

Orange Avenue Assoc. 2540 South Orange, Santa Ana Claim No: 9792

Has secondary source been removed to the extent practicable?	☑ Yes □ No
Has soil or groundwater been tested for MTBE and results reported in accordance with Health and Safety Code Section 25296.15?	☑ Yes □ No
Nuisance as defined by Water Code section 13050 does not exist at the Site?	☑ Yes □ No
Are there unique site attributes or site-specific conditions that demonstrably increase the risk associated with residual petroleum constituents?	□ Yes ☒ No
Media-Specific Criteria Candidate sites must satisfy all three of these media-specific criteria:	an an
1. Groundwater: To satisfy the media-specific criteria for groundwater, the contaminant plume that exceeds water quality objectives must be stable or decreasing in areal extent, and meet all of the additional characteristics of one of the five classes of sites:	
Is the contaminant plume that exceeds water quality objectives stable or decreasing in areal extent?	▼ Yes □ No □ NA
Does the contaminant plume that exceeds water quality objectives meet all of the additional characteristics of one of the five classes of sites?	☑ Yes □ No □ NA
If YES, check applicable class: ☑ 1 □ 2 □ 3 □ 4 □ 5	
For sites with releases that have not affected groundwater, do mobile constituents (leachate, vapors, or light non-aqueous phase liquids) contain sufficient mobile constituents to cause groundwater to exceed the groundwater criteria?	□ Yes □ No ☒ NA
	* *
2. Petroleum Vapor Intrusion to Indoor Air: The site is considered low-threat for vapor intrusion to indoor air if site-specific conditions satisfy all of the characteristics of one of the three classes of sites (a through c) or if the exception for active commercial fueling facilities applies.	
Is the Site an active commercial petroleum fueling facility?  Exception: Satisfaction of the media-specific criteria for petroleum vapor intrusion to indoor air is not required at active commercial petroleum fueling facilities, except in cases where release characteristics can be reasonably believed to pose an unacceptable health risk.	□ Yes ☑ No
a. Do site-specific conditions at the release site satisfy all of the applicable characteristics and criteria of scenarios 1 through 3 or all of the applicable characteristics and criteria of scenario 4?	□Yes □ No ☑ NA

If YES, check applicable scenarios: □ 1 □ 2 □ 3 □ 4	
b. Has a site-specific risk assessment for the vapor intrusion pathw been conducted and demonstrates that human health is protecte the satisfaction of the regulatory agency?	yay ed to ☑ Yes ☐ No ☐ NA
c. As a result of controlling exposure through the use of mitigation measures or through the use of institutional or engineering controls, has the regulatory agency determined that petroleum vapors migrating from soil or groundwater will have no significant risk of adversely affecting human health?	103 110 110
3. Direct Contact and Outdoor Air Exposure: The Site is considered low-threat for direct contact and outdoor air exposure if site-specific conditions satisfy one of the three classes of sites (a throug c).	ure h
a. Are maximum concentrations of petroleum constituents in soil le than or equal to those listed in Table 1 for the specified depth bel ground surface (bgs)?	ss ow Yes □ No □ NA
b. Are maximum concentrations of petroleum constituents in soil le than levels that a site specific risk assessment demonstrates will have no significant risk of adversely affecting human health?	ss □ Yes □ No ☒ NA
c. As a result of controlling exposure through the use of mitigation measures or through the use of institutional or engineering controls, has the regulatory agency determined that the concentrations of petroleum constituents in soil will have no significant risk of adversely affecting human health?	□ Yes □ No 丞 NA

Orange Avenue Assoc. 2540 South Orange, Santa Ana

Claim No: 9792

## ATTACHMENT 2: SUMMARY OF BASIC CASE INFORMATION (Conceptual Site Model)

Site Location/History

This case is located side mid-block on the west South Orange Avenue between East Adams Street and Goetz Avenue and is an active warehouse type structure.

The Site is bounded by a commercial storage facility to the west, a single set of railroad tracks to the northwest and north with commercial and residential on the other side, commercial and residential to the east across Orange Avenue and south.

Site maps showing the location of the former UTSs, excavation area and monitoring wells are provided at the end of this closure review summary (EnGen Corporation, 1999 and 2012).

Nature of Contaminants of Concern: Petroleum hydrocarbons only.

Source: UST system.

 Date reported: November 1994. Status of Release: USTs removed.

Free Product: None reported.

### Tank Information

k Information Tank No.	Size in Gallons	Contents	Closed in Place/ Removed/Active	Date	
1	2.000	Diesel	Removed	July 1994	
2	2,000	Gasoline	Removed	July 1994	

#### Receptors

- GW Basin: Coastal Plain of Orange County.
- Beneficial Uses: GeoTracker lists Municipal and Domestic Supply, Industrial Process Supply, Industrial Service Water Supply and Agricultural Supply.
- Land Use Designation: Aerial photograph available on GeoTracker indicates commercial/industrial land use in the vicinity of the Site.
- Public Water System: Metropolitan Water of Southern California.
- Distance to Nearest Supply Well: According to data available in GeoTracker, there are no public supply wells regulated by the California Department of Public Health within 250 feet of the defined plume boundary. No other water supply wells were identified within 250 feet of the defined plume boundary in the files reviewed.
- Distance to Nearest Surface Water: There is no identified surface water within 250 feet of the defined plume boundary.

## Geology/Hydrogeology

- Stratigraphy: The Site is underlain by interbedded and intermixed sand, silt, and clay.
- Maximum Sample Depth: 25 feet below ground surface (bgs).
- Minimum Groundwater Depth: 6.63 feet bgs at monitoring well MW-4.
- Maximum Groundwater Depth: 8.58 feet bgs at monitoring well MW-3.
- Current Average Depth to Groundwater: Approximately 8.30 feet bgs.
- Saturated Zones(s) Studied: Approximately 5 25 feet bgs.
- Appropriate Screen Interval: Submerged well screens in MW-1 through MW-4.
- Groundwater Flow Direction: Northeast with an average gradient of 0.003 feet/foot (November 2011). During the June 2011 monitoring event however, the flow direction was towards the south-southwest.

**Monitoring Well Information** 

Well Designation	Date Installed	Screen Interval (feet bgs)	Depth to Water (feet bgs)	
MVV-1	October 1999	20-25	8.39 (11/10/11)	
MW-2	May 2011	15-25	8.22 (11/10/11)	
MW-3	May 2011	15-25	8.58 (11/10/11)	
MW-4	May 2011	15-25	6.89 (11/10/11)	
MW-5	May 2012	5-15	9.00 (5/26/12)	
MW-6	May 2012	5-15	9.00 (5/26/12)	

## **Remediation Summary**

- Free Product: None reported.
- Soil Excavation: Approximately 400 tons of impacted soil were excavated and disposed offsite in 1994. Excavated area was replaced with clean fill and then paved with asphalt.
- In-Situ Soil Remediation: None.Groundwater Remediation: None.

Most Recent Concentrations of Petroleum Constituents in Soil

Constituent	Maximum 0-5 feet bgs [mg/kg and (date)]	Maximum 5-10 feet bgs [mg/kg and (date)]		
Benzene	ND @ 5 in MW-3 (5/26/2011)	ND @ 10 in MW-3 (5/26/2011)		
Ethylbenzene	ND @ 5 in MW-3 (5/26/2011)	6.62 (5/26/2011)		
Naphthalene	ND @ 5 in MW-3 (5/26/2011)	ND @ 10 in MW-3 (5/26/2011)		
PAHs	NÁ	NA		

NA: Not Analyzed, Not Applicable or Data Not Available

ND: Non-detect

mg/kg: Milligrams per kilogram, parts per million <: Not detected at or above stated reporting limit

PAHs: Polycyclic aromatic hydrocarbons

Most Recent Concentrations of Petroleum Constituents in Groundwater

Sample	Sample Date	TPHg (µg/L)	Benzene (µg/L)	Toluene (µg/L)	Ethyl- Benzene (µg/L)	Xylenes (μg/L)	MTBE (µg/L)	Naphthalene (μg/L)
MW-1	5/26/2012	361	74	<5	18	17.8	44	<5
MW-2	6/6/2011	<50	<1	<5	<5	<5	<1	<5
MW-3	6/6/2011	399	<1	<1	<5	20	<1	18
MW-4	6/6/2011	<50	<1	<5	<5	<5	<1	<5
MW-5	5/26/2012	20,600	6,200	<5	930	<5	3,500	<5
MW-6	5/26/2012	686	6	<1	<5	<5	600	<5
WQOs	**		1	150	300	1,750	5 <sup>a</sup>	

μg/L: Micrograms per liter, parts per billion

Not detected at or above stated reporting limit TPHg: Total petroleum hydrocarbons as gasoline

MTBE: Methyl tert-butyl ether TBA: Tert-butyl alcohol

WQOs: Water Quality Objectives, Santa Ana Regional Water Quality Control Board Basin Plan.


-: Regional Water Board Basin Plan does not have a numeric water quality objective for TPHg and Naphthalene.

a: Secondary maximum contaminant level (MCL)

Orange Avenue Assoc. 2540 South Orange, Santa Ana Claim No: 9792


#### **Groundwater Trends**

Since 1999, six groundwater monitoring wells have been installed and irregularly monitored.
 Benzene trends in well MW-1, which is located between the former UST excavation and the building, is shown below:




## **Evaluation of Current Risk**

- Estimate of Hydrocarbon Mass in Soil: None reported.
- Soil/Groundwater tested for methyl tert-butyl ether (MTBE): Yes, see table above.
- Oxygen Concentrations in Soil Vapor: None reported.
- Plume Length: <100 feet long.</li>
- Plume Stable or Decreasing: Yes.
- Contaminated Zone(s) Used for Drinking Water: No.
- Groundwater Risk from Residual Petroleum Hydrocarbons: The case meets Policy Criterion 1 by Class 1. The plume that exceeds water quality objectives is less than 100 feet in length.
  There is no free product. The nearest water supply well or surface water body is greater than 250 feet from the defined plume boundary.
- Indoor Vapor Risk from Residual Petroleum Hydrocarbons: The case meets Policy Criterion 2b. Although no document titled "Risk Assessment" was located in the files reviewed, a professional assessment of site-specific risk from exposure through the vapor intrusion pathway shows that maximum concentrations of petroleum constituents will have no significant risk of adversely affecting human health. The building where monitoring well MW-5 is reporting high groundwater benzene concentration has floors covered by 3 to 4 inch of concrete which restricts the potential for vapor intrusion to indoor air. In addition, the building houses electric motor and other heavy machinery shops. Such working environment requires sufficient ventilation and other safety measures to mitigate harmful exhaust and dust. These added measures also mitigate any vapor intrusion to indoor air risk from the groundwater benzene impact.
- Direct Contact Risk from Residual Petroleum Hydrocarbons: The case meets Policy Criterion
   3a. Maximum concentrations in soil are less than those in Policy Table 1 for
   Commercial/Industrial use, and the concentration limits for a Utility Worker are not exceeded.



Claim No: 9792



Page 10 of 10