# STATE OF CALIFORNIA STATE WATER RESOURCES CONTROL BOARD

## ORDER WQ 2014-0069 - UST

## In the Matter of Underground Storage Tank Case Closure

Pursuant to Health and Safety Code Section 25299.39.2 and the Low Threat Underground Storage Tank Case Closure Policy

# BY THE EXECUTIVE DIRECTOR1.

Pursuant to Health and Safety Code section 25299.39.2, the Manager of the Underground Storage Tank Cleanup Fund (Fund) recommends closure of the underground storage tank (UST) case at the site listed below.<sup>2</sup> The name of the Fund claimant, the Fund claim number, the site name and the applicable site address are as follows:

Bill and Sylvia Wilson Trust Claim No. 11829 Melody Toyota 750 El Camino Real, San Bruno

## San Mateo County Environmental Health Division

#### I. STATUTORY AND PROCEDURAL BACKGROUND

Section 25299.39.2 directs the Fund manager to review the case history of claims that have been active for five years or more (five-year review), unless there is an objection from the UST owner or operator. This section further authorizes the Fund Manager to make recommendations to the State Water Resources Control Board (State Water Board) for closure of a five-year-review case if the UST owner or operator approves. In response to a recommendation by the Fund Manager, the State Water Board, or in certain cases the State Water Board Executive Director, may close a case or require the closure of a UST case. Closure of a UST case is appropriate where the corrective action ensures the protection of human health, safety, and the environment and where the corrective action is consistent with:

<sup>&</sup>lt;sup>1</sup> State Water Board Resolution No. 2012-0061 delegates to the Executive Director the authority to close or require the closure of any UST case if the case meets the criteria found in the State Water Board's Low Threat Underground Storage Tank Case Closure Policy adopted by State Water Board Resolution No. 2012-0016.

<sup>&</sup>lt;sup>2</sup> Unless otherwise noted, all references are to the Health and Safety Code.

- 1) Chapter 6.7 of Division 20 of the Health and Safety Code and implementing regulations;
- 2) Any applicable waste discharge requirements or other orders issued pursuant to Division 7 of the Water Code; 3) All applicable state policies for water quality control; and 4) All applicable water quality control plans.

The Fund Manager has completed a five-year review of the UST case identified above, and recommends that this case be closed. The recommendation is based upon the facts and circumstances of this particular UST case. A UST Case Closure Review Summary Report has been prepared for the case identified above and the bases for determining compliance with the Water Quality Control Policy for Low-Threat Underground Storage Tank Case Closures (Low-Threat Closure Policy or Policy) are explained in the Case Closure Review Summary Report.

## A. Low-Threat Closure Policy

In State Water Board Resolution No. 2012-0016, the State Water Board adopted the Low Threat Closure Policy. The Policy became effective on August 17, 2012. The Policy establishes consistent statewide case closure criteria for certain low-threat petroleum UST sites. In the absence of unique attributes or site-specific conditions that demonstrably increase the risk associated with residual petroleum constituents, cases that meet the general and media-specific criteria in the Low-Threat Closure Policy pose a low threat to human health, safety and the environment and are appropriate for closure under Health and Safety Code section 25296.10. The Policy provides that if a regulatory agency determines that a case meets the general and media-specific criteria of the Policy, then the regulatory agency shall notify responsible parties and other specified interested persons that the case is eligible for case closure. Unless the regulatory agency revises its determination based on comments received on the proposed case closure, the Policy provides that the agency shall issue a closure letter as specified in Health and Safety Code section 25296.10. The closure letter may only be issued after the expiration of the 60-day comment period, proper destruction or maintenance of monitoring wells or borings, and removal of waste associated with investigation and remediation of the site.

Health and Safety Code section 25299.57, subdivision (I)(1) provides that claims for reimbursement of corrective action costs that are received by the Fund more than 365 days after the date of a closure letter or a Letter of Commitment, whichever occurs later, shall not be reimbursed unless specified conditions are satisfied. A Letter of Commitment has already been issued on the claim subject to this order and the respective Fund claimant, so the 365-day timeframe for the submittal of claims for corrective action costs will start upon the issuance of the closure letter.

#### **II. FINDINGS**

Based upon the UST Case Closure Review Summary Report prepared for the case attached hereto, the State Water Board finds that corrective action taken to address the unauthorized release of petroleum at the UST release site identified as:

Claim No. 11829 Melody Toyota

ensures protection of human health, safety and the environment and is consistent with Chapter 6.7 of Division 20 of the Health and Safety Code and implementing regulations, the Low-Threat Closure Policy and other water quality control policies and applicable water quality control plans.

Pursuant to the Low-Threat Closure Policy, notification has been provided to all entities that are required to receive notice of the proposed case closure, a 60-day comment period has been provided to notified parties, and any comments received have been considered by the Board in determining that the case should be closed.

Pursuant to section 21080.5 of the Public Resources Code, environmental impacts associated with the adoption of this Order were analyzed in the substitute environmental document (SED) the State Water Board approved on May 1, 2012. The SED concludes that all environmental effects of adopting and implementing the Low threat Closure Policy are less than significant, and environmental impacts as a result of complying with the Policy are no different from the impacts that are reasonably foreseen as a result of the Policy itself. A Notice of Decision was filed August 17, 2012. No new environmental impacts or any additional reasonably foreseeable impacts beyond those that were not addressed in the SED will result from adopting this Order.

The UST case identified above may be the subject of orders issued by the Regional Water Quality Control Board (Regional Water Board) pursuant to Division 7 of the Water Code. Any orders that have been issued by the Regional Water Board pursuant to Division 7 of the Water Code, or directives issued by a Local Oversight Program agency for this case should be rescinded to the extent they are inconsistent with this Order.

#### III. ORDER

#### IT IS THEREFORE ORDERED that:

- A. The UST case identified in Section II of this Order, meeting the general and mediaspecific criteria established in the Low-Threat Closure Policy, be closed in accordance with the following conditions and after the following actions are complete. Prior to the issuance of a closure letter, the Fund claimant is ordered to:
  - 1. Properly destroy monitoring wells and borings unless the owner of real property on which the well or boring is located certifies that the wells or borings will be maintained in accordance with local or state requirements;
  - 2. Properly remove from the site and manage all waste piles, drums, debris, and other investigation and remediation derived materials in accordance with local or state requirements; and
  - 3. Within six months of the date of this Order, submit documentation to the regulatory agency overseeing the UST case identified in Section II of this Order that the tasks in subparagraphs (1) and (2) have been completed.
- B. The tasks in subparagraphs (1) and (2) of paragraph (A) are ordered pursuant to Health and Safety Code section 25296.10 and failure to comply with these requirements may result in the imposition of civil penalties pursuant to Health and Safety Code section 25299, subdivision (d)(1). Penalties may be imposed administratively by the State Water Board or Regional Water Board.
- C. Within 30 days of receipt of proper documentation from the Fund claimant that requirements in subparagraphs (1) and (2) of paragraph (A) are complete, the regulatory agency that is responsible for oversight of the UST case identified in Section II of this Order shall notify the State Water Board that the tasks have been satisfactorily completed.
- D. Within 30 days of notification from the regulatory agency that the tasks are complete pursuant to paragraph (C), the Deputy Director of the Division of Financial Assistance shall issue a closure letter consistent with Health and Safety Code section 25296.10,

subdivision (g) and upload the closure letter and UST Case Closure Review Summary Report to GeoTracker.

- E. As specified in Health and Safety Code section 25299.39.2, subdivision (a) (2), corrective action costs incurred after a recommendation of closure shall be limited to \$10,000 per year unless the Board or its delegated representative agrees that corrective action in excess of that amount is necessary to meet closure requirements, or additional corrective actions are necessary pursuant to section 25296.10, subdivisions (a) and (b). Pursuant to section 25299.57, subdivision (I) (1), and except in specified circumstances, all claims for reimbursement of corrective action costs must be received by the Fund within 365 days of issuance of the closure letter in order for the costs to be considered.
- F. Any Regional Water Board or Local Oversight Program Agency directive or order that directs corrective action or other action inconsistent with case closure for the UST case identified in Section II is rescinded, but only to the extent the Regional Water Board order or Local Oversight Program Agency directive is inconsistent with this Order.

**Executive Director** 





#### **State Water Resources Control Board**

## **UST CASE CLOSURE REVIEW SUMMARY REPORT**

**Agency Information** 

Agency Name: San Mateo County Environmental Health Division (County)	Address: 2000 Alameda de las Pulgas, Ste.100 San Mateo, CA 94403
Agency Caseworker: Jacob Madden	Case No: 880039

#### **Case Information**

USTCF Claim No.: 11829	Global ID: T0608100890		
Site Name: Melody Toyota	Site Address: 750 El Camino Real		
5	San Bruno, CA 92680		
Responsible Party: Bill & Sylvia Wilson Trust	Address: 3466 Twin Oaks Ct		
c/o Dave Wilson	Napa, CA 94558		
USTCF Expenditures to Date: \$266,739	Number of Years Case Open: 25		

URL: <a href="http://geotracker.waterboards.ca.gov/profile">http://geotracker.waterboards.ca.gov/profile</a> report.asp?global id=T0608100890

#### Summary

The Low-Threat Underground Storage Tank Case Closure Policy (Policy) contains general and media-specific criteria, and cases that meet those criteria are appropriate for closure pursuant to the Policy. This case meets all of the required criteria of the Policy. A summary evaluation of compliance with the Policy is shown in **Attachment 1: Compliance with State Water Board Policies and State Law**. The Conceptual Site Model upon which the evaluation of the case has been made is described in **Attachment 2: Summary of Basic Case Information (Conceptual Site Model).** Highlights of the case follow:

An unauthorized release was reported in August 1987. In July 1996, one gasoline and three waste oil USTs were removed and an unknown volume of soil was excavated. Since 1987, eleven monitoring wells were installed and monitored. According to groundwater data, water quality objectives have been achieved or nearly achieved for all petroleum hydrocarbon constituents except benzene.

The petroleum release is limited to the soil and shallow groundwater. According to data available in GeoTracker, there are no supply wells regulated by the California Department of Public Health or surface water bodies within 250 feet of the defined plume boundary. No other water supply wells have been identified within 250 feet of the defined plume boundary in files reviewed. Water is provided to water users near the Site by the City of San Bruno. The affected groundwater is not currently being used as a source of drinking water, and it is highly unlikely that the affected groundwater will be used as a source of drinking water in the foreseeable future. Other designated beneficial uses of impacted groundwater are not threatened, and it is highly unlikely that they will be, considering these factors in the context of the site setting. Remaining petroleum hydrocarbon constituents are limited and stable, and concentrations are decreasing.

Corrective actions have been imple

Corrective actions have been implemented and additional corrective actions are not necessary. Any remaining petroleum hydrocarbon constituents do not pose a significant risk to human health, safety or the environment.

## Rationale for Closure under the Policy

- General Criteria: The case meets all eight Policy general criteria.
- Groundwater Specific Criteria: The case meets Policy Criterion 1 by Class 1. The
  contaminant plume that exceeds water quality objectives is less than 100 feet in length.
  There is no free product. The nearest water supply well or surface water body is greater
  than 250 feet from the defined plume boundary.
- Vapor Intrusion to Indoor Air: The case meets Policy Criterion 2a by Scenario 3a. The
  maximum benzene concentration in groundwater is less than 100 µg/L. The minimum
  depth to groundwater is greater than 5 feet, overlain by soil containing less than 100 mg/kg
  of TPH.
- Direct Contact and Outdoor Air Exposure: The case meets Policy Criterion 3a. Maximum concentrations in soil are less than those in Policy Table 1 for Commercial/Industrial use, and the concentration limits for a Utility Worker are not exceeded. There are no soil sample results in the case record for naphthalene. However, the relative concentration of naphthalene in soil can be conservatively estimated using the published relative concentrations of naphthalene and benzene in gasoline. Taken from Potter and Simmons (1998), gasoline mixtures contain approximately 2 percent benzene and 0.25 percent naphthalene. Therefore, benzene can be directly substituted for naphthalene concentrations with a safety factor of eight. Benzene concentrations from the Site are below the naphthalene thresholds in Policy Table 1. Therefore, the estimated naphthalene concentrations meet the thresholds in Table 1 and the Policy criteria for direct contact by a factor of eight. It is highly unlikely that naphthalene concentrations in the soil, if any, exceed the threshold.

## **Objections to Closure and Responses**

In correspondence dated May 3, 2012, the County denied an April 2012 request to close this site. The County objected to closure because:

The County believes that free product in monitoring well MW-3A had not been removed and that it would allow closure contingent on the recording of a deed restriction.
 <u>RESPONSE</u>: In the April 24, 2012, Groundwater Monitoring Report it was observed that no measurable free-product had been encountered in monitoring well MW-3A since the first quarter of 2009. The case meets all Policy criteria. No deed restriction is necessary.

In a telephone conversation on June 6, 2013, and an email correspondence the same day, the County stated that:

- The free product had not been removed to the extent practicable in compliance with federal law.
  - RESPONSE: No free product has been reported since the first guarter of 2009.
- The County is unwilling to close the case without a deed restriction requiring future remediation under the existing building in the event that the building is removed. RESPONSE: Secondary source has been removed and residual concentrations are stable and continue to decrease. There is no demonstrated threat to human health. Under the Policy, no further removal or active remedial actions are required. The case meets all Policy criteria. No deed restriction is necessary.

August 2013

#### Determination

Based on the review performed in accordance with Health & Safety Code Section 25299.39.2 subdivision (a), the Fund Manager has determined that closure of the case is appropriate.

## **Recommendation for Closure**

Based on available information, residual petroleum hydrocarbons at the Site do not pose a significant risk to human health, safety, or the environment, and the case meets the requirements of the Policy. Accordingly, the Fund Manager recommends that the case be closed. The State Water Board is conducting public notification as required by the Policy. San Mateo County has the regulatory responsibility to supervise the abandonment of monitoring wells.

Lisa Babcock, P.G. 3939, C.E.G. 1235

Prepared by: Walter Bahm

Claim No: 11829

## ATTACHMENT 1: COMPLIANCE WITH STATE WATER BOARD POLICIES AND STATE LAW

The case complies with the State Water Resources Control Board policies and state law. Section 25296.10 of the Health and Safety Code requires that sites be cleaned up to protect human health, safety, and the environment. Based on available information, any residual petroleum constituents at the site do not pose significant risk to human health, safety, or the environment.

The case complies with the requirements of the Low-Threat Underground Storage Tank (UST) Case Closure Policy as described below.<sup>1</sup>

Is corrective action consistent with Chapter 6.7 of the Health and Safety Code and implementing regulations?  The corrective action provisions contained in Chapter 6.7 of the Health and Safety Code and the implementing regulations govern the entire corrective action process at leaking UST sites. If it is determined, at any stage in the corrective action process, that UST site closure is appropriate, further compliance with corrective action requirements is not necessary. Corrective action at this site has been consistent with Chapter 6.7 of the Health and Safety Code and implementing regulations and, since this case meets applicable case-closure requirements, further corrective action is not necessary, unless the activity is necessary for case closure.	☑ Yes □ No
Have waste discharge requirements or any other orders issued pursuant to Division 7 of the Water Code been issued at this case?	□ Yes ☒ No
If so, was the corrective action performed consistent with any order?	□ Yes □ No ☒ NA
General Criteria General criteria that must be satisfied by all candidate sites:	
Is the unauthorized release located within the service area of a public water system?	☑ Yes □ No
Does the unauthorized release consist only of petroleum?	☑ Yes □ No
Has the unauthorized ("primary") release from the UST system been stopped?	☑ Yes □ No
Has free product been removed to the maximum extent practicable?	☑ Yes □ No □ NA
Has a conceptual site model that assesses the nature, extent, and mobility of the release been developed?	☑ Yes □ No

<sup>&</sup>lt;sup>1</sup> Refer to the Low-Threat Underground Storage Tank Case Closure Policy for closure criteria for low-threat petroleum UST sites. http://www.waterboards.ca.gov/board\_decisions/adopted\_orders/resolutions/2012/rs2012\_0016atta.pdf

Has secondary source been removed to the extent practicable?	☑ Yes □ No
Has soil or groundwater been tested for MTBE and results reported in accordance with Health and Safety Code Section 25296.15?	☑ Yes □ No
Nuisance as defined by Water Code section 13050 does not exist at the site?	☑ Yes □ No
Are there unique site attributes or site-specific conditions that demonstrably increase the risk associated with residual petroleum constituents?	□ Yes । No
Media-Specific Criteria Candidate sites must satisfy all three of these media-specific criteria:	
1. Groundwater:  To satisfy the media-specific criteria for groundwater, the contaminant plume that exceeds water quality objectives must be stable or decreasing in areal extent, and meet all of the additional characteristics of one of the five classes of sites:	GEG
Is the contaminant plume that exceeds water quality objectives stable or decreasing in areal extent?	☑ Yes □ No □ NA
Does the contaminant plume that exceeds water quality objectives meet all of the additional characteristics of one of the five classes of sites?	☑ Yes □ No □ NA
If YES, check applicable class: ② 1 □ 2 □ 3 □ 4 □ 5  For sites with releases that have not affected groundwater, do mobile constituents (leachate, vapors, or light non-aqueous phase liquids) contain sufficient mobile constituents to cause groundwater to exceed the groundwater criteria?	□ Yes □ No ☒ NA
2. Petroleum Vapor Intrusion to Indoor Air:  The site is considered low-threat for vapor intrusion to indoor air if site-specific conditions satisfy all of the characteristics of one of the three classes of sites (a through c) or if the exception for active commercial fueling facilities applies.	
Is the site an active commercial petroleum fueling facility?  Exception: Satisfaction of the media-specific criteria for petroleum vapor intrusion to indoor air is not required at active commercial petroleum fueling facilities, except in cases where release characteristics can be reasonably believed to pose an unacceptable health risk.	□ Yes ☒ No
<ul> <li>a. Do site-specific conditions at the release site satisfy all of the applicable characteristics and criteria of scenarios 1 through 3 or all of the applicable characteristics and criteria of scenario 4?</li> <li>If YES, check applicable scenarios: □ 1 □ 2 ☑ 3 □ 4</li> </ul>	⊠Yes □ No □ NA

	b.	Has a site-specific risk assessment for the vapor intrusion pathway been conducted and demonstrates that human health is protected to the satisfaction of the regulatory agency?	□ Yes □ No ☒ NA
	c.	As a result of controlling exposure through the use of mitigation measures or through the use of institutional or engineering controls, has the regulatory agency determined that petroleum vapors migrating from soil or groundwater will have no significant risk of adversely affecting human health?	□ Yes □ No ☒ NA
E)	Th	Direct Contact and Outdoor Air Exposure: e site is considered low-threat for direct contact and outdoor air exposure if e-specific conditions satisfy one of the three classes of sites (a through c).	
	a.	Are maximum concentrations of petroleum constituents in soil less than or equal to those listed in Table 1 for the specified depth below ground surface (bgs)?	Yes □ No □ NA
	b.	Are maximum concentrations of petroleum constituents in soil less than levels that a site specific risk assessment demonstrates will have no significant risk of adversely affecting human health?	□ Yes □ No ☒ NA
	c.	As a result of controlling exposure through the use of mitigation measures or through the use of institutional or engineering controls, has the regulatory agency determined that the concentrations of petroleum constituents in soil will have no significant risk of adversely affecting human health?	□ Yes □ No 丞 NA

Claim No: 11829

# ATTACHMENT 2: SUMMARY OF BASIC CASE INFORMATION (Conceptual Site Model)

## Site Location/History

- This Site is an auto dealership and is bounded by businesses across El Camino Real to the
  west, a commercial petroleum fueling facility to the north, a church across Hensley Avenue
  to the east, and businesses to the south.
- Mill's Park Cleaners, dry cleaning facility is upgradient of the Site.
- A Site map showing the location of the current and former USTs, monitoring wells, and groundwater level contours is provided at the end of this closure review summary (Gribi & Associates, 2012).
- Nature of Contaminants of Concern: Petroleum hydrocarbons and chlorinated solvents, unrelated to the Site.
- Source: UST System.
- Date reported: August 1987.
- Status of Release: USTs removed.

#### **Tank Information**

Tank No.	Size in Gallons	Contents	Closed in Place/ Removed/Active	Date
1	500	Gasoline	Removed	April 1996
2	300	Waste Oil	Removed	April 1996
3	300	Waste Oil	Removed	April 1996

#### Receptors

- GW Basin: Westside.
- Beneficial Uses: The San Francisco Regional Water Quality Control Board (Regional Water Board) Basin Plan lists agricultural, municipal, domestic and industrial supply.
- Land Use Designation: Commercial and industrial.
- Public Water System: City of San Bruno, Water and Sewer Department.
- Distance to Nearest Supply Well: According to data available in GeoTracker, there are no
  public supply wells regulated by the California Department of Public Health within 250 feet
  of the defined plume boundary. No other water supply wells were identified within 250 feet
  of the defined plume boundary in the files reviewed.
- Distance to Nearest Surface Water: There is no identified surface water within 250 feet of the defined plume boundary.

## Geology/Hydrogeology

- Stratigraphy: The Site is underlain by sand clay and silty sand.
- Maximum Sample Depth: 20 feet below ground surface (bgs).
- Minimum Groundwater Depth: 8.50 feet bgs at monitoring well MW-6.
- Maximum Groundwater Depth: 15.13 feet bgs at monitoring well MW-7.
- Current Average Depth to Groundwater: Approximately 13 feet bgs.
- Saturated Zones(s) Studied: Approximately 8-20 feet bgs.
- Appropriate Screen Interval: Yes.
- Groundwater Flow Direction: Variable, but generally northeast with an average gradient of 0.001 feet/foot (Gribi, April 2012).

Melody Toyota

750 El Camino Real, San Bruno

Claim No: 11829

**Monitoring Well Information** 

Well Designation	Date Installed	Screen Interval (feet bgs)	Depth to Water (feet bgs) (02/08/12)	
MW-1	January 1997	6-10	Destroyed	
MW-2	January 1997	5-10	Destroyed	
MW-3	January 1997	5-10	Destroyed	
MW-3A	January 2007	5-20	12.62	
MW-4A	March 2007	5-20	12.75	
MW-5A	March 2007	5-20	12.91	
MW-6	October 2005	5-20	11.55	
MW-7	October 2005	5-20	14.04	
MW-8	October 2005	5-20	13.57	

NM: Not measured

# **Remediation Summary**

- Free Product: Historically free product was reported in MW-3 (up to 0.39 feet). No measurable free product noted since 2009.
- Soil Excavation: An unknown volume of soils excavated during the 1996 UST removal.
- In-Situ Soil Remediation: Soil vapor extraction test performed on Site wells VP-1 and VP-6 in 1996.
- · Groundwater Remediation: None reported.

#### Most Recent Concentrations of Petroleum Constituents in Soil

Constituent	Maximum 0-5 feet bgs [mg/kg (date)]	Maximum 5-10 feet bgs [mg/kg (date)]		
Benzene	<0.01 (05/12/03)	< 0.005 (05/12/03)		
Ethylbenzene	0.161 (05/12/03)	0.036 (05/12/03)		
Naphthalene	NA	NA		
PAHs	NA	NA		

NA: Not Analyzed, Not Applicable or Data Not Available

mg/kg: milligrams per kilogram, parts per million <: Not detected at or above stated reporting limit

PAHs: Polycyclic aromatic hydrocarbons

Claim No: 11829

Most Recent Concentrations of Petroleum Constituents in Groundwater

[Sample	Sample Date	TPHg (µg/L)	Benzene (µg/L)	Toluene (µg/L)	Ethyl- Benzene (μg/L)	Xylenes (μg/L)	MTBE (µg/L)	TBA (µg/L)
MW-3A	02/08/12	82	1.2	0.68	< 0.5	<1	<1	<10
MW-4A	02/08/12	2,500	<0.5	0.75	<0.5	<1	<1	<10
MW-5A	02/08/12	4,100	1.9	0.57	<0.5	<1	<1	<10
MVV-6	02/08/12	330	<0.5	<0.5	<0.5	<1	<1	<10
MW-7	02/08/12	1,600	<0.5	0.77	<0.5	<1	<1	<10
MW-8	02/08/12	1,200	<0.5	<0.5	<0.5	<1	<1	<10
WQOs	_ = = =		1	150	300	1,750	5	1,200 <sup>b</sup>

NA: Not Analyzed, Not Applicable or Data Not Available

μg/L: micrograms per liter, parts per billion

<: Not detected at or above stated reporting limit TPHg: Total petroleum hydrocarbons as gasoline

MTBE: Methyl tert-butyl ether TBA: Tert-butyl alcohol


WQOs: Water Quality Objectives, Regional Water Board Basin Plan

--: Regional Water Board Basin Plan does not have a numeric WQO value for TPHg b: California Department of Public Health, Response Level

#### **Groundwater Trends**

Since 1997 groundwater has been regularly monitored at this Site. The TPHg detections in site monitoring wells have been attributed to the presence of the chlorinated solvents associated with the upgradient dry cleaners (Gribi, July 2012). Benzene trends are shown below: Source area (MW-3A), near downgradient (MW-5A), and far downgradient (MW-7).

## Source Area Well




750 El Camino Real, San Bruno


Claim No: 11829

Melody Toyota

**Near Downgradient Well** 



**Downgradient Well** 



## **Evaluation of Current Risk**

- Estimate of Hydrocarbon Mass in Soil: None reported.
- Soil/Groundwater tested for methyl tertiary-butyl ether (MTBE): Yes, see table above.
- Oxygen Concentrations in Soil Vapor: None reported.
- Plume Length: <100 feet.
- Plume Stable or Decreasing: Yes.
- Contaminated Zone(s) Used for Drinking Water: No.
- Groundwater Risk from Residual Petroleum Hydrocarbons: The case meets Policy Criterion 1 by Class 1. The contaminant plume that exceeds water quality objectives is less than 100 feet in length. There is no free product. The nearest water supply well or surface water body is greater than 250 feet from the defined plume boundary.

Claim No: 11829

• Indoor Vapor Risk from Residual Petroleum Hydrocarbons: The case meets Policy Criterion 2a by Scenario 3a. The maximum benzene concentration in groundwater is less than 100 μg/L. The minimum depth to groundwater is greater than 5 feet, overlain by soil containing less than 100 mg/kg of TPH.

• Direct Contact Risk from Residual Petroleum Hydrocarbons: The case meets Policy Criterion 3a. Maximum concentrations in soil are less than those in Policy Table 1 for Commercial/Industrial use, and the concentration limits for a Utility Worker are not exceeded. There are no soil sample results in the case record for naphthalene. However, the relative concentration of naphthalene in soil can be conservatively estimated using the published relative concentrations of naphthalene and benzene in gasoline. Taken from Potter and Simmons (1998), gasoline mixtures contain approximately 2 percent benzene and 0.25 percent naphthalene. Therefore, benzene can be directly substituted for naphthalene concentrations with a safety factor of eight. Benzene concentrations from the Site are below the naphthalene thresholds in Policy Table 1. Therefore, the estimated naphthalene concentrations meet the thresholds in Table 1 and the Policy criteria for direct contact by a factor of eight. It is highly unlikely that naphthalene concentrations in the soil, if any, exceed the threshold.

Claim No: 11829

DEALERSHIP PARKING LOT MW-8 (+21.77) MW-5A (+22.37) MW-6 (+23.68) MW-4A (+22.68) FORMER GASOLINE USTEXCAVATION +23.00 DEALERSHIP PARKING LOT Existing Monitoring Well DESIGNED BY: CHECKED BY: JEG DATE: 04/24/2012 FIGURE: 3 GROUNDWATER ELEVATIONS AND GRADIENT - 02/08/2012 DRAWN BY: MAR SCALE: MELODY TOYOTA UST SITE 750 EL CAMINO REAL PROJECT NO: SAN BRUNO, CALIFORNIA

Page 12 of 12