

**LEGEND:**

- Monitoring Well
- Domestic Supply Well (active and inactive)
- Other Supply Well
- Groundwater Extraction Well
- Multi-use Test Well, or Inactive Extraction/Injection Well
- ▲ #Z, #J
- ▲ Freshwater Injection Well
- PG&E-Owned Property
- PG&E Compressor Station
- County Parcel
- Approximate Limit of Saturated Alluvium Upper Aquifer
- Approximate Location of Lockhart Fault
- Fault Trace is Inferred, and There is No Surface Expression (Stamos et al. 2011)
- Bedrock Exposed at Ground Surface
- Location is Approximate, Survey Pending

MW-177D Well ID  
1.61E8  
(440470)

Cr(VI)/Cr(T) concentrations in µg/L; maximum of primary and duplicate samples during Second Quarter 2018 sampling. Data in parentheses are from previous reporting period. See Table E-1 for sample dates.

**Groundwater Cr(VI) Concentrations in Monitoring Wells:**

- More than 1,000 µg/L
- 100 to 1,000 µg/L
- 50 to 100 µg/L
- 10 to 50 µg/L
- 3.1 to 10 µg/L
- Less than 3.1 µg/L or ND

**ABBREVIATIONS:**

- µg/L Micrograms per Liter
- Cr(VI) Hexavalent Chromium
- Cr(T) Total Dissolved Chromium
- ND Estimated Result
- ND Not Detected
- NS Not Sampled

**NOTES:**


- Chromium results are shown for Site-wide Groundwater Monitoring Program and domestic wells sampled in the Second Quarter (April through June) 2018 monitoring period. For wells sampled multiple times during the reporting period, the most recent results are shown.
- The concentration outlines are based on Second Quarter 2018 chromium results for the groundwater monitoring and extraction wells that are completed in the shallow zone and deep zone of the Upper Aquifer as noted on Figures S-1 and S-2. Results for domestic wells (brown-colored plume areas) were not used for chromium plume contouring, except for those in the northern dispersed plume areas, pursuant to the Lahontan Regional Water Quality Control Board's Cleanup and Abatement Order dated November 4, 2015 (Water Board 2015).
- Pursuant to the Lahontan Regional Water Quality Control Board's Cleanup and Abatement Order dated November 4, 2015 (Water Board 2015), groundwater monitoring wells are not used for chromium contouring if they are located in the areas southwest of the Lockhart Fault and on or east of Dine Road. Monitoring wells sampled southwest of Lockhart Fault and east of Dine Road were sampled in support of United States Geological Survey background chromium investigations.
- Chromium plume contours in the general area south of Highway 58, were developed using a larger set of monitoring data which is presented in the Second Quarter 2018 Monitoring Report for the In Situ Reactive Zone and Northwest Freshwater Injection Projects (Arcadis 2018). Selected wells from that program are shown here for reference.

**WORK CITED:**

Arcadis. 2018. Second Quarter 2018 Monitoring Report for the In Situ Reactive Zone and Northwest Freshwater Injection Projects. Pacific Gas and Electric Company, Hinkley Compressor Station, Hinkley, California. California Regional Water Quality Control Board, Lahontan Region Order No. RW-2008-001 (Waste Discharge Requirements Identification No. 66369107001), July 30.

Stamos, C.L., P. Martin, T. Nishikawa, and B.F. Cox. 2001. Simulation of Ground-Water Flow in the Mojave River Basin, California U.S. Geological Survey Water-Resources Investigations Report 01-4062, Version 3. Prepared in cooperation with the Mojave Water Agency.

Water Board. 2015. Cleanup and Abatement Order No. RW-2015-0088 Requiring Pacific Gas and Electric Company to Cleanup and Abate Waste Discharges of Total and Hexavalent Chromium to the Groundwaters of the Mojave Hydrologic Unit. November 4.



**FIGURE S-5**  
**CHROMIUM GAS AND ELECTRIC COMPANY**  
**GROUNDWATER MONITORING AND DOMESTIC WELL**  
**SAMPLING AND MAXIMUM COMPOSITE PLUME**  
**OUTLINE IN UPPER AQUIFER**

SECOND QUARTER 2018 GROUNDWATER MONITORING REPORT AND DOMESTIC WELL RESULTS SITE-WIDE GROUNDWATER MONITORING PROGRAM

PACIFIC GAS AND ELECTRIC COMPANY  
HINKLEY COMPRESSOR STATION  
HINKLEY, CALIFORNIA