

**ATTACHMENT A****BASIN PLAN PROHIBITIONS**

California Water Code Section 13243 provides that a Regional Board, in a water quality control plan, may specify certain conditions or areas where the discharge of waste or certain types of waste is not permitted. The following discharge prohibitions are applicable to any person, as defined by Section 13050(c) of the California Water Code, who is a citizen, domiciliary, or political agency or entity of California whose activities in California could affect the quality of waters of the state within the boundaries of the San Diego Region.

1. The discharge of waste to waters of the state in a manner causing, or threatening to cause a condition of pollution, contamination or nuisance as defined in California Water Code Section 13050, is prohibited.
2. The discharge of waste to land, except as authorized by waste discharge requirements or the terms described in California Water Code Section 13264 is prohibited.
3. The discharge of pollutants or dredged or fill material to waters of the United States except as authorized by a NPDES permit or a dredged or fill material permit (subject to the exemption described in California Water Code Section 13376) is prohibited.
4. Discharges of recycled water to lakes or reservoirs used for municipal water supply or to inland surface water tributaries thereto are prohibited, unless this Regional Board issues a NPDES permit authorizing such a discharge; the proposed discharge has been approved by the State Department of Health Services and the operating agency of the impacted reservoir; and the discharger has an approved fail-safe long-term disposal alternative.
5. The discharge of waste to inland surface waters, except in cases where the quality of the discharge complies with applicable receiving water quality objectives, is prohibited. Allowances for dilution may be made at the discretion of the Regional Board. Consideration would include streamflow data, the degree of treatment provided and safety measures to ensure reliability of facility performance. As an example, discharge of secondary effluent would probably be permitted if streamflow provided 100:1 dilution capability.
6. The discharge of waste in a manner causing flow, ponding, or surfacing on lands not owned or under the control of the discharger is prohibited, unless the discharge is authorized by the Regional Board.
7. The dumping, deposition, or discharge of waste directly into waters of the state, or adjacent to such waters in any manner which may permit its being transported into the waters, is prohibited unless authorized by the Regional Board.
8. Any discharge to a storm water conveyance system that is not composed entirely of "storm water" is prohibited unless authorized by the Regional Board. [The federal regulations, 40 CFR 122.26(b)(13), define storm water as storm water

- runoff, snow melt runoff, and surface runoff and drainage. 40 CFR 122.26(b)(2) defines an illicit discharge as any discharge to a storm water conveyance system that is not composed entirely of storm water except discharges pursuant to a NPDES permit and discharges resulting from fire fighting activities. [§122.26 amended at 56 FR 56553, November 5, 1991; 57 FR 11412, April 2, 1992].
9. The unauthorized discharge of treated or untreated sewage to waters of the state or to a storm water conveyance system is prohibited.
  10. The discharge of industrial wastes to conventional septic tank/subsurface disposal systems, except as authorized by the terms described in California Water Code Section 13264, is prohibited.
  11. The discharge of radioactive wastes amenable to alternative methods of disposal into the waters of the state is prohibited.
  12. The discharge of any radiological, chemical, or biological warfare agent into waters of the state is prohibited.
  13. The discharge of waste into a natural or excavated site below historic water levels is prohibited unless the discharge is authorized by the Regional Board.
  14. The discharge of sand, silt, clay, or other earthen materials from any activity, including land grading and construction, in quantities which cause deleterious bottom deposits, turbidity or discoloration in waters of the state or which unreasonably affect, or threaten to affect, beneficial uses of such waters is prohibited.
  15. The discharge of treated or untreated sewage from vessels to Mission Bay, Oceanside Harbor, Dana Point Harbor, or other small boat harbors is prohibited.

**ATTACHMENT B****STANDARD PROVISIONS, REPORTING REQUIREMENTS, AND NOTIFICATIONS****1. STANDARD PROVISIONS – PERMIT COMPLIANCE [40 CFR 122.41]****(a) *Duty to comply* [40 CFR 122.41(a)].**

- (1) The Copermitee must comply with all of the conditions of this Order. Any noncompliance constitutes a violation of the Clean Water Act (CWA) and the California Water Code (CWC) and is grounds for enforcement action, for permit termination, revocation and reissuance, or modification; or denial of a permit renewal application.
- (2) The Copermitee shall comply with effluent standards or prohibitions established under section 307(a) of the CWA toxic pollutants and with standards for sewage sludge use or disposal established under section 405(d) of the CWA within the time provided in the regulations that establish these standards or prohibitions or standards for sewage sludge use or disposal, even if the Order has not yet been modified to incorporate the requirement.

**(b) *Need to halt or reduce activity not a defense* [40 CFR 122.41(c)].** It shall not be a defense for the Copermitee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this Order.**(c) *Duty to mitigate* [40 CFR 122.41(d)].** The Copermitee shall take all reasonable steps to minimize or prevent any discharge or prevent any discharge or sludge use or disposal in violation of this Order that has a reasonable likelihood of adversely affecting human health or the environment.**(d) *Proper operation and maintenance* [40 CFR 122.41(e)].** The Copermitee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the Copermitee to achieve compliance with the conditions of this Order. Proper operation and maintenance also includes adequate laboratory controls and appropriate quality assurance procedures. This provision requires the operation of back-up or auxiliary facilities or similar systems that are installed by the Copermitee only when necessary to achieve compliance with the conditions of this Order.**(e) *Property rights* [40 CFR 122.41(g)].**

- (1) This Order does not convey any property rights of any sort or any exclusive privilege.
- (2) The issuance of this Order does not authorize any injury to persons or property or invasion of other private rights, or any infringement of State or local law or regulations.

**(f) *Inspection and entry* [40 CFR 122.41(i)].** The Copermitee shall allow the Regional Water Quality Control Board, San Diego Region (Regional Board), State Water Resources Control Board (SWRCB), United States Environmental Protection Agency

(USEPA), and/or their authorized representatives (including an authorized contractor acting as their representative), upon presentation of credentials and other documents as may be required by law, to:

- (1) Enter upon the Copermittee's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of this Order;
- (2) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this Order;
- (3) Inspect and photograph, at reasonable times, any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this Order; and
- (4) Sample or monitor, at reasonable times, for the purpose of assuring Order compliance or as otherwise authorized by the CWA or the CWC, any substances or parameters at any location.

(g) *Bypass* [40 CFR 122.41(m)]

(1) Definitions:

- i) "Bypass" means the intentional diversion of waste streams from any portion of a treatment facility.
  - ii) "Severe property damage" means substantial physical damage to property, damage to the treatment facilities, which causes them to become inoperable, or substantial and permanent loss of natural resources that can reasonably be expected to occur in the absence of a bypass. Severe property damage does not mean economic loss caused by delays in production.
- (2) Bypass not exceeding limitations - The Copermittee may allow any bypass to occur which does not cause exceedances of effluent limitations, but only if it also is for essential maintenance to assure efficient operation. These bypasses are not subject to the provisions listed in Standard Provisions – Permit Compliance (g)(3), (g)(4) and (g)(5) below.
- (3) Prohibition of Bypass - Bypass is prohibited, and the Regional Board may take enforcement action against a Copermittee for bypass, unless:
- i) Bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;
  - ii) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass which occurred during normal periods of equipment downtime or preventive maintenance; and
  - iii) The Copermittee submitted notice as required under Standard Provisions – Permit Compliance (g)(3) above.

## (4) Notice

- i) Anticipated bypass. If the Copermittee knows in advance of the need for a bypass, it shall submit a notice, if possible at least ten days before the date of the bypass.
  - ii) Unanticipated bypass. The Copermittee shall submit notice of an unanticipated bypass as required in Standard Provisions 5(e) below (24-hour notice).
- (h) *Upset* [40 CFR 122.41(n)] Upset means an exceptional incident in which there is unintentional and temporary noncompliance with technology based effluent limitations because of factors beyond the reasonable control of the Copermittee. An upset does not include noncompliance to the extent caused by operational error, improperly designed treatment facilities, inadequate treatment facilities, lack of preventive maintenance, or careless or improper operation.
- (1) Effect of an upset. An upset constitutes an affirmative defense to an action brought for noncompliance with such technology based permit effluent limitations if the requirements of Standard Provisions – Permit Compliance (h)(2) below are met. No determination made during administrative review of claims that noncompliance was caused by upset, and before an action for noncompliance, is final administrative action subject to judicial review.
  - (2) Conditions necessary for a demonstration of upset. A Copermittee who wishes to establish the affirmative defense of upset shall demonstrate, through properly signed, contemporaneous operating logs, or other relevant evidence that:
    - i) An upset occurred and that the Copermittee can identify the cause(s) of the upset;
    - ii) The permitted facility was at the time being properly operated;
    - iii) The Copermittee submitted notice of the upset as required in Standard Provisions – Permit Compliance (5)(e)(ii)(B) below (24-hour notice); and
    - iv) The Copermittee complied with any remedial measures required under Standard Provisions – Permit Compliance 1(c) above.
  - (3) Burden of Proof. In any enforcement proceeding, the Copermittee seeking to establish the occurrence of an upset has the burden of proof.

**2. STANDARD PROVISIONS – PERMIT ACTION**

- (a) *General* [40 CFR 122.41(f)] This Order may be modified, revoked and reissued, or terminated for cause. The filing of a request by the Copermittee for modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any Order condition.
- (b) *Duty to reapply* [40 CFR 122.41(b)]. If the Copermittee wishes to continue an activity regulated by this Order after the expiration date of this Order, the Copermittee must apply for and obtain new permit.
- (c) *Transfers*. This Order is not transferable to any person except after notice to the Regional Board. The Regional Board may require modification or revocation and

reissuance of the Order to change the name of the Copermittee and incorporate such other requirements as may be necessary under the CWA and the CWC.

### 3. STANDARD PROVISIONS – MONITORING

- (a) Samples and measurements taken for the purpose of monitoring shall be representative of the monitored activity. [40 CFR Section 122.41 (j) (1)]
- (b) Monitoring results must be conducted according to test procedures under 40 CFR Part 136, or in the case of sludge use or disposal, approved under 40 CFR Part 136 unless otherwise specified in 40 CFR Part 503 unless other test procedures have been specified in this Order [40 CFR Section 122.41(j)(4)][40 CFR Section 122.44(i)(1)(iv)].

### 4. STANDARD PROVISIONS – RECORDS

- (a) Except for records of monitoring information required by this Order related to the Copermittee's sewage sludge use and disposal activities, which shall be retained for a period of at least five years (or longer as required by 40 CFR Part 503), the Copermittee shall retain records of all monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this Order, and records of all data used to complete the application for this Order, for a period of at least three (3) years from the date of the sample, measurement, report or application, This period may be extended by request of the Regional Water Board Executive Officer at any time [40 CFR Section 122.41(j)(2)].
- (b) *Records of monitoring information* [40 CFR 122.41(j) (3)] shall include:
  - (1) The date, exact place, and time of sampling or measurements;
  - (2) The individual(s) who performed the sampling or measurements;
  - (3) The date(s) analyses were performed;
  - (4) The individual(s) who performed the analyses;
  - (5) The analytical techniques or methods used; and
  - (6) The results of such analyses.
- (c) *Claims of confidentiality* [40 CFR Section 122.7(b)] of the following information will be denied:
  - (1) The name and address of any permit applicant or Copermittee; and
  - (2) Permit applications and attachments, permits and effluent data.

### 5. STANDARD PROVISIONS – REPORTING

- (a) *Duty to provide information* [40 CFR 122.41(h)]. The Copermittee shall furnish to the Regional Board, SWRCB, or USEPA within a reasonable time, any information which the Regional Board, SWRCB, or USEPA may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this Order or to determine compliance with this Order. Upon request, the Copermittee shall also furnish to the Regional Board, SWRCB, or USEPA, copies of records required to be kept by this Order.

(b) *Signatory and Certification Requirements* [40 CFR 122.41(k)]

- (1) All applications, reports, or information submitted to the Regional Board, SWRCB, or USEPA shall be signed and certified in accordance with Standard Provisions – Reporting 5(b)ii), 5(b)iii), 5(b)iv), and 5(b) (see 40 CFR 122.22)
- (2) *Applications* [40 CFR 122.22(a)(3)] All permit applications shall be signed by either a principal executive officer or ranking elected official.
- (3) *Reports* [40 CFR 122.22(b)]. All reports required by this Order, and other information requested by the Regional Board, SWRCB, or USEPA shall be signed by a person described in Standard Provisions – Reporting 5(b)(2) above, or by a duly authorized representative of that person. A person is a duly authorized representative only if:
  - i) The authorization is made in writing by a person described in Standard Provisions-Reporting 5(b)(2) above;
  - ii) The authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility or activity, such as the position of plant manager, operator of a well or a well field, superintendent, position of equivalent responsibility, or an individual or position having overall responsibility for environmental matters for the company. (A duly authorized representative may thus be either a named individual or any individual occupying a named position.); and,
  - iii) The written authorization is submitted to the Regional Water Board and State Water Board.
- (4) *Changes to authorization* [40 CFR Section 122.22(c)] If an authorization under Standard Provisions – Reporting 5(b)(3) of this reporting requirement is no longer accurate because a different individual or position has responsibility for the overall operation of the facility, a new authorization satisfying the requirements of Standard Provisions – Reporting 5(b)(3) above must be submitted to the Regional Water Board and State Water Board prior to or together with any reports, information, or applications to be signed by an authorized representative.
- (5) *Certification* [40 CFR Section 122.22(d)] Any person signing a document under Standard Provisions – Reporting 5(b)(2), or 5(b)(3) above shall make the following certification:

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

(c) *Monitoring reports.* [40 CFR 122.41(l)(4)]

- (1) Monitoring results shall be reported at the intervals specified in the Receiving Waters and Runoff Monitoring and Reporting Program No. R9-2009-0002.
- (2) Monitoring results must be reported on a Discharge Monitoring Report (DMR) form or forms provided or specified by the Regional Board or SWRCB for reporting results of monitoring of sludge use or disposal practices.
- (3) If the Copermittee monitors any pollutant more frequently than required by this Order using test procedures approved under 40 CFR Part 136 or, in the case of sludge use or disposal, approved under 40 CFR Part 136 unless otherwise specified in 40 CFR Part 503, or as specified in this Order, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the DMR or sludge reporting form specified by the Regional Board.
- (4) Calculations for all limitations, which require averaging of measurements, shall utilize an arithmetic mean unless otherwise specified in this Order.

(d) *Compliance schedules.* [40 CFR Section 122.41(l)(5)] Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule of this Order shall be submitted no later than 14 days following each schedule date.

(e) *Twenty-four hour reporting* [40 CFR Section 122.41(l)(6)]

- (1) The Copermittee shall report any noncompliance that may endanger health or the environment. Any information shall be provided orally within 24 hours from the time the Copermittee becomes aware of the circumstances. A written submission shall also be provided within five (5) days of the time the Copermittee becomes aware of the circumstances. The written submission shall contain a description of the noncompliance and its cause; the period of noncompliance, including exact dates and times, and if the noncompliance has not been corrected, the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance.
- (2) The following shall be included as information, which must be reported within 24 hours under this paragraph:
  - i) Any unanticipated bypass that exceeds any effluent limitation in the Order (See 40 CFR 122.41(g)).
  - ii) Any upset which exceeds any effluent limitation in this Order.
- (3) The Regional Board may waive the above-required written report under this provision on a case-by-case basis if the oral report has been received within 24 hours.

(f) *Planned changes.* [40 CFR Section 122.41(l)(1)] The Copermittee shall give notice to the Regional Board as soon as possible of any planned physical alterations or additions to the permitted facility. Notice is required under this provision only when:



- (1) The alteration or addition to a permitted facility may meet one of the criteria for determining whether a facility is a new source in 40 CFR 122.29(b); or
  - (2) The alteration or addition could significantly change the nature or increase the quantity of pollutants discharged. This notification applies to pollutants, which are not subject to effluent limitations in this Order.
  - (3) The alteration or addition results in a significant change in the Copermittee's sludge use or disposal practices, and such alteration, addition, or change may justify the application of permit conditions that are different from or absent in the existing Order, including notification of additional use or disposal sites not reported during the permit application process or not reported pursuant to an approved land application plan.
- (g) *Anticipated noncompliance.* [40 CFR Section 122.41(l)(7)] The Copermittee shall give advance notice to the Regional Board or SWRCB of any planned changes in the permitted facility or activity, which may result in noncompliance with Order requirements.
- (h) *Other noncompliance* [40 CFR Section 122.41(l) 7)] The Copermittee shall report all instances of noncompliance not reported under Standard Provisions 5(c), 5(d), and 5(e) above, at the time monitoring reports are submitted. The reports shall contain the information listed in Standard Provision – Reporting 5(e) above.
- (i) *Other information* [40 CFR Section 122.41(l)(8)] When the Copermittee becomes aware that it failed to submit any relevant facts in a permit application, or submitted incorrect information in a permit application or in any report to the Regional Board, SWRCB, or USEPA, the Copermittee shall promptly submit such facts or information.

## 6. STANDARD PROVISIONS – ENFORCEMENT

- (a) The Regional Board is authorized to enforce the terms of this permit under several provisions of the CWC, including, but not limited to, Sections 13385, 13386, and 13387.

## 7. ADDITIONAL STANDARD PROVISIONS

- (a) *Municipal separate storm sewer systems* [40 CFR 122.42(c)]. The operator of a large or medium municipal separate storm sewer system or a municipal separate storm sewer that has been designated by the Director under 40 CFR 122.26(a)(1)(v) must submit an annual report by the anniversary of the date of the issuance of the permit for such system. The report shall include:
- (1) The status of implementing the components of the storm water management program that are established as permit conditions;
  - (2) Proposed changes to the storm water management programs that are established as permit conditions. Such proposed changes shall be consistent with 40 CFR 122.26(d)(2)(iii); and
  - (3) Revisions, if necessary, to the assessment of controls and the fiscal analysis reported in the permit application under 40 CFR 122.26(d)(2)(iv) and 40 CFR

122.26(d)(2)(v);

- (4) A summary of data, including monitoring data, that is accumulated throughout the reporting year;
  - (5) Annual expenditures and budget for year following each annual report;
  - (6) A summary describing the number and nature of enforcement actions, inspections, and public education programs; and
  - (7) Identification of water quality improvements or degradation.
- (b) *Storm water discharges* [40 CFR 122.42(d)]. The initial permits for discharges composed entirely of storm water issued pursuant to 40 CFR 122.26(e)(7) shall require compliance with the conditions of the permit as expeditiously as practicable, but in no event later than three years after the date of issuance of the permit.
- (c) *Other Effluent Limitations and Standards* [40 CFR 122.44(b)(1)]. If any toxic effluent standard or prohibition (including any schedule of compliance specified in such effluent standard or prohibition) is promulgated under Section 307(a) of the CWA for a toxic pollutant which is present in the discharge and that standard or prohibition is more stringent than any limitation on the pollutant in this Order, the Regional Board may institute proceedings under these regulations to modify or revoke and reissue the Order to conform to the toxic effluent standard or prohibition.
- (d) *Discharge is a privilege* [CWC section 13263(g)]. No discharge of waste into the waters of the State, whether or not such discharge is made pursuant to waste discharge requirements, shall create a vested right to continue such discharge. All discharges of waste into waters of the State are privileges, not rights.
- (e) *Review and revision of Order* [CWC section 13263(e)]. Upon application by any affected person, or on its own motion, the Regional Board may review and revise this permit.
- (f) *Termination or modification of Order* [CWC section 13381]. This permit may be terminated or modified for causes, including, but not limited to, all of the following:
- (1) Violation of any condition contained in this Order.
  - (2) Obtaining this Order by misrepresentation, or failure to disclose fully all relevant facts.
  - (3) A change in any condition that requires either a temporary or permanent reduction or elimination of the permitted discharge.
- (g) *Transfers*. When this Order is transferred to a new owner or operator, such requirements as may be necessary under the CWC may be incorporated into this Order.
- (h) *Conditions not stayed*. The filing of a request by the Copermitttee for modification, revocation and reissuance, or termination of this Order, or a notification of planned change in or anticipated noncompliance with this Order does not stay any condition of this Order.

- (i) *Availability.* A copy of this Order shall be kept at a readily accessible location and shall be available to on-site personnel at all times.
- (j) *Duty to minimize or correct adverse impacts.* The Copermittees shall take all reasonable steps to minimize or correct any adverse impact on the environment resulting from noncompliance with this Order, including such accelerated or additional monitoring as may be necessary to determine the nature and impact of the noncompliance.
- (k) *Interim Effluent Limitations.* The Copermittee shall comply with any interim effluent limitations as established by addendum, enforcement action, or revised waste discharge requirements which have been, or may be, adopted by this Regional Board.
- (l) *Responsibilities, liabilities, legal action, penalties* [CWC sections 13385 and 13387]. The Porter-Cologne Water Quality Control Act provides for civil and criminal penalties comparable to, and in some cases greater than, those provided for under the CWA.

Nothing in this Order shall be construed to protect the Copermittee from its liabilities under federal, state, or local laws.

Except as provided for in 40CFR 122.41(m) and (n), nothing in this Order shall be construed to relieve the Copermittee from civil or criminal penalties for noncompliance.

Nothing in this Order shall be construed to preclude the institution of any legal action or relieve the Copermittee from any responsibilities, liabilities, or penalties to which the Copermittee is or may be subject to under Section 311 of the CWA.

Nothing in this Order shall be construed to preclude institution of any legal action or relieve the Copermittee from any responsibilities, liabilities, or penalties established pursuant to any applicable state law or regulation under authoring preserved by Section 510 of the CWA.

- (m) *Noncompliance.* Any noncompliance with this Order constitutes violation of the CWA and is grounds for denial of an application or modification of the Order (also see 40 CFR 122.41(a)).
- (n) *Director.* For purposes of this Order, the term "Director" used in parts of 40 CFR incorporated into this Order by reference and/or applicable to this Order shall have the same meaning as the term "Regional Board" used elsewhere in this Order, except that in 40 CFR 122.41(h) and (l), "Director" shall mean "Regional Board, SWRCB, and USEPA."
- (o) The Regional Board has, in prior years, issued a limited number of individual NPDES permits for non-storm water discharges to MS4s. The Regional Board or SWRCB may in the future, upon prior notice to the Copermittee(s), issue an NPDES permit for any non-storm water discharge (or class of non-storm water discharges) to a MS4. Copermittees may prohibit any non-storm water discharge (or class of non-storm water discharges) to a MS4 that is authorized under such separate NPDES permits.

- (p) *Effective date.* This Order shall become effective on the date of its adoption provided the USEPA has no objection. If the USEPA objects to its issuance, this Order shall not become effective until such objection is withdrawn. This Order supersedes Order No. 2001-01 upon the effective date of this Order.
- (q) *Expiration.* This Order expires five years after adoption.
- (r) *Continuation of expired order* [23 CCR 2235.4]. After this Order expires, the terms and conditions of this Order are automatically continued pending issuance of a new permit if all requirements of the federal NPDES regulations on the continuation of expired permits (40 CFR 122.6) are complied with.
- (s) *Applications.* Any application submitted by a Copermittee for reissuance or modification of this Order shall satisfy all applicable requirements specified in federal regulations as well as any additional requirements for submittal of a Report of Waste Discharge specified in the CWC and the California Code of Regulations.
- (t) *Confidentiality.* Except as provided for in 40 CFR 122.7, no information or documents submitted in accordance with or in application for this Order will be considered confidential, and all such information and documents shall be available for review by the public at the Regional Board office.
- (u) *Severability.* The provisions of this Order are severable, and if any provision of this Order, or the application of any provisions of this Order to any circumstance, is held invalid, the application of such provision to other circumstances and the remainder of this Order shall not be affected thereby.
- (v) *Report submittal.* The Copermittee shall submit reports and provide notifications as required by this Order to the following:

NORTHERN WATERSHED UNIT  
CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD  
SAN DIEGO REGION  
9174 SKY PARK COURT, SUITE 100  
SAN DIEGO CA 92123-4340  
Telephone: (858) 467-2952 Fax: (858) 571-6972

EUGENE BROMLEY  
US ENVIRONMENTAL PROTECTION AGENCY  
REGION IX  
PERMITS ISSUANCE SECTION (W-5-1)  
75 HAWTHORNE STREET  
SAN FRANCISCO CA 94105

Unless otherwise directed, the Copermittee shall submit one hard copy for the official record and one electronic copy of each report required under this Order to the Regional Board and one electronic copy to the EPA.

**ATTACHMENT C****ACRONYMS AND ABBREVIATIONS**

ADT	Average Daily Traffic
AMAL	Average Monthly Action Level
ASBS	Area of Special Biological Significance
AST	Active/Passive Sediment Treatment
BMP	Best Management Practice
Basin Plan	Water Quality Control Plan for the San Diego Basin
BU	Beneficial Use
CASQA	California Stormwater Quality Association
CEQA	California Environmental Quality Act
CFR	Code of Federal Regulations
CWA	Clean Water Act
CWC	California Water Code
CZARA	Coastal Zone Act Reauthorization Amendments of 1990
DAMP	Drainage Area Management Plan
DNQ	Detected, but not Quantified
EIA	Effective Impervious Area
ESAs	Environmentally Sensitive Areas
GIS	Geographic Information System
HMP	Hydromodification Management Plan
IBI	Index of Biotic Integrity
JRMP	Jurisdictional Runoff Management Plan
LID	Low Impact Development
MDAL	Maximum Daily Action Level
MEP	Maximum Extent Practicable
ML	Minimum Level
MS4	Municipal Separate Storm Sewer System
NOI	Notice of Intent
NPDES	National Pollutant Discharge Elimination System
Copermittees	County of Riverside, the 4 incorporated cities within the County of Riverside in the San Diego Region, and the Riverside County Flood Control District
RGOs	Retail Gasoline Outlets
ROWD	Riverside County Copermittees' Report of Waste Discharge (application for NPDES reissuance)
RWLs	Receiving Water Limitations
SAL	Storm Water Action Level
San Diego Water Board	California Regional Water Quality Control Board, San Diego Region
SIC	Standard Industrial Classification Code
SSMP	Standard Urban Storm Water Mitigation Plan
State Board	State Water Resources Control Board
SWQPA	State Water Quality Protected Area
TMDL	Total Maximum Daily Load

USEPA	United States Environmental Protection Agency
WLA	Waste Load Allocation
WQMP	Water Quality Management Plan
WRMP	Watershed Runoff Management Plan

## DEFINITIONS

**Active/Passive Sediment Treatment** - Using mechanical, electrical or chemical means to flocculate or coagulate suspended sediment for removal from runoff from construction sites prior to discharge.

**Anthropogenic Litter** – Trash generated from human activities, not including sediment.

**Average Monthly Action Level** – the highest allowable average of daily discharges over a calendar month, calculated as the sum of all daily discharges measured during a calendar month divided by the number of daily discharges measured during that month.

**Basin Plan** – Water Quality Control Plan, San Diego Basin, Region 9, and amendments, developed by the Regional Board.

**Beneficial Uses** - The uses of water necessary for the survival or well being of man, plants, and wildlife. These uses of water serve to promote tangible and intangible economic, social, and environmental goals. “Beneficial Uses” of the waters of the State that may be protected include, but are not limited to, domestic, municipal, agricultural and industrial supply; power generation; recreation; aesthetic enjoyment; navigation; and preservation and enhancement of fish, wildlife, and other aquatic resources or preserves. Existing beneficial uses are uses that were attained in the surface or ground water on or after November 28, 1975; and potential beneficial uses are uses that would probably develop in future years through the implementation of various control measures. “Beneficial Uses” are equivalent to “Designated Uses” under federal law. [California Water Code Section 13050(f)].

**Best Management Practices (BMPs)** - Defined in 40 CFR 122.2 as schedules of activities, prohibitions of practices, maintenance procedures, and other management practices to prevent or reduce the pollution of waters of the United States. BMPs also include treatment requirements, operating procedures and practices to control plant site runoff, spillage or leaks, sludge or waste disposal, or drainage from raw material storage. In the case of municipal storm water permits, BMPs are typically used in place of numeric effluent limits.

**Bioassessment** - The use of biological community information to evaluate the biological integrity of a water body and its watershed. With respect to aquatic ecosystems, bioassessment is the collection and analysis of samples of the benthic macroinvertebrate community together with physical/habitat quality measurements associated with the sampling site and the watershed to evaluate the biological condition (i.e. biological integrity) of a water body.

**Biocriteria** - Under the CWA, numerical values or narrative expressions that define a desired biological condition for a water body that are legally enforceable. The USEPA

defines biocriteria as: “numerical values or narrative expressions that describe the reference biological integrity of aquatic communities inhabiting waters of a given designated aquatic life use... (that)...describe the characteristics of water body segments least impaired by human activities.”

**Biofiltration** - refers to practices that use vegetation and amended soils to detain and treat runoff from impervious areas. Treatment is through filtration, infiltration, adsorption, ion exchange, and biological uptake of pollutants.

**Biological Integrity** - Defined in Karr J.R. and D.R. Dudley. 1981. Ecological perspective on water quality goals. Environmental Management 5:55-68 as: “A balanced, integrated, adaptive community of organisms having a species composition, diversity, and functional organization comparable to that of natural habitat of the region.” Also referred to as ecosystem health.

**Clean Water Act Section 402(p) [33 USC 1342(p)]** - The federal statute requiring municipal and industrial dischargers to obtain NPDES permits for their discharges of storm water.

**Clean Water Act Section 303(d) Water Body** - An impaired water body in which water quality does not meet applicable water quality standards and/or is not expected to meet water quality standards, even after the application of technology based pollution controls required by the CWA. The discharge of runoff to these water bodies by the Copermittees is significant because these discharges can cause or contribute to violations of applicable water quality standards.

**Construction Site** – Any project, including projects requiring coverage under the General Construction Permit, that involves soil disturbing activities including, but not limited to, clearing, grading, disturbances to ground such as stockpiling, and excavation.

**Contamination** - As defined in the Porter-Cologne Water Quality Control Act, contamination is “an impairment of the quality of waters of the State by waste to a degree which creates a hazard to the public health through poisoning or through the spread of disease. ‘Contamination’ includes any equivalent effect resulting from the disposal of waste whether or not waters of the State are affected.”

**Critical Channel Flow (Qc)** – The channel flow that produces the critical shear stress that initiates bed movement or that erodes the toe of channel banks. When measuring Qc, it should be based on the weakest boundary material – either bed or bank.

**CWA** – Federal Clean Water Act

**CWC** – California Water Code

**Daily Discharge** – Daily Discharge is defined as either: (1) the total mass of the constituent discharged over the calendar day or any 24 hour period that reasonably represents a calendar day for purposes of sampling (as specified in the permit), for a constituent with limitations expressed in units of mass or; (2) the unweighted arithmetic mean measurement of the constituent over the day for a constituent with limitations expressed in other units of measurement (e.g. concentration.)

The Daily Discharge may be determined by the analytical results of a composite sample taken over the course of one day (a calendar day, or other 24 hour period other than a day), or by the arithmetic mean of analytical results from one or more grab samples taken over the course of a day.

**Detected, but not Quantified** – those sample results less than the reporting level, but greater than or equal to the laboratory's Method of Detection Limit (MDL.)

**Development Projects** - Construction, rehabilitation, redevelopment, or reconstruction of any public or private residential project, industrial, commercial, or any other projects.

**Dilution Credit** – the amount of dilution granted to a discharger in the calculation of a WQBEL, based on the allowance of a specific mixing zone. It is calculated from the dilution ratio, or determined through conducting of a mixing zone study, or modeling of the discharge and receiving water.

**Dry Season** – May 1 through September 30 of each year.

**Dry Weather** – weather is considered dry if the preceding 72 hours has been without precipitation.

**Effectiveness Assessment Outcome Level 1** - Compliance with Activity-based Permit Requirements – Level 1 outcomes are those directly related to the implementation of specific activities prescribed by this Order or established pursuant to it.

**Effectiveness Assessment Outcome Level 2** - Changes in Attitudes, Knowledge, and Awareness – Level 2 outcomes are measured as increases in knowledge and awareness among target audiences such as residents, businesses, and municipal employees.

**Effectiveness Assessment Outcome Level 3** - Behavioral Change and BMP Implementation – Level 3 outcomes measure the effectiveness of activities in affecting behavioral change and BMP implementation.

**Effectiveness Assessment Outcome Level 4** - Load Reductions – Level 4 outcomes measure load reductions which quantify changes in the amounts of pollutants associated with specific sources before and after a BMP or other control measure is employed.

**Effectiveness Assessment Outcome Level 5** - Changes in Runoff and Discharge Quality – Level 5 outcomes are measured as changes in one or more specific constituents or stressors in discharges into or from MS4s.

**Effectiveness Assessment Outcome Level 6** - Changes in Receiving Water Quality – Level 6 outcomes measure changes to receiving water quality resulting from discharges into and from MS4s, and may be expressed through a variety of means such as compliance with water quality objectives or other regulatory benchmarks, protection of biological integrity, or beneficial use attainment.

**Enclosed Bays** – Enclosed bays are indentations along the coast that enclose an area of oceanic water within distinct headlands or harbor works. Enclosed bays include all



bays where the narrowest distance between the headlands or outermost bay works is less than 75 percent of the greatest dimension of the enclosed portion of the bay. Enclosed bays do not include inland surface waters or ocean waters.

**Erosion** – When land is diminished or worn away due to wind, water, or glacial ice. Often the eroded debris (silt or sediment) becomes a pollutant via storm water runoff. Erosion occurs naturally but can be intensified by land clearing activities such as farming, development, road building, and timber harvesting.

**Environmentally Sensitive Areas (ESAs)** - Areas that include but are not limited to all Clean Water Act Section 303(d) impaired water bodies; areas designated as Areas of Special Biological Significance by the State Water Resources Control Board (Water Quality Control Plan for the San Diego Basin (1994) and amendments); State Water Quality Protected Areas; water bodies designated with the RARE beneficial use by the State Water Resources Control Board (Water Quality Control Plan for the San Diego Basin (1994) and amendments); areas designated as preserves or their equivalent under the Natural Communities Conservation Program within the Cities and County of Orange; and any other equivalent environmentally sensitive areas which have been identified by the Copermittees.

**Estuaries** – waters, including coastal lagoons, located at the mouth of streams that serve as areas of mixing fresh and ocean waters. Coastal lagoons and mouths of streams that are temporarily separated from the ocean by sandbars shall be considered estuaries. Estuarine waters shall be considered to extend from a bay or the open ocean to a point upstream where there is no significant mixing of fresh water and ocean water. Estuaries do not include inland surface waters or ocean waters.

**Feasibility Analysis** – Detailed description of the selection process for the treatment control BMPs for a Priority Development Project, including justification of why one BMP is selected over another. For a Priority Development Project where a treatment control BMP with a low removal efficiency ranking (as identified by the Model SUSMP) is proposed, the analysis shall include a detailed and adequate justification exhibiting the reasons implementation of a treatment control BMP with a higher removal efficiency is infeasible for the Priority Development Project or portion of the Priority Development Project.

**Flow Duration** – The long-term period of time that flows occur above a threshold that causes significant sediment transport and may cause excessive erosion damage to creeks and streams (not a single storm event duration). The simplest way to visualize this is to consider a histogram of pre- and post-project flows using long-term records of hourly data. To maintain pre-project flow duration means that the total number of hours (counts) within each range of flows in a flow-duration histogram cannot increase between the pre- and post-project condition. Flow duration within the range of geomorphologically significant flows is important for managing erosion.

**GIS** – Geographic Information System

**Grading** - The cutting and/or filling of the land surface to a desired slope or elevation.

**Hazardous Material** – Any substance that poses a threat to human health or the environment due to its toxicity, corrosiveness, ignitability, explosive nature or chemical

reactivity. These also include materials named by the USEPA in 40 CFR 116 to be reported if a designated quantity of the material is spilled into the waters of the U.S. or emitted into the environment.

**Hazardous Waste** - Hazardous waste is defined as “any waste which, under Section 600 of Title 22 of this code, is required to be managed according to Chapter 30 of Division 4.5 of Title 22 of this code” [CCR Title 22, Division 4.5, Chapter 11, Article 1].

**Household Hazardous Waste** – Paints, cleaning products, and other wastes generated during home improvement or maintenance activities.

**Hydromodification** – The change in the natural watershed hydrologic processes and runoff characteristics (i.e., interception, infiltration, overland flow, interflow and groundwater flow) caused by urbanization or other land use changes that result in increased stream flows and sediment transport. In addition, alteration of stream and river channels, such as stream channelization, concrete lining, installation of dams and water impoundments, and excessive streambank and shoreline erosion are also considered hydromodification, due to their disruption of natural watershed hydrologic processes.

**Illicit Connection** – Any connection to the MS4 that conveys an illicit discharge.

**Illicit Discharge** - Any discharge to the MS4 that is not composed entirely of storm water except discharges pursuant to a NPDES permit and discharges resulting from fire fighting activities [40 CFR 122.26(b)(2)].

**Implementation Assessment** – Assessment conducted to determine the effectiveness of Copermittee programs and activities in achieving measurable targeted outcomes, and in determining whether priority sources of water quality problems are being effectively addressed.

**Inactive Slopes** – Slopes on which no grading or other soil disturbing activities are conducted for 10 or more days.

**Inland Surface Waters** – all surface waters of the State that do not include the ocean, enclosed bays, or estuaries.

**Integrated Assessment** – Assessment to be conducted to evaluate whether program implementation is properly targeted to and resulting in the protection and improvement of water quality.

**Jurisdictional Runoff Management Plan (JRMP)** – A written description of the specific jurisdictional runoff management measures and programs that each Copermittee will implement to comply with this Order and ensure that storm water pollutant discharges in runoff are reduced to the MEP and do not cause or contribute to a violation of water quality standards.

**Low Impact Development (LID)** – A storm water management and land development strategy that emphasizes conservation and the use of on-site natural features integrated with engineered, small-scale hydrologic controls to more closely reflect pre-development hydrologic functions.

**Low Impact Development Best Management Practices (LID BMPs)** – LID BMPs include schedules of activities, prohibitions of practices, maintenance procedures, and other management practices to prevent or reduce the pollution of waters of the United States through storm water management and land development strategies that emphasize conservation and the use of on-site natural features integrated with engineered, small-scale hydrologic controls to more closely reflect pre-development hydrologic functions. LID BMPs include retention practices that do not allow runoff, such as infiltration, rain water harvesting and reuse, and evapotranspiration. LID BMPs also include flow-through practices such as biofiltration that may have some discharge of storm water following pollutant reduction.

**Maximum Daily Action Level (MDAL)** – is the highest allowable daily discharge of a pollutant, over a calendar day (or 24 hour period). For pollutants with action levels expressed in units of mass, the daily discharge is calculated as the total mass of the pollutant discharged over the day. For pollutants with action levels expressed in other units of measurement, the daily discharge is calculated as the arithmetic mean measurement of the pollutant over the day.

**Maximum Extent Practicable (MEP)** – The technology-based standard established by Congress in CWA section 402(p)(3)(B)(iii) for storm water that operators of MS4s must meet. Technology-based standards establish the level of pollutant reductions that dischargers must achieve, typically by treatment or by a combination of source control and treatment control BMPs. MEP generally emphasizes pollution prevention and source control BMPs primarily (as the first line of defense) in combination with treatment methods serving as a backup (additional line of defense). MEP considers economics and is generally, but not necessarily, less stringent than BAT. A definition for MEP is not provided either in the statute or in the regulations. Instead the definition of MEP is dynamic and will be defined by the following process over time: municipalities propose their definition of MEP by way of their runoff management programs. Their total collective and individual activities conducted pursuant to the runoff management programs becomes their proposal for MEP as it applies both to their overall effort, as well as to specific activities (e.g., MEP for street sweeping, or MEP for MS4 maintenance). In the absence of a proposal acceptable to the Regional Board, the Regional Board defines MEP.

In a memo dated February 11, 1993, entitled "Definition of Maximum Extent Practicable," Elizabeth Jennings, Senior Staff Counsel, SWRCB addressed the achievement of the MEP standard as follows:

*“To achieve the MEP standard, municipalities must employ whatever Best Management Practices (BMPs) are technically feasible (i.e., are likely to be effective) and are not cost prohibitive. The major emphasis is on technical feasibility. Reducing pollutants to the MEP means choosing effective BMPs, and rejecting applicable BMPs only where other effective BMPs will serve the same purpose, or the BMPs would not be technically feasible, or the cost would be prohibitive. In selecting BMPs to achieve the MEP standard, the following factors may be useful to consider:*

- a. *Effectiveness: Will the BMPs address a pollutant (or pollutant source) of concern?*

- b. *Regulatory Compliance: Is the BMP in compliance with storm water regulations as well as other environmental regulations?*
- c. *Public Acceptance: Does the BMP have public support?*
- d. *Cost: Will the cost of implementing the BMP have a reasonable relationship to the pollution control benefits to be achieved?*
- e. *Technical Feasibility: Is the BMP technically feasible considering soils, geography, water resources, etc?*

*The final determination regarding whether a municipality has reduced pollutants to the maximum extent practicable can only be made by the Regional or State Water Boards, and not by the municipal discharger. If a municipality reviews a lengthy menu of BMPs and chooses to select only a few of the least expensive, it is likely that MEP has not been met. On the other hand, if a municipal discharger employs all applicable BMPs except those where it can show that they are not technically feasible in the locality, or whose cost would exceed any benefit derived, it would have met the standard. Where a choice may be made between two BMPs that should provide generally comparable effectiveness, the discharger may choose the least expensive alternative and exclude the more expensive BMP. However, it would not be acceptable either to reject all BMPs that would address a pollutant source, or to pick a BMP base solely on cost, which would be clearly less effective. In selecting BMPs the municipality must make a serious attempt to comply and practical solutions may not be lightly rejected. In any case, the burden would be on the municipal discharger to show compliance with its permit. After selecting a menu of BMPs, it is the responsibility of the discharger to ensure that all BMPs are implemented.”*

**Minimum Level** – the concentration at which the entire analytical system must give a recognizable signal and acceptable calibration point. The ML is the concentration in a sample that is equivalent to the concentration of the lowest calibration standard analyzed by a specific analytical procedure, assuming that all the method sample weights, volumes and processing steps have been followed.

**Monitoring Year** – the monitoring year includes a full wet season and dry season, beginning annually on October 1<sup>st</sup> and ending on September 30<sup>th</sup>.

**Municipal Separate Storm Sewer System (MS4)** – A conveyance or system of conveyances (including roads with drainage systems, municipal streets, catch basins, curbs, gutters, ditches, man-made channels, or storm drains): (i) Owned or operated by a State, city, town, borough, county, parish, district, association, or other public body (created by or pursuant to State law) having jurisdiction over disposal of sewage, industrial wastes, storm water, or other wastes, including special districts under State law such as a sewer district, flood control district or drainage district, or similar entity, or an Indian tribe or an authorized Indian tribal organization, or designated and approved management agency under section 208 of the CWA that discharges to waters of the United States; (ii) Designated or used for collecting or conveying storm water; (iii) Which is not a combined sewer; (iv) Which is not part of the Publicly Owned Treatment Works (POTW) as defined at 40 CFR 122.26.

**National Pollutant Discharge Elimination System (NPDES)** - The national program for issuing, modifying, revoking and reissuing, terminating, monitoring and enforcing permits, and imposing and enforcing pretreatment requirements, under Sections 307, 318, 402, and 405 of the CWA.

**NOI** – Notice of Intent

**Non-Storm Water** - All discharges to and from a MS4 that do not originate from precipitation events (i.e., all discharges from a MS4 other than storm water). Non-storm water includes illicit discharges, non-prohibited discharges, and NPDES permitted discharges.

**Nuisance** - As defined in the Porter-Cologne Water Quality Control Act a nuisance is “anything which meets all of the following requirements: 1) Is injurious to health, or is indecent, or offensive to the senses, or an obstruction to the free use of property, so as to interfere with the comfortable enjoyment of life or property. 2) Affects at the same time an entire community or neighborhood, or any considerable number of persons, although the extent of the annoyance or damage inflicted upon individuals may be unequal. 3) Occurs during, or as a result of, the treatment or disposal of wastes.”

**Ocean Waters** – the territorial marine waters of the State as defined by California law to the extent these waters are outside of enclosed bays, estuaries, and coastal lagoons. Discharges to ocean waters are regulated in accordance with the State Board's California Ocean Plan.

**Order** – Order No. R9-2009-0002 (NPDES No. CAS0108740)

**Person** - A person is defined as an individual, association, partnership, corporation, municipality, State or Federal agency, or an agent or employee thereof [40 CFR 122.2].

**Point Source** - Any discernible, confined, and discrete conveyance, including, but not limited to, any pipe, ditch, channel, tunnel, conduit, well, discrete fissure, container, rolling stock, concentrated animal feeding operations, landfill leachate collection systems, vessel, or other floating craft from which pollutants are or may be discharged. This term does not include return flows from irrigated agriculture or agricultural storm water runoff.

**Pollutant** - Any agent that may cause or contribute to the degradation of water quality such that a condition of pollution or contamination is created or aggravated.

**Pollution** - As defined in the Porter-Cologne Water Quality Control Act: “the alteration of the quality of the waters of the State by waste, to a degree that unreasonably affects the either of the following: 1) The waters for beneficial uses; or 2) Facilities that serve these beneficial uses.” Pollution may include contamination.

**Pollutants of Concern** – Pollutants for which water bodies are listed as impaired under CWA section 303(d), pollutants associated with the land use type of a development, and/or pollutants commonly associated with runoff. Pollutants commonly associated with runoff include total suspended solids; sediment; pathogens (e.g., bacteria, viruses, protozoa); heavy metals (e.g., copper, lead, zinc, and cadmium); petroleum products and polynuclear aromatic hydrocarbons; synthetic organics (e.g., pesticides, herbicides,

and PCBs); nutrients (e.g., nitrogen and phosphorus fertilizers); oxygen-demanding substances (decaying vegetation, animal waste, and anthropogenic litter).

**Pollution Prevention** - Pollution prevention is defined as practices and processes that reduce or eliminate the generation of pollutants, in contrast to source control BMPs, treatment control BMPs, or disposal.

**Post-Construction BMPs** - A subset of BMPs including structural and non-structural controls which detain, retain, filter, or educate to prevent the release of pollutants to surface waters during the final functional life of developments.

**Pre-Project or Pre-Development Runoff Conditions (Discharge Rates, Durations, Etc.)** – Runoff conditions that exist onsite immediately before the planned development activities occur. This definition is not intended to be interpreted as that period before any human-induced land activities occurred. This definition pertains to redevelopment as well as initial development.

**Principal Copermittee** – County of Orange

**Priority Development Projects** - New development and redevelopment project categories listed in Section F.1.d(2) of Order No. R9-2009-0002.

**Rainy Season** – (aka Wet Season) is the period of time from October 1 forward to April 30 when the San Diego region experiences the most rainfall.

**Receiving Waters** – Waters of the United States.

**Receiving Water Limitations (RWLs)** - Waste discharge requirements issued by the Regional Board typically include both: (1) “Effluent Limitations” (or “Discharge Limitations”) that specify the technology-based or water-quality-based effluent limitations; and (2) “Receiving Water Limitations” that specify the water quality objectives in the Basin Plan as well as any other limitations necessary to attain those objectives. In summary, the “Receiving Water Limitations” provision is the provision used to implement the requirement of CWA section 301(b)(1)(C) that NPDES permits must include any more stringent limitations necessary to meet water quality standards.

**Redevelopment** - The creation, addition, and or replacement of impervious surface on an already developed site. Examples include the expansion of a building footprint, road widening, the addition to or replacement of a structure, and creation or addition of impervious surfaces. Replacement of impervious surfaces includes any activity that is not part of a routine maintenance activity where impervious material(s) are removed, exposing underlying soil during construction. Redevelopment does not include trenching and resurfacing associated with utility work; resurfacing existing roadways; new sidewalk construction, pedestrian ramps, or bikelane on existing roads; and routine replacement of damaged pavement, such as pothole repair.

**Retain** – to keep or hold in a particular place, condition, or position without discharge to surface waters.

**Runoff** - All flows in a storm water conveyance system that consists of the following components: (1) storm water (wet weather flows) and (2) non-storm water including dry weather flows.

**San Diego Water Board** – As used in this document the term "San Diego Water Board" is synonymous with the term "Regional Board" as defined in Water Code section 13050(b) and is intended to refer to the California Regional Water Quality Control Board for the San Diego Region as specified in Water Code Section 13200.

**Sediment** - Soil, sand, and minerals washed from land into water. Sediment resulting from anthropogenic sources (i.e. human induced land disturbance activities) is considered a pollutant. This Order regulates only the discharges of sediment from anthropogenic sources and does not regulate naturally occurring sources of sediment. Sediment can destroy fish-nesting areas, clog animal habitats, and cloud waters so that sunlight does not reach aquatic plants.

**Shared Treatment Control BMP** - BMPs used by multiple developments to infiltrate, filter, or treat the required volume or flow prior to discharge to a receiving water. This could include, for example, a treatment BMP at the end of an enclosed storm drain that collects runoff from several commercial developments.

**Source Control BMP** – Land use or site planning practices, or structural or nonstructural measures that aim to prevent runoff pollution by reducing the potential for contamination at the source of pollution. Source control BMPs minimize the contact between pollutants and runoff.

**State Water Quality Protection Area** – A nonterrestrial marine or estuarine area designated to protect marine species or biological communities from an undesirable alteration in natural water quality, including, but not limited to, areas of special biological significance that have been designated by the State Water Resources Control Board through its water quality control planning process. Areas of special biological significance are a subset of State Water Quality Protection Areas, and require special protection as determined by the State Water Resources Control Board pursuant to the California Ocean Plan adopted and reviewed pursuant to Article 4 (commencing with Section 13160) of Chapter 3 of Division 7 of the California Water Code and pursuant to the Water Quality Control Plan for Control of Temperature in the Coastal and Interstate Waters and Enclosed Bays and Estuaries of California (California Thermal Plan) adopted by the state board.

**Storm Water** – Per 40 CFR 122.26(b)(13), means storm water runoff, snowmelt runoff and surface runoff and drainage. Surface runoff and drainage pertains to runoff and drainage resulting from precipitation events.

**Standard Storm Water Mitigation Plan (SSMP)** – A plan developed to mitigate the impacts of runoff from Priority Development Projects.

**Third Party Inspectors** - Industrial and commercial facility inspectors who are not contracted or employed by a regulatory agency or group of regulatory agencies, such as the Regional Board or Copermittees. The third party inspector is not a regular facility employee self-inspecting their own facility. The third party inspector could be a contractor or consultant employed by a facility or group of businesses to conduct inspections.

**Total Maximum Daily Load (TMDL)** - The maximum amount of a pollutant that can be discharged into a water body from all sources (point and non-point) and still maintain water quality standards. Under CWA section 303(d), TMDLs must be developed for all water bodies that do not meet water quality standards after application of technology-based controls.

**Toxicity** - Adverse responses of organisms to chemicals or physical agents ranging from mortality to physiological responses such as impaired reproduction or growth anomalies). The water quality objectives for toxicity provided in the Water Quality Control Plan, San Diego Basin, Region 9, (Basin Plan), state in part...“All waters shall be free of toxic substances in concentrations that are toxic to, or that produce detrimental physiological responses in human, plant, animal, or aquatic life....The survival of aquatic life in surface waters subjected to a waste discharge or other controllable water quality factors, shall not be less than that for the same water body in areas unaffected by the waste discharge”.

**Treatment Control BMP** – Any engineered system designed to remove pollutants by simple gravity settling of particulate pollutants, filtration, biological uptake, media absorption or any other physical, biological, or chemical process.

**Unpaved Road** – is a long, narrow stretch without pavement used for traveling by motor passenger vehicle between two or more points. Unpaved roads are generally constructed of dirt, gravel, aggregate or macadam and may be improved or unimproved.

**Waste** - As defined in CWC Section 13050(d), “waste includes sewage and any and all other waste substances, liquid, solid, gaseous, or radioactive, associated with human habitation, or of human or animal origin, or from any producing, manufacturing, or processing operation, including waste placed within containers of whatever nature prior to, and for purposes of, disposal.”

Article 2 of CCR Title 23, Chapter 15 (Chapter 15) contains a waste classification system that applies to solid and semi-solid waste, which cannot be discharged directly or indirectly to water of the state and which therefore must be discharged to land for treatment, storage, or disposal in accordance with Chapter 15. There are four classifications of waste (listed in order of highest to lowest threat to water quality): hazardous waste, designated waste, non-hazardous solid waste, and inert waste.

**Water Quality Assessment** – Assessment conducted to evaluate the condition of non-storm water and storm water discharges, and the water bodies which receive these discharges.

**Water Quality Objective** - Numerical or narrative limits on constituents or characteristics of water designated to protect designated beneficial uses of the water. [California Water Code Section 13050 (h)]. California’s water quality objectives are established by the State and Regional Water Boards in the Water Quality Control Plans. Numeric or narrative limits for pollutants or characteristics of water designed to protect the beneficial uses of the water. In other words, a water quality objective is the maximum concentration of a pollutant that can exist in a receiving water and still generally ensure that the beneficial uses of the receiving water remain protected (i.e., not impaired). Since water quality objectives are designed specifically to protect the



beneficial uses, when the objectives are violated the beneficial uses are, by definition, no longer protected and become impaired. This is a fundamental concept under the Porter Cologne Act. Equally fundamental is Porter Cologne's definition of pollution. A condition of pollution exists when the water quality needed to support designated beneficial uses has become unreasonably affected or impaired; in other words, when the water quality objectives have been violated. These underlying definitions (regarding beneficial use protection) are the reason why all waste discharge requirements implementing the federal NPDES regulations require compliance with water quality objectives. (Water quality objectives are also called water quality criteria in the CWA.)

**Water Quality Standards** - The beneficial uses (e.g., swimming, fishing, municipal drinking water supply, etc.) of water and the water quality objectives necessary to protect those uses.

**Waters of the State** - Any water, surface or underground, including saline waters within the boundaries of the State [CWC section 13050 (e)]. The definition of the Waters of the State is broader than that for the Waters of the United States in that all water in the State is considered to be a Waters of the State regardless of circumstances or condition. Under this definition, a MS4 is always considered to be a Waters of the State.

**Waters of the United States** - As defined in the 40 CFR 122.2, the Waters of the U.S. are defined as: "(a) All waters, which are currently used, were used in the past, or may be susceptible to use in interstate or foreign commerce, including all waters which are subject to the ebb and flow of the tide; (b) All interstate waters, including interstate "wetlands;" (c) All other waters such as intrastate lakes, rivers, streams (including intermittent streams), mudflats, sandflats, "wetlands," sloughs, prairie potholes, wet meadows, playa lakes, or natural ponds the use, degradation or destruction of which would affect or could affect interstate or foreign commerce including any such waters: (1) Which are or could be used by interstate or foreign travelers for recreational or other purposes; (2) From which fish or shellfish are or could be taken and sold in interstate or foreign commerce; or (3) Which are used or could be used for industrial purposes by industries in interstate commerce; (d) All impoundments of waters otherwise defined as waters of the United States under this definition; (e) Tributaries of waters identified in paragraphs (a) through (d) of this definition; (f) The territorial seas; and (g) "Wetlands" adjacent to waters (other than waters that are themselves wetlands) identified in paragraphs (a) through (f) of this definition. Waters of the United States do not include prior converted cropland. Notwithstanding the determination of an area's status as prior converted cropland by any other federal agency, for the purposes of the Clean Water Act, the final authority regarding Clean Water Act jurisdiction remains with the EPA."

**Watershed** - That geographical area which drains to a specified point on a water course, usually a confluence of streams or rivers (also known as drainage area, catchment, or river basin).

**Watershed Runoff Management Plan (WRMP)** – A written description of the specific watershed runoff management measures and programs that each watershed group of Copermittees will implement to comply with this Order and ensure that storm water pollutant discharges in runoff are reduced to the MEP and do not cause or contribute to a violation of water quality standards.

**WDRs** – Waste Discharge Requirements

**ATTACHMENT D****SCHEDULED SUBMITTALS SUMMARY AND REPORTING CHECKLIST**

<b>Submittal</b>	<b>Permit Section</b>	<b>Completion Date</b>	<b>Frequency</b>
Prohibitions on dry-weather discharges not listed in Section B.2	B.2	July 1, 2012, then in JRMP Annual Report	Annual
Submit Certified Statement of Adequate Legal Authority	E.2	June 30, 2012	One time
Updated SSMP	F.1.d, K.2.a	June 30, 2012	One time
Identify and remove barriers to LID implementation	F.1.d.(4)(a)(v)	With JRMP Annual Report	Annual
Hydromodification Management Plan	F.1.h.(5), K.2.b	June 30, 2013	One Time for Draft
Flood Control Structure BMP Inventory and Evaluation	F.3.a.(4)	With JRMP Annual Report	Annual
Retrofitting Program	F.3.d.(3)	With JRMP Annual Report	Annual
Updated Watershed Workplans	G.1 K.1.b	June 30, 2012	One time
Fiscal Analysis	H.3	With JRMP Annual Report	Annual
Updated Jurisdictional Runoff Management Plans	K.1.a	June 30, 2012	One time
Report of Waste Discharge	K.2.c	At least 180 days prior to expiration of this Order	One time
Principal Copermittee submits JRMP Annual Reports to Regional Board	K.3.a.(2)	October 31, 2013 and annually thereafter	Annual
Principal Copermittee submits Notification of Principal Copermittee	M	180 days after adoption of the Order	One Time

**Jurisdictional Runoff Management Program Annual Report Checklist**

In the JRMP Annual Report each Copermitttee shall provide an Annual Report Checklist. The Annual Report Checklist must be no longer than 2 pages, be current as of the 1<sup>st</sup> day of the rainy season of that year, and include a signed certification statement. The Annual Report Summary Checklist must provide the following information:

Order Requirements

Were All Requirements of this Order Met?

Construction

Number of Active Sites  
Number of Inactive Sites  
Number of Sites Inspected  
Number of Inspections  
Number of Violations  
Number of Construction Enforcement Actions Taken

New Development

Number of Development Plan Reviews  
Number of Grading Permits Issued  
Number of Projects Exempted from Interim/Final Hydromodification Requirements

Post Construction Development

Number of Priority Development Projects  
Number of SUSMP Required Post-Construction BMP Inspections  
Number of SUSMP Required Post-Construction BMP Violations  
Number of SUSMP Required Post-Construction BMP Enforcement Actions Taken

Illicit Discharges and Connections

Number of IC/ID Inspections  
Number of IC/ID Detections by Staff  
Number of IC/ID Detections from the Public  
Number of IC/ID Eliminations  
Number of IC/ID Violations  
Number of IC/ID Enforcement Actions Taken

MS4 Maintenance

Number of Inspections Conducted  
Amount of Waste Removed  
Total Miles of MS4 Inspected

Municipal/Commercial/Industrial

Number of Facilities  
Number of Inspections Conducted  
Number of Facilities Inspected  
Number of Violations  
Number of Enforcement Actions Taken

## Attachment E

### RECEIVING WATERS AND MS4 DISCHARGE MONITORING AND REPORTING PROGRAM NO. R9-2010-0016

I.	PURPOSE .....	2
II.	MONITORING PROGRAM .....	2
A.	Receiving Waters Monitoring Program.....	3
1.	Mass Loading Station (MLS) Monitoring.....	3
2.	Stream Assessment Monitoring.....	6
3.	Follow-up Analysis and Actions.....	9
4.	Regional Monitoring Programs .....	10
B.	Wet Weather MS4 Discharge Monitoring .....	11
C.	Non-Storm Water Dry Weather Action Levels and IDDE .....	13
D.	High Priority Inland Aquatic Habitat Monitoring.....	15
E.	Special Studies .....	18
F.	Monitoring Provisions.....	22
III.	REPORTING PROGRAM .....	25
A.	Monitoring Reporting .....	25
B.	Interim Reporting Requirements .....	27
C.	Reporting Dates and Frequencies.....	28

## I. PURPOSE

- A. This Receiving Waters and MS4 Discharge Monitoring and Reporting Program (MRP) is intended to meet the following goals:
1. Assess compliance with Order No. R9-2010-0016;
  2. Measure and improve the effectiveness of the Copermittees' runoff management programs;
  3. Assess the chemical, physical, and biological impacts to receiving waters resulting from MS4 discharges;
  4. Characterize storm water discharges;
  5. Identify sources of specific pollutants;
  6. Prioritize drainage and sub-drainage areas that need management actions;
  7. Detect and eliminate illicit discharges and illicit connections to the MS4;
  8. Assess the overall health of receiving waters; and
  9. Provide information to implement required BMP improvements.
- B. This Receiving Waters and MS4 Discharges Monitoring and Reporting Program is designed to answer the following core management questions<sup>1</sup>:
1. Are conditions in receiving waters protective, or likely to be protective, of beneficial uses?
  2. What is the extent and magnitude of the current or potential receiving water problems?
  3. What is the relative MS4 discharge contribution to the receiving water problem(s)?
  4. What are the sources of MS4 discharge that contribute to receiving water problem(s)?
  5. Are conditions in receiving waters getting better or worse?

## II. MONITORING PROGRAM

The Monitoring Program is designed to assess the condition of receiving waters, monitor pollutants in storm and non-storm water effluent from the MS4, and conduct Special Studies to address conditions of concern. Where feasible, the Monitoring Program is designed to allow the Copermittees to combine required monitoring elements or efforts that are not mutually exclusive while still meeting the requirements of the Order.

---

<sup>1</sup> Core management questions from "Model Monitoring Program for Municipal Separate Storm Sewer Systems in Southern California: A report from the Stormwater Monitoring Coalition's Model Monitoring Technical Committee." Technical Report No. 419. August 2004.

## **A. Receiving Waters Monitoring Program**

Each Copermittee must collaborate with the other Copermittees to develop, conduct, and report on a year-round watershed based Receiving Waters Monitoring Program. The monitoring program design, implementation, analysis, assessment, and reporting must be conducted on a watershed basis for the Santa Margarita Hydrologic Unit (HU) and must be designed to meet the goals and answer the questions listed in section I above. The monitoring program must include the following components:

### **1. MASS LOADING STATION (MLS) MONITORING**

- a. Locations: The following existing mass loading stations must continue to be monitored: Lower Temecula Creek, Lower Murrieta Creek at the USGS Weir, and a permanent reference station.<sup>2</sup> Copermittees may propose, for San Diego Water Board review and approval, changing the location of a mass loading station.
- b. Frequency: Each mass loading station must be monitored each year three times during wet weather events and twice during dry weather flow conditions.
- c. Timing: Each mass loading station must be monitored for the first wet weather event of the season which meets USEPA's criteria described in 40 CFR 122.21(g)(7). Monitoring of the third wet weather event must be conducted after February 1. Dry weather mass loading monitoring events must be sampled at least three months apart between May and October. If flows are not evident for the second event, then sampling must be conducted during non-rain events in the following wet weather season.
- d. Protocols: Protocols for mass loading sampling and analysis including analytical methods, target reporting limits, and data reporting formats must be compatible with the State Water Resources Control Board's (State Water Board's) State Surface Water Ambient Monitoring Program (SWAMP). If the mass loading sampling and analysis are determined to be impracticable with the SWAMP standards, the Copermittees must provide a written explanation and discussion in the submittal of the Planned Monitoring Program. Wet weather samples must be flow-weighted composites, collected for the duration of the entire runoff event. Where such monitoring is not practical, such as for large watersheds with significant groundwater recharge flows, composites must be collected at a minimum during the first 3 hours of

---

<sup>2</sup> A map depicting mass loading stations can be found in the Fact Sheet for Order R9-2010-0016.

flow. Dry weather event sampling must be time-weighted composites composed of 24 discrete hourly samples, whereby the mass loads of pollutants are calculated as the product of the composite sample concentration and the total volume of water discharged past the monitoring point during the time of sample collection.

(1) Automatic samplers must be used to collect samples from mass loading stations.

(2) Grab samples must be analyzed for temperature, pH, specific conductance, biochemical oxygen demand, oil and grease, E. coli, fecal coliform, enterococcus and for total petroleum hydrocarbons whenever a sheen is observed.

- e. Copermittees must measure or estimate flow rates and volumes for each mass loading station sampling event to determine mass loadings of pollutants. Data from nearby USGS gauging stations may be utilized, or flow rates may be estimated in accordance with the USEPA Storm Water Sampling Guidance Document (EPA-833-B-92-001), Section 3.2.1.
- f. In the event that the required number of sampling events are not conducted during one monitoring year at any given station, the Copermittees must provide a written explanation for the reduced number of sampling events in the subsequent Receiving Waters Monitoring Annual Report. The explanation must include, at a minimum, streamflow data from the nearest USGS gauging station, a full description of any equipment failures and subsequent remedies if applicable, efforts made to resample a future event, and any quality assurance or quality control issues encountered. The explanation must also include a description of steps taken to prevent further sampling failures.
- g. The following constituents must be analyzed for each monitoring event at each station:

Table 1. Analytical Testing for Mass Loading (II.A.1) and Stream Assessment (II.A.2)

<b>Conventionals, Nutrients, Hydrocarbons</b>	<b>Pesticides</b>	<b>Metals (Total and Dissolved)</b>	<b>Bacteriological (mass loading)</b>
<ul style="list-style-type: none"> <li>• Total Dissolved Solids</li> <li>• Total Suspended Solids</li> <li>• Turbidity</li> <li>• Total Hardness</li> <li>• pH</li> <li>• Specific Conductance</li> <li>• Temperature</li> <li>• Dissolved Oxygen</li> <li>• Total Phosphorus</li> <li>• Dissolved Phosphorus</li> <li>• Nitrite<sup>°</sup></li> <li>• Nitrate<sup>°</sup></li> <li>• Total Kjeldahl Nitrogen</li> <li>• Ammonia</li> <li>• Biological Oxygen Demand, 5-day</li> <li>• Chemical Oxygen Demand</li> <li>• Total Organic Carbon</li> <li>• Dissolved Organic Carbon</li> <li>• Methylene Blue Active Substances</li> <li>• Oil and Grease</li> <li>• Sulfate</li> </ul>	<ul style="list-style-type: none"> <li>• Diazinon</li> <li>• Chlorpyrifos</li> <li>• Malathion</li> <li>• Carbamates</li> <li>• Pyrethroids</li> </ul>	<ul style="list-style-type: none"> <li>• Arsenic</li> <li>• Cadmium</li> <li>• Total Chromium</li> <li>• Hexavalent Chromium**</li> <li>• Copper</li> <li>• Lead</li> <li>• Iron</li> <li>• Manganese</li> <li>• Nickel</li> <li>• Selenium</li> <li>• Zinc</li> <li>• Mercury</li> <li>• Silver</li> <li>• Thallium</li> </ul>	<ul style="list-style-type: none"> <li>• E. coli</li> <li>• Fecal Coliform</li> <li>• Enterococcus</li> </ul>
<p><sup>°</sup> Nitrate and nitrite may be combined and reported as nitrate + nitrite.  <sup>**</sup> Hexavalent Chromium sampling must occur only for mass loading stations for the 1<sup>st</sup> wet weather event and 1 dry weather event.</p>			



- h. Toxicity testing must be conducted for each monitoring event at each station according to the following Table 2:

Table 2. Toxicity Testing for Mass Loading (II.A.1) and Stream Assessment (II.A.2)

Program Component	Dry Weather Flows	Storm Water Flows
	Freshwater Organisms	Freshwater Organisms
Mass Loading	3 chronic* 3 acute*	3 acute*
Stream Assessment**	3 chronic* 3 acute*	n/a
Sediment Toxicity Special Study	1 chronic 1 acute	n/a

Table Notes  
 \* Toxicity testing must include use of *Pimephales promelas* (fathead minnow), *Hyalella azteca* and *Pseudokirchneriella subcapitata* (formerly *Selenastrum capricornutum*, unicellular algae).  
 \*\* Duplicative toxicity testing is not required for Stream Assessment Monitoring stations co-located at mass loading stations since Stream Assessment Monitoring must be conducted in conjunction with dry weather mass loading.

Species Notes:  
 1. Acute toxicity may be determined during the course of chronic toxicity monitoring per U.S. EPA protocols.

- i. The presence of acute toxicity must be determined in accordance with USEPA protocol (EPA-821-R-02-012). The presence of chronic freshwater toxicity must be determined in accordance with USEPA protocol (EPA-821-R-02-013).

**2. Stream Assessment Monitoring**

Copermittees must conduct Stream Assessment Monitoring using multiple lines of evidence to assess the condition of biological communities in freshwater receiving waters. Stream assessment must include the collection and reporting of the following specified instream biological, chemical, and physical (including habitat) data.

- a. Locations: At a minimum, the program must consist of station identification, sampling, monitoring, and analysis of data for six stream assessment stations in order to determine the biological, chemical and physical integrity of streams within the County of Riverside. The two existing mass loading stations at Murrieta and Temecula Creeks must continue to be monitored. Copermittees may propose, for San Diego Water Board review and approval, changing the location of stream assessment monitoring stations where the mass loading stations

location has changed pursuant to section II.A.1.a. Two reference stream assessment stations, including the existing Adobe Creek station, must be identified, sampled, monitored, and analyzed. Locations of reference stations must be identified according to protocols outlined in “A Quantitative Tool for Assessing the Integrity of Southern Coastal California Streams,” by Ode, et al. 2005.<sup>3</sup>

- b. Frequency: Stream assessment stations must be monitored in May or June (to represent the influence of wet weather on the communities). The timing of monitoring of stream assessment stations located at mass loading stations must coincide with dry weather monitoring of those mass loading stations.
- c. Parameters / Methods: Stream assessment monitoring must include bioassessment, aquatic chemistry, and aqueous toxicity.
  - (1) Aquatic chemistry and aqueous toxicity must be conducted as outlined in Tables 1 and 2 using the same parameters and methods as the mass loading station monitoring.
  - (2) Bioassessment analysis procedures must include calculation of the Index of Biotic Integrity (IBI) for benthic macroinvertebrates for all bioassessment stations, as outlined in “A Quantitative Tool for Assessing the Integrity of Southern Coastal California Streams,” by Ode, et al. 2005.
  - (3) Monitoring of stream assessment stations must be conducted according to the most current bioassessment Standard Operating Procedures (SOP) developed by the Surface Water Ambient Monitoring Program (SWAMP), and amendments, as applicable.<sup>4</sup> In collecting macroinvertebrate samples, the discharger must use the “Reachwide Benthos (Multihabitat) Procedure.” The discharger must conduct, concurrently with all required macroinvertebrate collections, the “full” suite of physical/habitat characterization measurements specified in the SWAMP Bioassessment SOP, and as summarized in the *SWAMP Stream Habitat Characterization Form — Full Version*.<sup>5</sup>

---

<sup>3</sup> Ode, et al. 2005. “A Quantitative Tool for Assessing the Integrity of Southern Coastal California Streams.” Environmental Management. Vol. 35, No. 1, pp. 1-13.

<sup>4</sup> Ode, P.R.. 2007. Standard operating procedures for collecting macroinvertebrate samples and associated physical and chemical data for ambient bioassessments in California. California State Water Resources Control Board Surface Water Ambient Monitoring Program (SWAMP) Bioassessment SOP 001.

[http://www.swrcb.ca.gov/water\\_issues/programs/swamp/tools.shtml#monitoring](http://www.swrcb.ca.gov/water_issues/programs/swamp/tools.shtml#monitoring)

<sup>5</sup> Available at:

[http://www.waterboards.ca.gov/water\\_issues/programs/swamp/docs/reports/fieldforms\\_fullversion052908.pdf](http://www.waterboards.ca.gov/water_issues/programs/swamp/docs/reports/fieldforms_fullversion052908.pdf)

- (4) Monitoring of stream assessment stations must incorporate assessment of algae using SWAMP's SOP for Collecting Stream Algae Samples.<sup>6</sup> Assessment of freshwater algae must include algal taxonomic composition (diatoms and soft algae) and algal biomass. Future bioassessment must incorporate algal IBI scores, when developed.
- d. A qualified professional environmental laboratory must perform all sampling, laboratory, quality assurance, and analytical procedures in accordance with the Southern California Regional Watershed Monitoring Program Bioassessment Quality Assurance Project Plan.<sup>7</sup> The Copermittees must utilize future Quality Assurance Project Plans as developed by SWAMP.
- (1) The Copermittees must have and follow a quality assurance (QA) plan that covers the required stream assessment monitoring. External QA checks must be funded by the Copermittees, and performed by the California Department of Fish and Game's Aquatic Bioassessment Laboratory. An alternate laboratory with equivalent expertise and performance may be used if approved in advance in writing by San Diego Water Board.
- (2) Identified organisms must be archived (i.e., retained) by the Copermittee(s) for a period of not less than three years from the date that all QA steps are completed. The identified organisms must be relinquished to the San Diego Water Board upon request by the San Diego Water Board.
- (3) The macroinvertebrate results (i.e., taxonomic identifications consistent with the specified SAFIT STEs, and number of organisms within each taxa) must be submitted to the San Diego Water Board in electronic format. SWAMP is currently developing standardized formats for reporting bioassessment data. All bioassessment data collected after those formats become available must be submitted using the SWAMP formats. Until those formats are available, the biological data must be submitted in MS-Excel<sup>8</sup> (or equivalent) format.

---

<sup>6</sup> Fetscher et al. 2009. Standard Operating Procedures for Collecting Stream Algae Samples and Associated Physical Habitat and Chemical Data for Ambient Bioassessments in California.

<sup>7</sup> Version 1.0 of the Southern California Regional Watershed Monitoring Program Bioassessment Quality Assurance Program Plan was released on June 25, 2009.

<sup>8</sup> Any version of Excel, 2000 or later, may be used.

The physical/habitat data must be reported using the standard format titled *SWAMP Stream Habitat Characterization Form — Full Version*.

**3. FOLLOW-UP ANALYSIS AND ACTIONS (TIE AND TRE TRIAD APPROACH)**

When results from the required monitoring indicate adverse water quality effects at a mass loading station or stream assessment station as defined in Table 3, Copermittees within the watershed(s) that discharge to that location must evaluate the extent and causes of MS4 discharge pollution to the adverse effects in receiving waters and prioritize and implement management actions to eliminate non-storm water discharges and/or reduce storm water sources from the MS4 as described in Table 3. Toxicity Identification Evaluations (TIEs) must be conducted to determine the cause of toxicity as outlined in Table 3 below. Other follow-up activities, which must be conducted by the Copermittees, are also identified in Table 3. Once the cause of toxicity has been identified by a TIE, the Copermittees must perform source identification projects as needed and implement the measures necessary to reduce or eliminate the pollutant discharges and abate the sources causing the toxicity.

Table 3. Triad Approach to Determining Follow-Up Actions<sup>9</sup>

Chemistry	Toxicity	Benthic Alteration	Example Conclusions	Possible Actions or Decisions
1. Exceedance of water quality objectives	Evidence of toxicity	Indications of alteration	Strong evidence of pollution-induced degradation	Use TIE to identify contaminants of concern, based on TIE metric Initiate upstream source identification as a high priority
2. No persistent exceedances of water quality objectives	No evidence of toxicity	No indications of alteration	No evidence of current pollution-induced degradation Potentially harmful pollutants not yet concentrated enough to cause visible impact	No immediate action necessary Conduct periodic broad scans for new and/or potentially harmful pollutants
3. Exceedance of water quality objectives	No evidence of toxicity	No indications of alteration	Contaminants are not bioavailable Test organisms not sensitive to problem pollutants	TIE would not provide useful information with no evidence of toxicity Continue monitoring for toxic and benthic impacts Initiate upstream source identification as a low priority Consider whether different or additional test organisms should be evaluated
4. No persistent exceedances of water quality objectives	Evidence of toxicity	No indications of alteration	Unmeasured contaminant(s) or conditions have the potential to cause degradation Pollutant causing toxicity at very low levels	Recheck chemical analyses; verify toxicity test results Consider additional advanced chemical analyses Use TIE to identify contaminants of concern, based on TIE metric Initiate upstream source identification as a medium priority
5. No persistent exceedances of water quality objectives	No evidence of toxicity	Indications of alteration	Alteration may not be due to toxic contamination Test organisms not sensitive to problem pollutants	No action necessary due to toxic chemicals Initiate upstream source identification (for physical sources) as a high priority Consider whether different or additional test organisms should be evaluated
6. Exceedance of water quality objectives	Evidence of toxicity	No indications of alteration	Toxic contaminants are bioavailable, but in situ effects are not demonstrable Benthic analysis not sensitive enough to detect impact Potentially harmful pollutants not yet concentrated enough to change community	Determine if chemical and toxicity tests indicate persistent degradation Recheck benthic analyses; consider additional data analyses If recheck indicates benthic alteration, perform TIE to identify contaminants of concern, based on TIE metric Initiate upstream source identification as a high priority If recheck shows no effect, use TIE to identify contaminants of concern, based on TIE metric Initiate upstream source identification as a medium priority
7. No persistent exceedances of water quality objectives	Evidence of toxicity	Indications of alteration	Unmeasured toxic contaminants are causing degradation Pollutant causing toxicity at very low levels Benthic impact due to habitat disturbance, not toxicity	Recheck chemical analyses and consider additional advanced analyses Use TIE to identify contaminants of concern, based on TIE metric Initiate upstream source identification as a high priority Consider potential role of physical habitat disturbance
8. Exceedance of water quality objectives	No evidence of toxicity	Indications of alteration	Test organisms not sensitive to problem pollutants Benthic impact due to habitat disturbance, not toxicity	TIE would not provide useful information with no evidence of toxicity Initiate upstream source identification as a high priority Consider whether different or additional test organisms should be evaluated Consider potential role of physical habitat disturbance

#### 4. REGIONAL MONITORING PROGRAMS

The San Diego Water Board recognizes the importance and advantages of participation by Copermittees in Regional Monitoring Programs. As such, the Copermittees may propose participation in additional regional monitoring programs to supplement and/or replace monitoring required under this Order. The regional monitoring plan must be submitted to the San Diego Water Board<sup>10</sup> for review and approval. Documentation of participation and monitoring must be included in the annual report(s).

<sup>9</sup> Model Monitoring Program for Municipal Separate Storm Sewer Systems in Southern California. Stormwater Monitoring Coalition August 2004. See Table 5-4 for definitions.

<sup>10</sup> For the purposes of Receiving Waters and MS4 Discharge Monitoring and Reporting Program No. R9-2010-0016, review and approval by the San Diego Water Board of draft monitoring plans, proposals or protocols shall be conducted by the San Diego Water Board Executive Officer.

## **B. Wet Weather MS4 Discharge Monitoring**

Each Copermitttee must collaborate with the other Copermitttees to develop, conduct, and report on a year-round, watershed-based, Wet Weather MS4 Discharge Monitoring Program. The monitoring program design, implementation, analysis, assessment, and reporting must be conducted on a watershed basis for each of the hydrologic subareas within the Santa Margarita HU under jurisdiction of the Copermitttees. The monitoring program must be designed to meet the goals, and answer the questions, listed in Section I above, as well as to implement required Storm Water Action Levels (SALs) in the Order. The monitoring program must include the following components;

### **1. MS4 OUTFALL MONITORING**

The Copermitttees must collaborate to develop and implement a monitoring program to characterize pollutant discharges from MS4 outfalls in each watershed during wet weather. The program must include the rationale and criteria for selection of outfalls to be monitored. The program must, at a minimum, include collection of samples for pollutants listed in Table 4 (below). This monitoring program must be designed to sample a representative percentage<sup>11</sup> of the major outfalls within each hydrologic subarea and must begin no later than the 2012-2013 monitoring year.

- a. The program must comply with Section D of this Order for Storm Water Action Levels (SALs). Samples must be collected during the first 24 hours of the storm water discharge or for the entire storm water discharge if it is less than 24 hours.
  - (1) Grab samples may be utilized only for pH, indicator bacteria, DO, temperature and hardness.
  - (2) All other constituents must be sampled using 24-hour composite samples or for the entire storm water discharge if the storm event is less than 24 hours.
- b. Sampling to compare MS4 outfall discharges with total metal SALs must include a measurement of receiving water hardness at each outfall. If a total metal concentration exceeds a SAL in Section D of

---

<sup>11</sup> A representative percentage determination must consider hydrologic conditions, total drainage area of the site, population density of the site, traffic density, age of the structures or buildings in the area, and land use types (commercial, residential and industrial).

the Order, that concentration must be compared to the California Toxic Rule criteria and the USEPA 1-hour maximum concentration for the detected level of receiving water hardness associated with that sample. If it is determined that the sample's total metal concentration for that specific pollutant exceeds the SAL but does not exceed the applicable 1-hour criteria for the measured level of hardness, then the SAL shall be considered not exceeded for that measurement.

Table 4. Analytical Testing for Wet Weather MS4 Discharges

Conventionals, Nutrients, Hydrocarbons	Pesticides	Metals (Total and Dissolved)	Bacteriological
<ul style="list-style-type: none"> <li>• Total Dissolved Solids</li> <li>• Total Suspended Solids</li> <li>• Turbidity*</li> <li>• Total Hardness</li> <li>• pH</li> <li>• Specific Conductance</li> <li>• Temperature</li> <li>• Dissolved Oxygen</li> <li>• Total Phosphorus*</li> <li>• Dissolved Phosphorus</li> <li>• Nitrite *</li> <li>• Nitrate *</li> <li>• Total Kjeldahl Nitrogen</li> <li>• Ammonia</li> <li>• Biological Oxygen Demand, 5-day</li> <li>• Chemical Oxygen Demand</li> <li>• Total Organic Carbon</li> <li>• Dissolved Organic Carbon</li> <li>• Oil and Grease</li> <li>• Sulfate</li> </ul>	<ul style="list-style-type: none"> <li>• Diazinon</li> <li>• Chlorpyrifos</li> <li>• Pyrethroids</li> </ul>	<ul style="list-style-type: none"> <li>• Arsenic</li> <li>• Cadmium*</li> <li>• Chromium</li> <li>• Copper*</li> <li>• Lead*</li> <li>• Nickel</li> <li>• Selenium</li> <li>• Zinc*</li> <li>• Mercury</li> <li>• Silver</li> <li>• Thallium</li> <li>• Iron</li> <li>• Manganese</li> </ul>	<ul style="list-style-type: none"> <li>• Fecal Coliform</li> <li>• Enterococcus</li> <li>• E. coli</li> </ul>
<p>° Nitrate and nitrite may be combined and reported as nitrate + nitrite. ★Pollutant for which there is a Storm Water Action Level</p>			

## 2. SOURCE IDENTIFICATION MONITORING

The Copermittees must collaborate to develop and implement a monitoring program to identify sources of pollutants causing the priority water quality problems within each hydrologic subarea. The monitoring program must include focused monitoring which moves upstream into each watershed as necessary to identify sources. This monitoring program must be implemented within each hydrologic subarea and must begin no later than the 2012-2013 monitoring year.

### 3. COMMENCEMENT OF MS4 OUTFALL AND SOURCE IDENTIFICATION MONITORING

The Principal Copermittee must submit to the San Diego Water Board for review and approval, a detailed draft of the wet weather MS4 discharge monitoring program to be implemented. The description must identify and provide the rationale for all constituents monitored, locations of monitoring, frequency of monitoring, and analyses to be conducted with the data generated. The draft must be submitted with the proposed monitoring program (Section III.A.1).

### **C. Non-Storm Water Dry Weather Action Levels and Illicit Discharge Detection and Elimination**

Each Copermittee must collaborate with the other Copermittees to conduct, and report on a year-round watershed based Dry Weather Non-storm Water MS4 Discharge Monitoring Program. The monitoring program's implementation, analysis, assessment, and reporting must be conducted to assess compliance with section B and C of this Order, meet the goals of the MRP, and conduct Illicit Discharge Detection and Elimination Activities under Section F.4 of this Order. The monitoring program must also be designed to assess the contribution of dry weather flows to Clean Water Act Section 303(d) listed impairments. The monitoring program must include the following components:

#### 1. MS4 OUTFALL MONITORING

Each Copermittee's program must be designed to determine levels of pollutants in effluent discharges from the MS4 into receiving waters. Each Copermittee must conduct the following dry weather field screening and analytical monitoring tasks:

##### a. Dry Weather Non-storm Water Effluent Analytical Monitoring Station Identification

(1) Sampling Stations must be located at major outfalls pursuant to section C of this Order. Other outfall sampling points (or any other point of access such as manholes) identified by the Copermittees as potential high risk sources of polluted effluent or as identified under Section C.4 of the Order must be sampled.

(2) Each Copermittee must clearly identify each dry weather effluent analytical monitoring station on its MS4 Map as either a separate GIS layer or a map overlay hereinafter referred to as a Dry Weather Non-storm Water Effluent Analytical Stations Map.



b. Develop Dry Weather Non-storm Water Effluent Analytical Monitoring Procedures

Each Copermittee must develop and/or update written procedures for effluent analytical monitoring including field observations, monitoring, and analyses to be conducted. These procedures must be consistent with 40 CFR part 136. At a minimum, the procedures must meet the following guidelines and criteria:

- (1) Determining Sampling Frequency: Effluent analytical monitoring must be conducted at major outfalls and identified stations. The Copermittees must sample a representative percentage of major outfalls and identified stations within each hydrologic subarea.<sup>12</sup> The sampling must be done to assess compliance with dry weather non-storm water action levels pursuant to section C of this Order. All monitoring conducted must be preceded by a minimum of 72 hours of dry weather.
- (2) Sampling of non-storm water discharges may be done utilizing grab samples. If a ponded MS4 discharge is observed at a monitoring station, the Copermittee(s) must record the observation and collect at least one (1) grab sample. If flow is evident, a 1-hour composite sample may be taken. The Copermittee(s) must estimate the discharge flow by measuring the width of water surface, approximate depth of water, and approximate flow velocity. A flow meter may also be utilized.
- (3) Effluent samples must undergo analytical laboratory analysis for (a) all constituents described in *Table 1. Analytical Testing for Mass Loading and Stream Assessment* of this Order; (b) Constituents with assigned non-storm water action levels under Section C of this Order; and (c) Total Residual Chlorine.
- (4) If the station is dry (i.e. no flowing or ponded MS4 discharge is observed), the Copermittee(s) must make and record all applicable observations on the MS4 outfall and receiving waters, including any evidence of past non-storm water flows and the presence of trash.

---

<sup>12</sup> A representative percentage determination must consider hydrologic conditions, total drainage area of the site, population density of the site, traffic density, age of the structures or buildings in the area, and land use types (commercial, residential and industrial).

## 2. SOURCE IDENTIFICATION MONITORING

The Copermittees must collaborate to develop and implement a monitoring program to identify sources of pollutants in non-storm water discharges in accordance with Sections C and F.4 of this Order. The source identification portion of the monitoring program must include: the following components:

- a. Development and/or update of response criteria for dry weather non-storm water effluent analytical monitoring results:
  - (1) Response criteria must include action levels described in Section C of this Order.
  - (2) Response criteria must include evaluation of LC<sub>50</sub> levels for toxicity to appropriate test organisms.
- b. Develop and/or update Illicit Discharge Detection and Elimination response procedures for source identification follow up investigations and elimination in the event of exceedance of dry weather non-storm water effluent analytical monitoring response criteria (see above). These procedures must be consistent with procedures required in section C, F.4.d, and F.4.e. of this Order.

## 3. COMMENCEMENT OF MS4 OUTFALL AND SOURCE IDENTIFICATION MONITORING

The Copermittees must commence implementation of dry weather effluent analytical monitoring under the requirements of this Order no later than **July 1, 2012**. If monitoring indicates an illicit connection or illegal discharge, the Copermittee(s) must conduct the follow-up investigation and elimination activities described in sections C, F.4.d and F.4.e of this Order. In the interim period until the dry weather non-storm water effluent analytical monitoring program of this Order is implemented, each Copermittee must continue to implement dry weather field screening and analytical monitoring as it was most recently implemented pursuant to Order No. 2004-001.

### **D. High Priority Inland Aquatic Habitat Monitoring**

The Copermittees must develop and submit to the San Diego Water Board by April 01, 2012, an inland aquatic habitat monitoring program for areas supporting high priority aquatic and/or riparian species. The goal of the monitoring program is to assess if MS4 storm water and non-storm water

discharges are affecting high priority inland aquatic habitat. The monitoring will assist the Copermittees in preventing the degradation of high quality waters within the jurisdiction of this Order that support high priority species by identifying discharges from MS4s which may cause or have the potential to cause impairment of beneficial uses within these areas.<sup>13</sup> High priority species include those federally and/or state listed as endangered, threatened, or as a species of concern. The design and goal of the monitoring program must be consistent with the criteria listed in Section I.B of this Monitoring Program, including evaluation of the protection of high priority species in receiving waters. The Copermittees must implement the program unless otherwise directed in writing by the San Diego Water Board.

The monitoring program must include the following components:

1. OUTFALL AND RECEIVING WATER MONITORING

The program must be designed to determine levels of pollutants in storm water and non-storm water effluent discharges from the MS4 discharged into high priority inland aquatic habitat(s) and the level of those pollutants found in ambient receiving waters subject to the discharge. The Copermittees must conduct the following field screening and analytical monitoring tasks:

a. MS4 and Receiving Waters Monitoring Station Identification

- (1) MS4 discharge stations must be major outfalls that directly discharge into high priority inland aquatic habitat. MS4 discharge stations may be selected in conjunction with monitoring required under Section II.B and II.C of the Receiving Waters and MS4 Discharge Monitoring Program.
- (2) Receiving water station(s) must be located upstream and downstream of the discharge within the high priority inland aquatic habitat. Receiving water stations must be located to prevent any significant co-mingling of receiving water flows with other sources.

---

<sup>13</sup> In accordance with requirements of State Water Resources Control Board Resolution No. 68-16, Statement of Policy with Respect to Maintaining High Quality Waters in California.

b. Develop Analytical Monitoring Procedures

Each Copermittee must develop procedures for analytical monitoring (these procedures must be consistent with 40 CFR part 136), including field observations, pollutants to be monitored, analyses to be conducted, and quality assurance/control. At a minimum, the procedures must meet the following guidelines and criteria:

- (1) Determining Sampling Frequency: The Copermittees must sample a representative number of major outfalls and receiving waters that are considered high priority inland aquatic habitat. Sampling of the discharge and receiving waters must be paired and occur during both storm and non-storm conditions.
- (2) Sampling in receiving waters may be done utilizing grab samples, though composite samples are encouraged. Sampling of storm and non-storm water discharges from the MS4 must be done in accordance with Section II.B and II.C. If ponded receiving waters is/are observed at a monitoring station, the Copermittees must make written observations and collect at least one (1) grab sample. The Copermittee(s) must estimate the flow by measuring the width of water surface, approximate depth of water, and approximate flow velocity
- (3) The proposed constituents for which samples will undergo analytical laboratory analysis.
- (4) Procedures for recording applicable observations when monitoring stations are dry (i.e. no flowing water or ponded conditions).

3. ASSESSMENT OF MONITORING RESULTS

The program must include a discussion of monitoring results within the monitoring annual report. The discussion must include an evaluation of the contribution of MS4 discharges to ambient water conditions within high priority inland aquatic habitats, as well as any actions taken to prevent and/or reduce sources of those pollutants.

4. SOURCE IDENTIFICATION MONITORING

The Copermittees must collaborate to conduct source identification monitoring in accordance with Section II.B and II.C of the Monitoring and Reporting Program of this Order.

## **E. Special Studies**

1. The Copermitees must conduct special studies, including any monitoring and/or modeling required for TMDL development and implementation, as directed by the San Diego Water Board.
2. Sediment Toxicity Study

The Copermitees must develop and submit to the San Diego Water Board by April 01, 2012, a special study workplan to investigate the toxicity of sediment in streams and potential impact on benthic macroinvertebrate IBI scores. The Sediment Toxicity Special Study must be implemented in conjunction with the Stream Assessment Monitoring in II.A.2. The Copermitees must implement the special study unless otherwise directed in writing by the San Diego Water Board.

The Sediment Toxicity Special Study must include the following elements:

- a. Sampling Locations: At least 4 stream assessment locations must be sampled, including 1 reference site and 1 mass loading site. Selection of sites must be done with consideration of subjectivity of receiving waters to discharges from residential and agricultural land uses.
- b. Frequency: At a minimum, sampling must occur once per year at each site for at least 2 years. Sampling must be done in conjunction with the stream assessment sampling required under Section II.A.2 of the Monitoring and Reporting Program of this Order.
- c. Parameters/Methods: At a minimum, sediment toxicity analysis must include the measurement of metals, pyrethroids and organochlorine pesticides. The analysis must include estimates of bioavailability based upon sediment grain size, organic carbon and receiving water temperature at the sampling site. Acute and chronic toxicity testing must be done using *Hyalella azteca* in accordance with Table 2.
- d. Results: Results and a Discussion must be included in the Monitoring Annual Report (see III.A). The Discussion must include an assessment of the relationship between observed IBI scores under Section II.A.2 and all variables measured.

### 3. Trash and Litter Investigation

The Copermittees must develop and submit to the San Diego Water Board by September 01, 2012, a special study workplan to assess trash (including litter) as a pollutant within receiving waters on a watershed based scale. Litter is defined in California Government Code 68055.1g as "...improperly discarded waste material, including, but not limited to, convenience food, beverage, and other product packages or container constructed of steel, aluminum, glass, paper, plastic and other natural and synthetic, materials, thrown or deposited on lands and waters of the state, but not including the properly discarded waste of the primary processing of agriculture, mining, logging, sawmilling, or manufacturing." A lead Copermittee must be selected for the Santa Margarita HU for the purposes of this Special Study. The Copermittees must implement the special study unless otherwise directed in writing by the San Diego Water Board

The Trash and Litter Investigation must include the following elements:

- a. Locations: The lead Copermittee must identify suitable sampling locations within the Santa Margarita HU.
- b. Frequency: Trash at each location must be monitored a minimum of twice during the wet season following a qualified monitoring storm event (minimum of 0.1 inches preceded by 72 hours of dry weather) and twice during the dry season.
- c. Protocol: The lead Copermittee for the Santa Margarita HU must use the "Final Monitoring Workplan for the Assessment of Trash in San Diego County Watersheds" and "A Rapid Trash Assessment Method Applied to Waters of the San Francisco Bay Region" to develop a monitoring protocol for the Santa Margarita HU.
- d. Results and Discussion from the Trash and Litter Study must be included in the Monitoring Annual Report. The Results and Discussion must, at a minimum, include source identification, an evaluation of BMPs for trash reduction and prevention, and a description of any BMPs implemented in response to study results.

### 4. Agricultural, Federal and Tribal Input Study

The Copermittees must develop and submit to the San Diego Water Board by September 01, 2012, a special study workplan to investigate the water quality of agricultural, federal and tribal runoff that is discharged into

their MS4 (see Finding D.3.c of the Order). The Copermittees must implement the special study unless otherwise directed in writing by the San Diego Water Board.

The Agricultural, Federal and Tribal Input Special Study must include the following elements:

- a. Locations: The Copermittees must identify a representative number of sampling stations within their MS4 that receive discharges of agricultural, federal, and tribal runoff that has not co-mingled with any other source. At least one station from each category must be identified.
  - b. Frequency: One storm event must be monitored at each sampling location each year for at least 2 years.
  - c. Parameters/Methods: At a minimum, analysis must include those constituents listed in Table 1 of the MRP (see II.A.1). Grab samples may be utilized, though composite samples are preferred. Copermittees must also measure or estimate flow rates and volumes of discharges into the MS4.
  - d. Results: Results and Discussion from the Agricultural, Federal and Tribal Input Study must be included in the Monitoring Annual Report.
5. MS4 and Receiving Water Maintenance Study

The Copermittees must develop and submit to the San Diego Water Board by April 01, 2012, a special study workplan to investigate receiving waters that are also considered part of the MS4 (see Finding D.3.c of the Order) and which are subject to continual vegetative clearance activities (e.g. mowing). The study must be designed to assess the effects of vegetation removal activities and water quality, including, but not limited to, modification of biogeochemical functions, in-stream temperatures, receiving water bed and bank erosion potential and sediment transport. The Copermittees must implement the special study unless otherwise directed in writing by the San Diego Water Board.

The MS4 and Receiving Water Maintenance Special Study must include the following elements:

- a. Locations: The Copermittees must identify suitable sampling locations, including at least one reference system that is not subject to maintenance activities.

- b. Parameters/Methods: At a minimum, the Copermittees must monitor pre and post maintenance activities for indicator bacteria, turbidity (NTU), temperature, dissolved oxygen and nutrients (Nitrite, Nitrate, Total Kjeldahl Nitrogen, Ammonia and Total Phosphorous). Copermittees must also measure or estimate flow rates and volumes.
- c. Results and Discussion from the MS4 and Receiving Water Maintenance Study must be included in the Annual Monitoring Report. The Discussion must include relevance of findings to CWA Section 303(d) listed impaired waters.

#### 6. Intermittent and Ephemeral Stream Perennial Conversion Study

The Copermittees must develop and submit to the San Diego Water Board by April 01, 2013, a special study workplan to investigate the extent of any impacts to beneficial uses from the conversion of historically ephemeral or intermittent receiving waters to perennially flowing waters due to the continued discharge of currently exempted non-storm water from the MS4 and/or discharges into MS4s covered under a separate NPDES permit into receiving waters. The goal of the study is to assess if any impacts to beneficial uses, including, but not limited to, WILD, WARM, COLD or RARE, have occurred due to continuous discharge of currently exempted non-storm water discharges, and if the discharges should no longer be exempt. The Copermittees must implement the special study unless otherwise directed in writing by the San Diego Water Board.

The Intermittent and Ephemeral Stream Perennial Conversion Special Study must include the following elements:

- a. Locations: The Copermittees must investigate their MS4 and adjacent downstream receiving waters to identify portions that have historically been ephemeral or intermittent but currently exhibit perennial flow due to exempted non-storm water discharges. Investigation must include historic habitat assessments, USGS gauging information, and historic aerial photography. Sampling must occur at a minimum of 2 identified perennially converted locations. Should the Copermittees be unable to locate any converted waters, a full description of the investigation must be documented in the annual report.



- b. Parameters/Methods: The Copermitees must conduct water quality monitoring of the non-storm water discharge in accordance with Section C of this Order. In addition, the Copermitees must select a minimum of 2 downstream sampling points within the receiving waters subject the discharge and conduct the following:
    - (1) Grab samples must be taken and analyzed for indicator bacteria, nutrients (Nitrite, Nitrate, Total Kjeldahl Nitrogen, Ammonia and Total Phosphorous), turbidity (NTU), temperature, dissolved oxygen, total hardness, pH and 303(d) listed pollutants for all receiving waters at or downstream of the sampling site. The Copermitees must measure or estimate flow rates and volumes at each sampling point.
    - (2) Sampling at each site must include a quantitative and qualitative evaluation of beneficial uses. At a minimum, sampling must include observation estimation of active bed and bank erosion and erosion potential, invasive/non-native plant cover, aquatic non-native species, and potential vector control requirements.
  - c. Results and Discussion from the Intermittent and Ephemeral Stream Perennial Conversion Study must be included in the Annual Monitoring Report.
7. Stormwater Monitoring Coalition (SMC) Regional Monitoring of Southern California Coastal Watersheds:

The Copermitees must implement the monitoring program developed by the SMC for Regional Monitoring of the southern California coastal watersheds within the Santa Margarita Hydrologic Unit. Each Copermitee must evaluate the results of the monitoring program within and downstream of their jurisdiction and integrate the results into program assessments and modifications.

## **F. Monitoring Provisions**

All monitoring activities must meet the following requirements:

1. Where procedures are not otherwise specified in this Receiving Waters Monitoring and Reporting Program, sampling, analysis and quality assurance/quality control must be conducted in accordance with the Quality Assurance Management Plan (QAMP) for the State of California's Surface Water Ambient Monitoring Program (SWAMP), adopted by the State Water Resources Control Board (SWRCB).

2. Samples and measurements taken for the purpose of monitoring must be representative of the monitored activity [40 CFR 122.41(j)(1)].
3. The Copermitees must retain records of all monitoring information, including all calibration and maintenance of monitoring instrumentation, copies of all reports required by this Order, and records of all data used to complete the Report of Waste Discharge and application for this Order, for a period of at least five (5) years from the date of the sample, measurement, report, or application. This period may be extended by request of the San Diego Water Board or USEPA at any time and must be extended during the course of any unresolved litigation regarding this discharge. [40 CFR 122.41(j)(2), CWC section 13383(a)]
4. Records of monitoring information must include [40 CFR 122.41(j)(3)]:
  - a. The date, exact place, and time of sampling or measurements;
  - b. The individual(s) who performed the sampling or measurements;
  - c. The date(s) analyses were performed;
  - d. The individual(s) who performed the analyses;
  - e. The analytical techniques or methods used; and
  - f. The results of such analyses.
5. All sampling, sample preservation, and analyses must be conducted according to test procedures approved under 40 CFR part 136, unless other test procedures have been specified in this Receiving Waters Monitoring and Reporting Program or approved by the San Diego Water Board [40 CFR 122.41(j)(4)].
6. The CWA provides that any person who falsifies, tampers with, or knowingly renders inaccurate any monitoring device or method required to be maintained under this Order must, upon conviction, be punished by a fine of not more than \$10,000, or by imprisonment for not more than two years, or both. If a conviction of a person is for a violation committed after a first conviction of such person under this paragraph, punishment is a fine of not more than \$20,000 per day of violation, or by imprisonment of not more than four years, or both. [40 CFR 122.41(j)(5)]
7. Calculations for all limitations which require averaging of measurements must utilize an arithmetic mean unless otherwise specified in this Receiving Waters Monitoring and Reporting Program. [40 CFR 122.41(l)(4)(iii)]

8. All chemical, bacteriological, and toxicity analyses must be conducted at a laboratory certified for such analyses by the California Department of Health Services or a laboratory approved by the San Diego Water Board.
9. For priority toxic pollutants that are identified in the California Toxics Rule (CTR) (65 Fed. Reg. 31682), the Copermittees must instruct their laboratories to establish calibration standards that are equivalent to or lower than the Minimum Levels (MLs) published in Appendix 4 of the Policy for Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bays, and Estuaries of California (SIP). If a Copermittee can demonstrate that a particular ML is not attainable, in accordance with procedures set forth in 40 CFR 136, the lowest quantifiable concentration of the lowest calibration standard analyzed by a specific analytical procedure (assuming that all the method specified sample weights, volumes, and processing steps have been followed) may be used instead of the ML listed in Appendix 4 of the SIP. The Copermittee must submit documentation from the laboratory to the San Diego Water Board for approval prior to raising the ML for any priority toxic pollutant.
10. The San Diego Water Board may make revisions to this Receiving Waters and MS4 Discharge Monitoring and Reporting Program at any time during the term of Order No. R9-2010-0016 and may include a reduction or increase in the number of parameters to be monitored, locations monitored, the frequency of monitoring, or the number and size of samples collected.
11. The Clean Water Act provides that any person who knowingly makes any false statement, representation, or certification in any record or other document submitted or required to be maintained under this permit, including monitoring reports or reports of compliance or non-compliance must, upon conviction, be punished by a fine of not more than \$10,000 per violation, or by imprisonment for not more than six months per violation, or by both. [40 CFR 122.41(k)(2)]
12. Monitoring must be conducted according the USEPA test procedures approved under 40 CFR 136, "Guidelines Establishing Test Procedures for Analysis of Pollutants under the Clean Water Act" as amended, unless other test procedures have been specified in this Receiving Waters and MS4 Discharge Monitoring and Reporting Program, in Order No. R9-2010-0016, or by the San Diego Water Board.
13. If a Copermittee(s) monitors any pollutant more frequently than required by the permit using test procedures approved under 40 CFR part 136, unless otherwise specified in the Order, the results of this monitoring must

be included in the calculation and reporting of the data submitted in the reports requested by the San Diego Water Board. [40 CFR 122.41(l)(4)(ii)]

### III. REPORTING PROGRAM

#### A. Monitoring Reporting

1. Planned Monitoring Program: The Principal Copermittee must submit to the San Diego Water Board by **June 1, 2012**, a proposed workplan describing the Receiving Waters and MS4 Discharge Monitoring Program to be implemented. Any updates to the planned monitoring program workplan proposed by the Copermittees shall be submitted with each Monitoring Annual Report. The Copermittees shall implement the proposed workplan unless otherwise directed in writing by the San Diego Water Board.
2. Monitoring Annual Report: The Principal Copermittee must submit the Receiving Waters and MS4 Discharge Monitoring Annual Report to the San Diego Water Board on October 1 of each year, beginning on **October 1, 2013**. Receiving Waters and MS4 Discharge Monitoring Annual Reports must include monitoring conducted under the previous fiscal year, must meet the following requirements:
  - a. Annual monitoring reports must include the data/results, methods of evaluating the data, graphical summaries of the data, and an explanation/discussion of the data for each monitoring program component.
  - b. Annual monitoring reports must include a watershed-based analysis of the findings of each monitoring program component (mass loading, bioassessment, etc...). Each watershed-based analysis must include:
    - (1) Identification and prioritization of water quality problems within each watershed.
    - (2) Identification and description of the nature and magnitude of potential sources of the water quality problems within each watershed.
    - (3) Evaluation and presentation of pollutant load and concentration increases or decreases at each mass loading station over time.
    - (4) Evaluation of pollutant loads and concentrations measured at mass loading stations with respect to land use, population, sources, and other characteristics of watersheds using tools such as multiple linear regression, factor analysis, and cluster analysis.

- (5) Identification of links between source activities/conditions and observed receiving water impacts.
  - (6) Identification of recommended future monitoring to identify and address sources of water quality problems.
  - (7) Results and discussion of any TIE conducted, together with actions that will be implemented to reduce the discharge of pollutants in storm water, eliminate any discharge of pollutants in non-storm water, and abate the sources causing the toxicity.
- c. Annual monitoring reports must include an analysis and interpretation of the data for each watershed with respect to the management questions listed in section I.B of this Receiving Waters Monitoring and Reporting Program.
  - d. Annual monitoring reports must include a discussion describing how each of the goals listed in section I.A of this MRP is addressed by the Copermittees' monitoring program for the monitoring year covered by the report.
  - e. Annual monitoring reports must include identification and analysis of any long-term trends in storm water or receiving water quality. Trend analysis must use nonparametric approaches, such as the Mann-Kendall test, including exogenous variables in a multiple regression model, and/or using a seasonal nonparametric trend model, where applicable.
  - f. Annual monitoring reports must provide an estimation of total pollutant loads (wet weather loads plus dry weather loads) due to MS4 Discharge for each of the hydrologic subareas, including for 303(d) pollutants specified in Table 2 of the Order.
  - g. Annual monitoring reports must, for each monitoring program component listed above, include an assessment of compliance with applicable water quality standards.
  - h. Annual monitoring reports must describe monitoring station locations by latitude and longitude coordinates, frequency of sampling, quality assurance/quality control procedures, and sampling and analysis protocols.

- i. Annual monitoring reports must use a standard report format and include the following elements:
    - (1) A stand alone comprehensive executive summary addressing all sections of the monitoring report;
    - (2) Comprehensive interpretations and conclusions; and
    - (3) Recommendations for future actions.
  - j. All monitoring reports submitted to the Principal Copermittee or the San Diego Water Board must contain the certified perjury statement described in Attachment B of this Order No. R9-2010-0016.
  - k. Annual monitoring reports must be reviewed prior to submittal to the San Diego Water Board by a committee of the Copermittees (consisting of no less than three different Copermittee members).
  - l. Annual monitoring reports must be submitted in both electronic and paper formats. Electronic formats must be CEDEN or SWAMP-uploadable.<sup>14</sup>
3. Monitoring programs and reports must comply with section II.F of Receiving Waters and MS4 Discharge Monitoring and Reporting Program No. R9-2010-0016 and Attachment B of this Order.
  4. Following completion of an annual cycle of monitoring in October, the Copermittees must make the monitoring data and results available to the San Diego Water Board at the San Diego Water Board's request. Following completion of the annual cycle of monitoring, the Copermittees must upload monitoring data and results into the California Environmental Data Exchange Network (CEDEN)<sup>15</sup>.

## **B. Interim Reporting Requirements**

For the October 2010 to October 2012 monitoring period, the Principal Copermittee must submit the Receiving Waters Monitoring Annual Report as required under Order No. 2004-001. The Receiving Waters Monitoring Annual Report must address the monitoring conducted to comply with the requirements of Order No. 2004-0001.

---

<sup>14</sup> For updates to the SWAMP templates and formats, see <http://www.waterboards.ca.gov/swamp>.

<sup>15</sup> <http://www.ceden.org/>

### C. Reporting Dates

Table 5. Table of Required MRP Reporting Dates and Frequencies.

<b>Submittal</b>	<b>Section</b>	<b>Completion Date</b>	<b>Frequency</b>
Description of Proposed Monitoring Program	III.A.1	June 1, 2012	One Time
Receiving Waters and MS4 Discharge Monitoring Annual Reports, Including Proposed Updates to the Monitoring Program	III.A.2	Starting October 1, 2013	Annual
Copermittees submit Interim Monitoring Program Annual Report	III.B	As required under Order No. 2004-001	One Time
Draft Wet Weather MS4 Discharge Monitoring Program	II.B	June 01, 2012	One Time
Draft High Priority Inland Aquatic Habitat Monitoring	II.D	April 01, 2012	One Time
Draft Sediment Toxicity Special Study	II.E.2	April 01, 2012	One Time
Draft Trash and Litter Special Study	II.E.3	September 01, 2012	One Time
Draft Agricultural, Federal and Tribal Input Study	II.E.4	September 01, 2012	One Time
Draft MS4 and Receiving Water Maintenance Study	II.E.5	April 01, 2012	One Time
Draft Intermittent and Ephemeral Stream Perennial Conversion Study	II.E.6	April 01, 2013	One Time

**Attachment F**

**SOURCE DATA**

I. STORM WATER ACTION LEVELS DATABASE .....2

II. NUMERIC ACTION LEVELS EVALUATION DATA<sup>1</sup> .....9

---

<sup>1</sup> Represented data from monitoring conducted by the Copermittees and provided in the 2008-09 Annual Monitoring Report.



**I. STORM WATER ACTION LEVELS DATABASE**

<b>N02+NO3 (mg/l)</b>	<b>Phosphorous Total (mg/l)</b>	<b>Cadmium Total (ug/l)</b>	<b>Copper Total (ug/l)</b>	<b>Lead Total (ug/l)</b>	<b>Zinc Total (ug/l)</b>	<b>Turbidity (NTU)</b>
4.70	7.90	9.80	800.00	660.00	22500.00	10
4.20	7.19	6.00	340.00	620.00	18000.00	15
3.90	4.96	6.00	320.00	540.00	11000.00	15
3.90	4.50	6.00	270.00	520.00	9970.00	16
3.60	4.40	6.00	244.00	460.00	9100.00	22
3.60	4.24	6.00	230.00	450.00	8800.00	23
3.60	2.59	5.30	220.00	450.00	6500.00	23
3.50	2.59	5.00	220.00	440.00	5500.00	24
3.30	2.50	4.10	210.00	430.00	5000.00	24
3.30	2.50	4.00	210.00	400.00	4900.00	30
3.10	2.50	4.00	209.00	380.00	4600.00	31
3.00	2.27	4.00	209.00	360.00	4300.00	33
2.96	2.00	4.00	200.00	350.00	3800.00	36
2.90	2.00	4.00	200.00	330.00	3800.00	36
2.70	2.00	4.00	200.00	320.00	3400.00	39
2.70	2.00	3.90	200.00	320.00	3390.00	40
2.60	1.90	3.80	200.00	320.00	3100.00	45
2.60	1.90	3.40	180.00	310.00	2500.00	50
2.60	1.80	3.40	180.00	310.00	2200.00	50
2.50	1.80	3.20	166.00	310.00	2100.00	60
2.50	1.70	3.10	163.00	310.00	1829.00	61
2.32	1.70	3.00	160.00	300.00	1700.00	62
2.30	1.70	3.00	150.00	290.00	1500.00	65
2.20	1.60	3.00	140.00	280.00	1400.00	65
2.20	1.60	3.00	140.00	270.00	1300.00	66
2.10	1.60	3.00	140.00	270.00	1300.00	69
2.10	1.53	3.00	140.00	270.00	1285.00	70
2.10	1.50	3.00	140.00	270.00	1200.00	72
2.10	1.50	3.00	130.00	260.00	1100.00	80
2.00	1.47	3.00	130.00	260.00	1054.00	84
2.00	1.46	3.00	128.00	250.00	1000.00	97
2.00	1.40	3.00	120.00	250.00	980.00	111
2.00	1.40	3.00	120.00	250.00	960.00	140
1.90	1.40	3.00	120.00	245.00	850.00	151
1.90	1.30	2.90	120.00	230.00	850.00	157
1.90	1.30	2.80	120.00	230.00	850.00	590
1.90	1.30	2.70	111.00	225.00	850.00	
1.90	1.30	2.60	111.00	220.00	840.00	
1.80	1.30	2.50	110.00	220.00	780.00	
1.80	1.30	2.40	110.00	210.00	768.00	
1.70	1.24	2.40	110.00	210.00	760.00	
1.70	1.20	2.30	110.00	200.00	750.00	

## Order No. R9-2010-0016

1.70	1.20	2.20	110.00	200.00	740.00	
1.70	1.20	2.10	110.00	190.00	740.00	
1.70	1.20	2.00	100.00	190.00	730.00	
1.70	1.10	2.00	100.00	190.00	720.00	
1.70	1.10	2.00	100.00	190.00	710.00	
1.60	1.10	2.00	100.00	170.00	710.00	
1.60	1.10	2.00	100.00	170.00	700.00	
1.60	1.06	2.00	100.00	170.00	700.00	
1.60	1.00	2.00	99.00	160.00	690.00	
1.60	0.96	2.00	94.00	160.00	690.00	
1.60	0.96	2.00	91.00	150.00	680.00	
1.60	0.94	2.00	91.00	150.00	680.00	
1.53	0.94	2.00	90.00	150.00	670.00	
1.50	0.92	2.00	90.00	150.00	660.00	
1.50	0.91	2.00	89.00	150.00	660.00	
1.50	0.85	2.00	87.00	140.00	660.00	
1.50	0.85	2.00	87.00	140.00	650.00	
1.50	0.85	2.00	84.00	140.00	630.00	
1.50	0.83	2.00	83.00	130.00	610.00	
1.40	0.83	2.00	82.00	130.00	610.00	
1.40	0.83	2.00	81.00	130.00	597.00	
1.40	0.81	2.00	81.00	130.00	590.00	
1.40	0.81	2.00	77.00	130.00	590.00	
1.40	0.81	2.00	77.00	123.00	576.00	
1.40	0.80	2.00	76.00	120.00	570.00	
1.40	0.80	2.00	74.00	120.00	570.00	
1.32	0.78	2.00	72.00	120.00	560.00	
1.30	0.78	1.90	72.00	120.00	560.00	
1.30	0.77	1.90	72.00	120.00	540.00	
1.30	0.77	1.90	72.00	115.00	540.00	
1.30	0.76	1.80	72.00	110.00	520.00	
1.30	0.76	1.80	71.00	110.00	520.00	
1.30	0.75	1.80	70.00	110.00	520.00	
1.30	0.75	1.70	70.00	110.00	510.00	
1.29	0.75	1.60	67.00	102.00	500.00	
1.20	0.74	1.60	66.00	100.00	500.00	
1.20	0.73	1.60	66.00	100.00	490.00	
1.20	0.72	1.60	66.00	100.00	480.00	
1.20	0.72	1.60	65.00	100.00	475.00	
1.20	0.72	1.60	65.00	100.00	470.00	
1.20	0.71	1.50	63.00	99.00	470.00	
1.20	0.71	1.50	63.00	97.00	462.00	
1.20	0.69	1.40	62.00	97.00	460.00	
1.20	0.68	1.30	62.00	97.00	460.00	
1.20	0.68	1.30	60.00	95.00	450.00	
1.20	0.68	1.20	60.00	91.00	440.00	
1.10	0.68	1.20	59.00	90.00	440.00	
1.10	0.68	1.20	56.59	90.00	440.00	

## Order No. R9-2010-0016

1.10	0.67	1.20	55.00	87.00	430.00	
1.10	0.66	1.10	55.00	86.00	430.00	
1.10	0.66	1.10	54.00	86.00	430.00	
1.10	0.65	1.10	54.00	84.00	420.00	
1.10	0.65	1.10	54.00	82.00	420.00	
1.10	0.65	1.10	53.00	82.00	410.00	
1.10	0.65	1.00	53.00	81.00	409.00	
1.00	0.63	1.00	52.00	78.00	400.00	
1.00	0.62	1.00	51.00	78.00	400.00	
1.00	0.61	1.00	50.00	78.00	400.00	
1.00	0.60	1.00	50.00	77.00	390.00	
1.00	0.60	1.00	50.00	76.00	390.00	
1.00	0.59	1.00	50.00	76.00	390.00	
0.99	0.57	1.00	50.00	69.00	390.00	
0.99	0.57	1.00	50.00	69.00	390.00	
0.98	0.56	1.00	50.00	67.00	370.00	
0.97	0.56	1.00	50.00	66.00	370.00	
0.96	0.55	1.00	49.00	66.00	370.00	
0.96	0.55	1.00	49.00	66.00	360.00	
0.95	0.55	1.00	49.00	65.00	360.00	
0.95	0.53	1.00	48.00	64.00	360.00	
0.93	0.53	1.00	48.00	61.00	360.00	
0.93	0.53	1.00	47.00	57.00	350.00	
0.93	0.52	1.00	46.08	57.00	350.00	
0.93	0.52	1.00	46.00	56.00	350.00	
0.92	0.52	1.00	46.00	56.00	340.00	
0.90	0.52	1.00	44.25	53.00	340.00	
0.88	0.51	1.00	44.00	53.00	340.00	
0.87	0.51	1.00	44.00	52.60	340.00	
0.86	0.50	1.00	44.00	52.00	340.00	
0.85	0.49	1.00	44.00	51.00	340.00	
0.84	0.49	1.00	43.00	51.00	334.00	
0.83	0.48	1.00	43.00	50.00	330.00	
0.81	0.48	1.00	43.00	50.00	330.00	
0.81	0.48	1.00	42.00	50.00	330.00	
0.80	0.47	1.00	42.00	50.00	330.00	
0.80	0.47	1.00	42.00	50.00	330.00	
0.78	0.47	1.00	41.00	50.00	330.00	
0.78	0.46	1.00	40.00	50.00	330.00	
0.77	0.46	1.00	40.00	50.00	320.00	
0.77	0.46	1.00	40.00	50.00	320.00	
0.77	0.45	1.00	40.00	50.00	320.00	
0.74	0.45	1.00	40.00	50.00	320.00	
0.73	0.44	1.00	39.00	49.00	310.00	
0.72	0.44	1.00	39.00	47.00	310.00	
0.69	0.44	1.00	39.00	46.00	310.00	
0.69	0.44	1.00	39.00	46.00	308.00	
0.69	0.44	1.00	39.00	44.00	300.00	

## Order No. R9-2010-0016

0.67	0.44	1.00	39.00	44.00	300.00	
0.67	0.44	1.00	37.00	43.00	300.00	
0.66	0.43	1.00	37.00	42.00	300.00	
0.66	0.42	1.00	37.00	41.00	290.00	
0.65	0.42	1.00	37.00	41.00	285.00	
0.63	0.41	1.00	37.00	41.00	280.00	
0.62	0.41	1.00	36.00	41.00	280.00	
0.62	0.41	1.00	36.00	41.00	280.00	
0.62	0.40	1.00	36.00	40.10	280.00	
0.60	0.40	1.00	36.00	40.00	280.00	
0.59	0.40	1.00	35.00	39.30	280.00	
0.59	0.40	1.00	35.00	39.00	280.00	
0.58	0.40	1.00	34.00	39.00	280.00	
0.57	0.40	1.00	34.00	39.00	280.00	
0.57	0.40	1.00	33.40	38.00	270.00	
0.55	0.40	1.00	33.00	38.00	270.00	
0.52	0.40	1.00	33.00	38.00	270.00	
0.50	0.40	1.00	33.00	37.00	270.00	
0.50	0.39	1.00	33.00	36.00	270.00	
0.46	0.39	1.00	33.00	36.00	270.00	
0.42	0.39	1.00	32.26	36.00	260.00	
0.42	0.38	1.00	32.01	36.00	260.00	
0.35	0.38	1.00	32.00	35.00	260.00	
0.10	0.38	1.00	32.00	34.00	260.00	
0.06	0.37	1.00	32.00	34.00	260.00	
	0.36	1.00	32.00	33.00	250.00	
	0.36	1.00	32.00	33.00	250.00	
	0.36	1.00	32.00	33.00	250.00	
	0.36	1.00	31.00	33.00	250.00	
	0.35	1.00	31.00	32.00	247.00	
	0.35	1.00	31.00	32.00	242.13	
	0.35	1.00	31.00	31.94	240.00	
	0.35	1.00	30.00	30.00	240.00	
	0.34	1.00	30.00	30.00	240.00	
	0.34	1.00	30.00	30.00	240.00	
	0.34	1.00	30.00	30.00	240.00	
	0.34	1.00	30.00	30.00	230.00	
	0.34	1.00	29.00	30.00	230.00	
	0.34	1.00	29.00	30.00	220.00	
	0.33	1.00	28.00	29.00	220.00	
	0.33	1.00	28.00	29.00	220.00	
	0.33	0.98	28.00	29.00	210.00	
	0.33	0.94	28.00	29.00	210.00	
	0.33	0.94	27.19	28.00	210.00	
	0.33	0.92	27.00	28.00	210.00	
	0.32	0.90	27.00	28.00	210.00	
	0.32	0.90	27.00	27.00	210.00	
	0.32	0.86	26.00	27.00	210.00	

## Order No. R9-2010-0016

	0.32	0.80	26.00	26.31	205.00	
	0.32	0.80	26.00	26.00	202.79	
	0.31	0.71	25.00	26.00	202.00	
	0.31	0.70	25.00	25.00	200.00	
	0.30	0.70	25.00	25.00	200.00	
	0.30	0.60	24.00	25.00	200.00	
	0.30	0.60	24.00	24.60	200.00	
	0.30	0.59	23.00	24.00	200.00	
	0.30	0.59	23.00	24.00	200.00	
	0.30	0.52	23.00	24.00	200.00	
	0.30	0.50	23.00	24.00	194.49	
	0.29	0.50	23.00	23.00	190.00	
	0.29	0.50	22.00	23.00	190.00	
	0.29	0.50	22.00	23.00	190.00	
	0.29	0.50	21.00	23.00	190.00	
	0.29	0.50	21.00	23.00	184.13	
	0.29	0.50	21.00	23.00	180.00	
	0.28	0.50	21.00	22.20	180.00	
	0.28	0.50	20.36	22.00	180.00	
	0.28	0.50	20.00	22.00	180.00	
	0.27	0.50	20.00	22.00	180.00	
	0.27	0.50	20.00	22.00	180.00	
	0.27	0.50	20.00	21.20	180.00	
	0.26	0.50	20.00	21.10	170.00	
	0.26	0.40	19.00	21.00	170.00	
	0.26	0.40	19.00	20.00	170.00	
	0.26	0.40	18.00	19.10	170.00	
	0.25	0.30	18.00	19.00	160.00	
	0.25	0.30	18.00	19.00	160.00	
	0.25	0.30	18.00	19.00	160.00	
	0.25	0.30	18.00	19.00	160.00	
	0.25	0.30	17.00	18.50	160.00	
	0.25	0.30	17.00	18.00	160.00	
	0.24	0.20	17.00	18.00	160.00	
	0.24	0.20	17.00	18.00	160.00	
	0.24	0.20	17.00	18.00	160.00	
	0.23	0.04	17.00	17.00	160.00	
	0.23		17.00	17.00	150.00	
	0.23		17.00	17.00	150.00	
	0.23		17.00	17.00	150.00	
	0.22		16.00	17.00	150.00	
	0.22		16.00	17.00	150.00	
	0.22		16.00	17.00	146.00	
	0.22		16.00	17.00	145.00	
	0.22		16.00	17.00	140.00	
	0.22		15.00	16.90	140.00	
	0.22		15.00	16.00	140.00	
	0.21		15.00	15.00	140.00	

## Order No. R9-2010-0016

	0.21		15.00	15.00	140.00	
	0.21		15.00	15.00	140.00	
	0.21		14.50	15.00	140.00	
	0.21		14.00	15.00	140.00	
	0.21		14.00	14.00	140.00	
	0.20		14.00	14.00	140.00	
	0.20		14.00	14.00	136.55	
	0.20		14.00	13.00	135.60	
	0.20		14.00	13.00	130.00	
	0.20		13.00	13.00	130.00	
	0.20		13.00	13.00	130.00	
	0.20		13.00	13.00	130.00	
	0.20		13.00	12.00	130.00	
	0.20		13.00	12.00	130.00	
	0.19		13.00	12.00	130.00	
	0.19		12.00	12.00	127.00	
	0.19		12.00	12.00	124.00	
	0.19		12.00	12.00	122.05	
	0.19		12.00	11.00	120.00	
	0.19		11.00	11.00	120.00	
	0.19		11.00	11.00	120.00	
	0.18		10.00	10.00	120.00	
	0.18		10.00	10.00	112.11	
	0.18		10.00	10.00	110.00	
	0.18		10.00	10.00	110.00	
	0.18		9.60	10.00	110.00	
	0.18		9.60	10.00	110.00	
	0.17		9.10	10.00	110.00	
	0.17		9.10	10.00	110.00	
	0.17		9.00	10.00	110.00	
	0.17		8.30	9.60	110.00	
	0.17		8.20	9.40	110.00	
	0.16		8.00	9.10	108.00	
	0.15		8.00	9.00	100.00	
	0.15		7.70	9.00	100.00	
	0.15		7.70	9.00	100.00	
	0.15		7.00	9.00	100.00	
	0.15		7.00	8.00	100.00	
	0.15		6.80	8.00	100.00	
	0.14		6.80	8.00	99.00	
	0.14		6.80	8.00	98.00	
	0.14		6.50	8.00	97.00	
	0.14		6.50	8.00	93.40	
	0.14		6.30	8.00	92.00	
	0.14		6.30	7.60	92.00	
	0.14		6.10	7.50	90.00	
	0.13		5.60	7.00	90.00	
	0.13		5.40	7.00	90.00	

## Order No. R9-2010-0016

	0.13		5.20	6.00	86.00	
	0.13		5.00	6.00	83.00	
	0.13		4.90	6.00	81.00	
	0.12		4.50	5.90	81.00	
	0.12		4.10	5.80	80.00	
	0.12		4.10	5.40	80.00	
	0.11		3.90	5.00	80.00	
	0.11		3.40	5.00	80.00	
	0.11		2.60	5.00	80.00	
	0.11		2.60	5.00	79.00	
	0.10		2.60	5.00	73.00	
	0.10		2.30	5.00	72.00	
	0.10		2.00	4.80	70.00	
	0.10		2.00	4.80	70.00	
	0.09		1.70	4.70	70.00	
	0.08		1.50	4.60	70.00	
	0.06		1.50	4.00	64.00	
	0.03		1.50	4.00	63.00	
			1.40	3.80	61.00	
			1.40	3.00	60.00	
				3.00	56.00	
				2.30	44.00	
				2.00	40.00	
				1.60	37.00	
					35.00	
					30.00	
					26.00	
					24.00	
					20.00	
					10.00	
					5.00	

## II. NUMERIC ACTION LEVELS EVALUATION DATA







































































