

Appendix A

Proposed Basin Plan Amendment (February 8, 2008)

(Page intentionally left blank)

Proposed Basin Plan Amendment

The following text is proposed for insertion into Chapter 7, Water Quality Attainment Strategies including Total Maximum Daily Loads (TMDLs). Because this text would be added in its entirety, it is not shown below in underline/strikeout.

Sonoma Creek Watershed Sediment TMDL and Habitat Enhancement Plan

The goals of the Sonoma Creek Watershed Sediment TMDL and Habitat Enhancement Plan (Plan) are to:

- Conserve the steelhead trout population
- Restore water quality to meet water quality standards, including attaining beneficial uses
- Enhance the overall health of the native fish community
- Protect and enhance habitat for native aquatic species
- Enhance the aesthetic and recreational values of the creek and its tributaries

To achieve these goals, specific actions are needed to:

1. Reduce sediment loads, and fine sediment in particular, to Sonoma Creek and its tributaries
2. Attain and maintain suitable gravel quality in freshwater reaches of Sonoma Creek and its tributaries
3. Reduce and prevent channel incision
4. Reduce erosion and sedimentation
5. Repair large sources of sediment supply (e.g. landslides)
6. Enhance channel complexity (e.g. by adding and encouraging retention of large woody debris and restoring riparian vegetation)

The following sections establish:

1. A sediment total maximum daily load (TMDL) defining the allowable amount of sediment that can be discharged into Sonoma Creek, expressed as mass, and as a percentage of the natural background sediment delivery rate to channels
2. An implementation plan to achieve the TMDL and related habitat enhancement goals

Problem Statement

Steelhead populations in the Sonoma Creek watershed have declined substantially since the late 1940s. Results of recent analyses of fisheries and sediment sources indicate that:

1. Excessive amounts of fine sediment have been deposited in the streambed at potential steelhead spawning and rearing sites. Excess fine sediment in the streambed can cause poor incubation conditions for fish eggs, resulting in high mortality prior to emergence.

Fine sediment also compromises the quality of pools as rearing habitat, and reduces winter rearing habitat by filling the spaces between cobbles and boulders.

2. Changes in physical habitat structure that appear to be caused by erosion of bed and banks (incision) in Sonoma Creek are resulting in significant adverse changes to steelhead habitat. Analysis of in-stream shelter in Sonoma Creek yielded a low score when considering the watershed-wide average (38, which is 13 percent of the maximum score), indicating low quality of rearing habitat for juvenile steelhead. A steelhead census performed in 2002 indicates only 10 percent of steelhead are surviving past the juvenile rearing stage. These conditions are limiting the success of steelhead fish in Sonoma Creek.
3. Stressful water temperatures, low summer flows, and migration barriers also impact the health of Sonoma Creek’s coldwater fishery.

Due to excess erosion and sedimentation in the Sonoma Creek Watershed, the narrative water quality objectives for sediment and settleable material are not being met and cold freshwater habitat, wildlife habitat, fish spawning, recreation, and preservation of rare and endangered species beneficial uses are impaired. In addition, channel incision has caused habitat simplification, which has reduced and quantity and quality of spawning and rearing habitat for salmonids and other native aquatic species. Channel incision is a controllable water quality factor that is contributing to a violation of the narrative water quality objective for population and community ecology.

Numeric Targets and Desired Condition

Meeting the numeric targets and desired condition listed in Table 1 will allow water quality in Sonoma Creek and its tributaries to achieve the Basin Plan’s narrative water quality objectives for sediment, settleable material, and population and community ecology.

Table 1. TMDL sediment targets for Sonoma Creek and its Tributaries

Spawning gravel permeability	Median value \geq 7000 cm/hr ^a
Pool filling	Decreasing trend in the volume of fine sediment deposited in pools
Substrate Composition- Percent Fines	Percent of fine sediment less than 0.85 mm in diameter is less than or equal to 14 percent of the total bulk core sample (\leq 14% fines < 0.85 mm) ^b
	Percent of fine sediment less than 6.40 mm in diameter is less than or equal to 30 percent of the total bulk core sample (\leq 30% fines < 6.40 mm) ^b
^a Target applies to all potential spawning sites for steelhead and salmon in Sonoma Creek and its tributaries.	
^b Target applies to wadeable streams and rivers with gradient less than 3 percent. A wadeable stream is one which an average human can safely cross on foot during the summer, low flow season while wearing chest waders.	

Sources

Field assessments and sediment load modeling provide credible estimates of average rates of sediment delivery to Sonoma Creek. As shown in Table 2, the average annual sediment load to the freshwater reach of Sonoma Creek is estimated to be 118,000 tons per year, or 360 tons per km² per year. The natural background sediment delivery rate to Sonoma Creek is 52,000 tons per year, or 160 tons per km² per year. Therefore, the current sediment delivery rate is estimated to be 225 percent of the natural background rate.

Table 2. Sediment Delivery to Sonoma Creek (tons/year)

	Annual Sediment Load (tons/year) ^a
Natural Processes	
• Channel Erosion, Incision	25,000
• Landslides	4,000
• Soil Creep	17,000
• Surface Erosion	6,000
Total- Natural Processes	52,000
Human Actions	
• Channel Erosion, Incision	43,000
• Landslides	1,000
• Surface Erosion from Vineyards, Other Row Crops, and Grazing Lands:	9,000
• Urban Stormwater	1,000
• Roads and Stream Crossings	11,000
Total- Human Actions	66,000
TOTAL	118,000
^a Sediment loads are rounded to the nearest thousand.	

Total Maximum Daily Load and Allocations

The Sonoma Creek sediment TMDL is established at 65,400 tons per year, which is approximately 125 percent of natural background load. Natural background load depends upon natural processes, and varies significantly. Therefore, the TMDL and allocations are expressed both in terms of sediment mass and percent of natural background. The percentage based TMDL, 125% of natural background, applies throughout the watershed. In order to achieve the TMDL, controllable sediment delivery resulting from human actions needs to be reduced by approximately 80 percent from current proportion of the total load (Table 3). TMDL attainment will be evaluated at the limit of tidal influence in the Sonoma Creek watershed, which

approximates the downstream boundary of freshwater habitat for steelhead. Sonoma Creek has several tributaries that join the mainstem below the tidal limit; therefore, several points will be used to evaluate TMDL attainment. These points are: mainstem Sonoma Creek just downstream of the Fowler/Carriger Creek confluence, and the freshwater portions (above tidal influence) of Schell, Ramos, Carneros, and Merazo Creeks. Attainment of the TMDL will be evaluated over a 5-to-10-year averaging period. The TMDL equal to 125 percent of natural background load, can be achieved if human-related sources are reduced to the level of the allocations shown in Table 3.

Table 3. Sonoma Creek Sediment Load and Wasteload Allocations (tons/year)

Source Category	Current Condition	Allocation	
		tons/year	Percent Natural Background
LOAD ALLOCATIONS			
Natural Processes			
• Channel Erosion, Incision	25,400	25,400	49
• Landslides	4,100	4,100	8
• Soil Creep	16,600	16,600	32
• Surface Erosion	6,200	6,200	12
Total - Natural Processes	52,300	52,300	100
Human Actions			
• Channel Erosion, Incision	43,300	7,800	15
• Landslides	900	200	0.4
• Surface Erosion, including Vineyards, Grazed Lands, Unmanaged Areas, and Minor Agriculture	8,600	1,600	3
• Roads and Stream crossings	11,200	2,000	4
Total - Human Actions (Load Allocations)	64,000	11,600	22
Total - Load Allocations		63,900	122
WASTELOAD ALLOCATIONS			
Construction Stormwater- NPDES Permit No. CAS000002	300	300	0.6
Municipal Stormwater- NPDES Permit No. CAS000004	600	600	1
Industrial Stormwater- NPDES Permit No. CAS000001	100	100	0.2
Caltrans Stormwater- NPDES Permit No. CAS000003	500	500	1
Total - Wasteload Allocations		1,500	3
TOTAL ALLOCATIONS = TMDL		65,400	125
^a Allocations are rounded to the nearest hundred.			

IMPLEMENTATION PLAN

The Implementation actions described below are to achieve TMDL targets and allocations and habitat enhancement goals. In addition, actions specified in this plan are expected to enhance steelhead population. It is important to note that the allocations in the TMDL are not directly enforceable. To demonstrate attainment of applicable allocations, responsible parties must demonstrate that they are in compliance with required implementation measures and any applicable waste discharge requirements (WDRs), waiver conditions, or NPDES permits.

Regulatory Tools

The state's Policy for Implementation and Enforcement of the Nonpoint Source Pollution Control Program requires regulation of nonpoint source discharges using the Water Board's administrative permitting authorities, including waste discharge requirements, waiver of WDRs, Basin Plan Discharge Prohibitions, or some combination of these. Consistent with this policy, Tables 4.1 – 4.4 specify actions and performance standards by nonpoint source category, as needed to achieve TMDL sediment targets and allocations in the Sonoma Creek watershed. The Water Board will consider adopting conditions for waiving WDRs that apply to the nonpoint sources (vineyards, grazing, roads, etc.) listed in Tables 4.1 – 4.4, address all pollutants of concern, protect all beneficial uses, and balance the agricultural, environmental, recreational, and residential needs of the watershed.

The wasteload allocations contained in Table 3 apply to point sources of sediment that are regulated by NPDES permits. Table 4.5 shows implementation measures required of these sources, which include municipal stormwater, runoff from state highways, and from industrial and construction sites.

Problems associated with channel incision, related rapid bank erosion, and loss of essential habitat features, reflect and integrate multiple historical and ongoing disturbances, some of which are local and direct, and others that are indirect and distal. Effectively addressing these issues will require cooperative and coordinated actions by multiple landowners, working with public agencies, over significant distances along the creek. The most effective means of controlling channel incision and reducing related fine sediment delivery to the creek is a channel restoration program that re-establishes width-to-depth ratios and sinuosity values conducive to formation of alternate bars and a modest flood plain. The Water Board will work with stakeholders along Sonoma Creek, through local stewardship groups, to implement such channel restoration/habitat enhancement projects. Tables 5.1 to 5.3 (Recommended Measures to Protect or Enhance Habitat), specify actions to address adverse impacts of channel incision on salmonid habitat quantity and quality, and to accomplish habitat enhancement goals for flow, temperature, and fish passage for steelhead.

Individual landowners or coalitions may work with "third parties" to develop and implement sediment pollutant control programs. With regard to achievement of actions to protect or enhance baseflow, fish passage, habitat complexity, and stream temperature, the effectiveness

of the recommended actions specified in Tables 5.1 through 5.3, will be evaluated as part of the adaptive implementation program.

Agricultural Water Quality Control Program Costs

Implementation measures for grazing lands and vineyards constitute an agricultural water quality control program and therefore, consistent with California Water Code requirements (Section 13141), the cost of this program is estimated herein. This cost estimate includes the cost of implementing all actions to reduce sediment discharges and enhance habitat complexity as specified in the implementation plan, and is based on costs associated with technical assistance and evaluation, project design, and implementation of actions needed to achieve the TMDL. In estimating costs, the Water Board has assumed that owners of agricultural businesses own 75 percent of total land area on hillside parcels, and 95 percent of the land along Sonoma Creek and lower reaches of its tributaries. Based on these assumptions, the estimated total cost for program implementation for agricultural sources is \$1.3-to-2.3 million per year throughout the 20-year implementation period. More than three-quarters of these potential costs are associated with addressing channel incision and enhancing habitat conditions (to reverse the impacts of channel incision) in Sonoma Creek and its tributaries. Considering potential benefits to the public in terms of ecosystem functions, aesthetics, recreation, and water quality, it is anticipated that at least 75 percent of the cost of these actions will be paid for with public funds. Therefore, the total cost to agricultural businesses associated with efforts to reduce sediment supply and enhance habitat in Sonoma Creek is \$300,000-\$600,000 per year over the 20-year implementation period.

Evaluation and Monitoring

In collaboration with stakeholders in the watershed, Water Board staff will develop a detailed monitoring program to assess progress of TMDL attainment and provide a basis for reviewing and revising TMDL elements or implementation actions. As an initial milestone, by fall 2011, the Water Board and watershed partners will complete monitoring plans to evaluate: a) attainment of water quality targets; and b) suspended sediment and turbidity conditions. Initial data collection, based on the protocols established in these monitoring plans is anticipated to begin in the winter of 2011-2012.

As a whole, the monitoring program will be designed to:

1. *Assess channel response and progress towards achieving water quality targets.* In-channel effectiveness monitoring will be conducted to evaluate: a) progress toward achieving water quality targets, and b) channel response to management measures and natural processes. Parameters that will be monitored to assess progress toward achieving water quality targets are streambed permeability, pool filling, and percent fines composition of the substrate. The number of sites to be monitored will be selected based on availability/presence of the applicable habitat feature (i.e. spawning gravels and pools), as well as the number of samples needed to have a high degree of statistical confidence in estimated values. Frequency of monitoring should be once every five years, at a minimum, for streambed permeability and pool filling. If resources are available, desired monitoring frequency for all

TMDL target parameters is once every two to three years. Pool filling should be monitored every two to three years to allow a trend analysis. The Water Board may establish alternative water quality parameters and/or numeric target values at a future date as part of the adaptive implementation process, when/if information becomes available to conclude with a high degree of confidence that one or more alternative parameters or target values provide a superior basis for determining attainment of water quality objectives for sediment, and the protection of fisheries-related beneficial uses.

2. *Further evaluate potential impacts of suspended sediment and related turbidity.* To further study potential impacts of suspended sediment and related turbidity, monitoring of turbidity should continue. The Sonoma Ecology Center maintains a continuous and automated monitoring station at the Sonoma Valley Watershed Station in Eldridge, CA. Monitoring of suspended sediment should continue to further understanding of turbidity and suspended sediment concentrations in ambient conditions, and during and after storms. Turbidity/suspended sediment data should be analyzed to determine the length of time it takes for turbidity levels to drop to pre-storm levels after a storm event.

It is expected that as sediment reduction and habitat enhancement measures (including reducing channel incision) are undertaken, suspended sediment concentrations and turbidity levels will decrease. This expectation should be confirmed with continued turbidity monitoring. In addition, turbidity monitoring can provide information regarding the effectiveness of sediment reduction measures because it is a sensitive measure of the effects of land use on streams.

3. *Assess whether required sediment reduction measures are undertaken.* Implementation monitoring will be conducted by landowners or designated agents, per the compliance monitoring and reporting provisions of applicable waivers of Waste Discharge Requirements, Waste Discharge Requirements, and NPDES permits.
4. *Evaluate effectiveness of selected sediment reduction measures (both structural and management-related).* The Water Board will conduct upslope effectiveness monitoring to evaluate sediment delivery to channels from land use activities and natural processes. The first sediment source analysis update will occur by 2020, when sediment delivery associated with human activities may be reduced by 25 percent or more. A subsequent update may occur, assuming the water quality targets for sediment are not already achieved, by 2025, when sediment supply associated with human activities may be reduced by 40 percent or more. An additional goal for future updates of the source analysis is to reduce uncertainty associated with estimates of sediment delivery rates.
5. *Evaluate effectiveness of recommended habitat enhancement measures and assess progress towards goals of the Habitat Enhancement Plan.* The Water Board and local partners should monitor habitat complexity-related water quality indicators to assess progress towards achievement of a balanced sediment budget (where the amount of fine and coarse sediment input to a given channel reach is equal to the amount that is transported downstream).

Monitoring should occur to determine whether there is an increasing trend in the percent of the length of mainstem of Sonoma Creek, and in the lower alluvial reaches of its tributaries, that attain the following conditions:

- a) The bankfull channel width-to depth ratio is $\geq 12:1$.
- b) The average spacing between alluvial and/or forced gravel bars within the active channel is \leq times the width of the bankfull channel.
- c) Available shear stress at bankfull flow does not exceed the amount required to initiate motion of the streambed by more than approximately 20 percent.
- d) Floodplain width is ≥ 4 times bankfull channel width.

Monitoring should also assess whether there is:

- e) An increasing trend through time in the mean area and frequency of riffles and gravel bars within the mainstem channel; and
- f) A decreasing trend through time in the percent of the length of the mainstem of Sonoma Creek, and in the lower alluvial reach of its tributaries, where banks or bed are hardened, and/or where constructed levees contribute to channel instability.

The information gained from monitoring will guide adaptive implementation.

Adaptive Implementation

In concert with the monitoring program, described above, the Sonoma Creek Watershed Sediment TMDL and Habitat Enhancement Plan will be regularly updated. Results of in-progress or anticipated studies that enhance understanding of the population status of steelhead trout in the Sonoma Creek watershed, and/or factors controlling those populations, may also trigger changes to the plan and TMDL. At a minimum, data in response to the following questions will be considered to guide research and monitoring efforts and focus each subsequent update of the TMDL.

Key Questions to be considered in the course of Adaptive Implementation:

- What is the population status of steelhead in the watershed? Is there an increase in the number or percentage of steelhead that survive past the juvenile rearing life stage as sediment reduction and habitat enhancement measures are implemented?
- Are Sonoma Creek and its tributaries progressing toward TMDL targets as expected? If there has not been adequate progress, how might the implementation actions, targets or allocations be modified?
- What are expected benefits of various actions to enhance habitat for steelhead? Which actions, and in which locations, would enhancement measures have the most benefit and be the most cost-effective?
- Are the specified sediment reduction measures and recommended habitat enhancement measures resulting in an improving trend in channel stability?
- What effect will climate change have on hydrology, sediment transport, and habitat for the watershed's aquatic species? How will climate change effect the outcome of required and recommended measures, and how should these measured be adjusted in response?

- Are there new data or information available that warrants revision of water quality targets, allocations, or implementation measures?

Table 4.1 Required and Trackable TMDL Implementation Measures for Sediment Discharges Associated with Vineyards

Sources and Performance Standards	Actions	Implementing Parties	Completion Dates
<p>Surface Erosion associated with vineyards: Comply with the Sonoma County Vineyard Erosion and Sediment Control Ordinance (Sonoma County Code, Chapter 30, Article V) and minimize erosion from existing vineyards; and</p> <p>Roads: Road-related sediment delivery to channels \leq 120 tons per road mile per 20-year period^{3,4}; and</p> <p>Gullies and/or shallow landslides: Promote natural recovery and minimize human-caused increases in sediment delivery from unstable areas; or Implement farm plan certified under Fish Friendly Farming Environmental Certification Program or other farm plan certification program approved as part of WDRs waiver conditions.</p>	<p>Submit a Report of Waste Discharge¹ to the Water Board that provides, at a minimum, the following: a description of the vineyard; identification of site-specific erosion control measures needed to achieve performance standard(s) specified in this table; and a schedule for implementation of identified erosion control measures.</p>	<p>Vineyard owner and/or operator</p>	<p>June 2014</p>
	<p>Comply with applicable waste discharge requirements (WDRs) or waiver of WDRs.</p>	<p>Vineyard owner and/or operator</p>	<p>As specified in applicable WDRs or waiver of WDRs</p>
	<p>Report progress on implementation of site specific erosion control measures.²</p>	<p>Vineyard owner and/or operator</p>	<p>As specified in applicable WDRs or waiver of WDRs</p>
<p>¹ Or compliance with applicable conditional waivers of WDRs that may be adopted by the Water Board. ² Reports may be submitted individually or jointly through a recognized third party. ³ To achieve 82 percent reduction, from current estimate of 34 tons per mile per year, as needed to meet the sediment load allocation for road-related sediment delivery. ⁴ Performance standard for road-related sediment delivery of 120 tons per mile per 20-year period, is equivalent to a 20-year average rate of 6 tons per mile per year.</p>			

Table 4.2 Required TMDL Implementation Measures for Sediment Discharges Associated with Grazing

Source(s) and Performance Standard(s)	Actions	Implementing Parties	Completion Dates
<p>Surface erosion associated with livestock grazing: Attain or exceed minimal residual dry matter values consistent with University of California Division of Agriculture and Natural Resources guidelines; and</p> <p>Roads: Road-related sediment delivery to channels \leq 120 tons per road mile per 20-year period^{3,4} and</p> <p>Gullies and/or shallow landslides: Promote natural recovery and minimize human-caused increases in sediment delivery from unstable areas</p>	<p>Submit a Report of Waste Discharge¹ to the Water Board that provides, at a minimum, the following: description of the property; identification of site-specific erosion control measures to achieve performance standard(s) specified in this table; and a schedule for implementation of identified erosion control measures.</p>	<p>Landowner and/or ranch operator</p>	<p>June 2014</p>
	<p>Comply with applicable waste discharge requirements (WDRs) or waiver of WDRs.</p>	<p>Landowner and/or ranch operator</p>	<p>As specified in applicable WDRs or waiver of WDRs</p>
	<p>Report progress on implementation of site specific erosion control measures.²</p>	<p>Landowner and/or ranch operator</p>	<p>As specified in applicable WDRs or waiver of WDRs</p>
<p>¹Or compliance with applicable conditional waivers of WDRs that may be adopted by the Water Board. ²These reports may be prepared individually or jointly or through a recognized third party. ³To achieve 82 percent reduction, from current estimate of 34 tons per mile per year, as needed to meet the sediment load allocation for road-related sediment delivery. ⁴Performance standard for road-related sediment delivery of 120 tons per mile per 20-year period, is equivalent to a 20-year average rate of 6 tons per mile per year.</p>			

Table 4.3 Required TMDL Implementation Measures for Sediment Discharges Associated with Rural Lands¹

Sources and Performance Standards	Actions	Implementing Parties	Completion Dates
<p>Roads: Road-related sediment delivery to channels ≤ 120 tons per road mile per 20-year period^{4,5}; and</p> <p>Gullies and/or shallow landslides: Promote natural recovery, and minimize human caused increases in sediment delivery from unstable areas.</p>	<p>Submit a Report of Waste Discharge² to the Water Board that provides, at a minimum, the following: description of the property; identification of site-specific erosion control measures to achieve performance standard(s) specified in this table; and a schedule for implementation of identified erosion control measures.</p>	<p>Landowners</p>	<p>June 2014</p>
	<p>Comply with applicable Waste Discharge Requirements (WDRs) or waiver of WDRs.</p>	<p>Landowners</p>	<p>As specified in applicable WDRs or waiver of WDRs</p>
	<p>Report progress on implementation of-site specific erosion control measures.³</p>	<p>Landowners</p>	<p>As specified in applicable WDRs or waiver of WDRs</p>
<p>¹Rural lands include: non-farmed and non-grazing portions of parcels >10 acres that contain one or more residences, and/or a winery; vacant residential parcels >10 acres; and/or portions of 10-acres or larger parcels with secondary vineyard, orchard, and/or grazing.</p> <p>²Or compliance with applicable conditional waivers of WDRs that may be adopted by the Water Board</p> <p>³ These reports may be prepared individually or jointly or through a recognized third party.</p> <p>⁴To achieve 82 percent reduction, from current estimate of 34 tons per mile per year, as needed to meet the sediment load allocation for road-related sediment delivery.</p> <p>⁵Performance standard for road-related sediment delivery of 120 tons per mile per 20-year period, is equivalent to a 20-year average rate of 6 tons per mile per year.</p>			

Table 4.4 Required TMDL Implementation Measures for Sediment Discharges associated with Parks and Open Space, and/or Municipal Public Works

Landowner Type	Sources and Performance Standards	Actions	Implementing Parties	Completion Dates
PARKS AND OPEN SPACE AND PUBLIC WORKS	<p>Roads: Road-related sediment delivery to channels \leq 120 tons per road mile per 20-year period^{3,4}; and</p> <p>Gullies and/or shallow landslides: Promote natural recovery, and minimize human caused increases in sediment delivery from unstable areas.</p>	<p>Submit a Report of Waste Discharge¹ to Water Board that provides, at a minimum, the following: description of the road network and/or segments; identification of erosion and sediment control measures to achieve performance standard(s) specified in this table; and a schedule for implementation of identified control measures. For paved roads, erosion and sediment control actions could primarily focus on road crossings to meet the performance standard.</p> <p>Adopt and implement best management practices for maintenance of unimproved (dirt/gravel) roads, and conduct a survey of stream-crossings associated with paved public roadways, and develop a prioritized implementation plan for repair and/or replacement of high priority crossings/culverts to reduce road-related erosion and protect stream-riparian habitat conditions.</p>	<p>Sonoma County Stormwater Management Program (SWMP)</p> <p>State of California, Department of Parks and Recreation</p> <p>State of California, Department of Transportation</p> <p>County of Sonoma Transportation and Public Works</p>	June 2014
		<p>Comply with applicable Waste Discharge Requirements (WDRs) or waiver of WDRs.</p>	<p>Landowners</p>	<p>As specified in applicable WDRs or waiver of WDRs, and/or the SWMP</p>

Landowner Type	Sources and Performance Standards	Actions	Implementing Parties	Completion Dates
		Report progress on development and implementation of best management practices to control road-related erosion. ²	Landowners	As specified in applicable WDRs or waiver of WDRs, and/or SWMP
<p>¹Or compliance with applicable conditional waivers of WDRs that may be adopted by the Water Board.</p> <p>²These reports may be prepared individually or jointly or through a recognized third party.</p> <p>³To achieve 82 percent reduction, from current estimate of 34 tons per mile per year, as needed to meet the sediment load allocation for road-related sediment delivery.</p> <p>⁴Performance standard for road-related sediment delivery of 120 tons per mile per 20-year period, is equivalent to a 20-year average rate of 6 tons per mile per year.</p>				

Table 4.5 Required TMDL Implementation Measures for Sediment Discharges associated with Urban Land Uses

Source	Performance Standards	Actions	Implementing Parties	Completion Dates
Construction Stormwater Runoff	Control and minimize sediment and erosion from construction sites through appropriate use of Best Management Practices.	<p>Comply with the requirements of the <i>General Permit for Discharges of Storm Water Associated with Construction Activity</i> (NPDES Permit No. CAS000002) or updated versions of the Construction General Permit.</p> <p>Develop, maintain, and implement a Storm Water Pollution Prevention Plan (SWPPP) that describes BMPs to be used to control erosion and sedimentation.</p> <p>Develop and implement a sediment monitoring plan if the construction site discharges directly to Sonoma Creek or its tributaries.</p>	Owners or Operators of Sites under Construction	As specified in the Construction General Permit (NPDES Permit No. CAS000002)
Industrial Stormwater Runoff	Control discharges from industrial facilities to the standard of “best available technology economically achievable” and the “best conventional pollutant control technology”.	<p>Comply with the <i>Industrial Stormwater General Permit</i> (NPDES Permit No. CAS000001).</p> <p>Develop a SWPPP and monitoring plan to identify sources of pollutants (including sediment) and the means to control them to reduce stormwater pollution.</p>	Owners or Operators of Industrial Facility Sites	As specified in the Industrial Stormwater General Permit (NPDES Permit No. CAS000001)
Municipal Stormwater	Reduce discharge of pollutants,	Comply with approved stormwater	Sonoma County	As specified in approved
	including sediment, to the	management plans.	Water Agency,	stormwater management

Source	Performance Standards	Actions	Implementing Parties	Completion Dates
<i>Runoff</i>	maximum extent practicable (MEP).	Comply with Municipal Stormwater Permit (NPDES Permit No. CAS000004).	County of Sonoma, City of Sonoma, Sonoma Developmental Center, and any other designated entities	plan and in applicable NPDES permit (NPDES Permit No. CAS000004).
	Attenuate peak flows and durations from new and redevelopment projects to MEP standards.	Amend and implement stormwater management plans to control peak flow rates and durations	Sonoma County Water Agency, County of Sonoma, City of Sonoma, Sonoma Developmental Center, and any other designated entities	No later than June 2014
<i>State Highways Stormwater Runoff</i>	Control runoff from state highways and associated construction activities.	Comply with the <i>Statewide Stormwater Permit</i> (NPDES Permit No. CAS000003).	California Department of Transportation (Caltrans)	As specified in applicable NPDES permit (NPDES Permit No. CAS000003).

Table 5.1 Recommended Actions to Reduce Sediment Load and Enhance Habitat Complexity in Sonoma Creek and its Tributaries

Recommended Action	Management Objective(s)	Actions	Implementing Parties	Completion Dates and Notes
<p>Prevent and Reduce Channel Incision</p>	<p>Reduce rates of sediment delivery (associated with incision and associated bank erosion) to channels, by 80 percent.</p> <p>Enhance channel habitat as needed to support self-sustaining run of steelhead and enhance the overall health of the native fish community.</p> <p>Stabilize channel banks and riparian areas to reduce sediment loads from landslides.</p>	<p>Develop and prioritize channel restoration projects to address unstable areas, based on level of incision and/or landslide instability.</p>	<p>Landowners and/or designated agents, and reach-based stewardships</p>	<p>Comply with conditions of Clean Water Act Section 401 certifications</p>
<p>Enhance Physical Habitat Structure</p>	<p>Enhance quality of rearing habitat for juvenile salmonids by increasing riparian canopy, large woody debris, and frequency and depth of pool habitat.</p>	<p>Develop, prioritize, and implement plans to increase channel complexity, including increasing riparian canopy, pool habitat, and large woody debris.</p>	<p>Landowners and/or designated agents, and reach-based stewardships</p>	

Table 5.2 Recommended actions to Protect or Enhance Baseflow

Recommended Action	Management Objective	Action(s)	Implementing Parties	Schedule/Notes
<p>Enhance Summer Base Flows</p>	<p>Maintain suitable conditions for juvenile rearing, and smolt migration to Sonoma Creek estuary.</p>	<p>Implement a groundwater management plan to: 1) maintain groundwater levels for the support of beneficial uses, 2) increase water recycling and conservation in order to enhance summer base-flows, 3) identify and protect groundwater recharge areas, 4) enhance the recharge of groundwater where appropriate; and 5) protect against adverse interactions between groundwater and surface water flows.</p> <p>Identify potential groundwater recharge areas and develop pilot projects.</p>	<p>Sonoma County Water Agency, Valley of the Moon Water District, City of Sonoma, Basin Advisory Panel¹, and interested collaborators</p>	<p><i>The Sonoma Valley Groundwater Management Plan²</i> was adopted by the Sonoma County Water Agency in November 2007. The plan includes an implementation schedule to achieve recommended actions to protect or enhance baseflow.</p>
<p>¹The Basin Advisory Panel was formed to act as the groundwater management plan stakeholder group for the Sonoma Valley Basin</p> <p>² <i>The Sonoma Valley Groundwater Management Plan</i> (developed by the Sonoma County Water Agency, Valley of the Moon Water District, and City of Sonoma) is a non-regulatory plan aimed at locally managing, protecting, and enhancing groundwater resources.</p>				

Table 5.3 Recommended Actions to Restore to Fish Passage

Recommended Action	Management Objective(s)	Action(s)	Implementing Parties	Schedule/Notes
Address Fish Passage Barriers	No significant structural impediments to salmonid migration or passage in mainstem or key tributaries.	Design, replace or retrofit road crossings to allow fish passage according to fish-friendly guidance such as those developed by FishNet 4C, Department of Fish and Game, or other appropriate entity with expertise in salmonid habitat restoration.	Local public agencies, watershed groups and landowners	
	Reduce the number of stream miles inaccessible to fish.	Develop, prioritize, and implement plans to remove identified barriers to fish passage.	Local public agencies, watershed groups, and landowners	