

Measurement Quality Objectives for Acute Marine Water Toxicity Test Methods



The following Measurement Quality Objectives establish recommendations and requirements for acute marine water toxicity testing conducted for the State Water Resources Control Board's Surface Water Ambient Monitoring Program (SWAMP) projects. Non-SWAMP projects should meet the minimum requirements established in the fifth edition of the U.S. EPA guidance document *Methods for Measuring the Acute Toxicity of Effluents and Receiving Waters to Freshwater and Marine Organisms* (821/R-02/012).

Table 1. Laboratory Quality Control for Acute Marine Water Toxicity Test Methods

Negative Control	Frequency of Analysis	Measurement Quality Objective	Data Quality Indicator or Reasoning
Laboratory Control Water	Laboratory control water, consistent with the appropriate U.S. EPA test method, must be used with each analytical batch.	Laboratory control water must meet all test acceptability criteria for the species of interest.	Evaluates the health and sensitivity of the test organisms.
Additional Control Water for Manipulated Samples	Additional controls are required whenever manipulations are performed on one or more of the ambient samples within each analytical batch.	Both controls must meet test acceptability criteria, but if the secondary control is significantly different from the primary control, then the secondary control should be used for further statistical analysis in the determination of sample toxicity.	Evaluates the effects of manipulations upon the test organisms.
Additional Control Water for Unmanipulated Samples	Additional controls can be used for samples that have parameters near the tolerance threshold of the organism.	Must meet test acceptability criteria to be used for statistical comparisons. Does not have to be significantly different from the primary control for statistical comparisons.	Evaluates the effects of parameters near the tolerance threshold of the organism.

Positive Control	Frequency of Analysis	Measurement Quality Objective	Data Quality Indicator or Reasoning
Reference Toxicant Tests	One reference toxicant test per analytical batch is required when using organisms that are either commercially-supplied or wild-caught. Monthly reference toxicant testing is required for laboratories utilizing in-house cultures.	The last plotted data point (LC50 or EC50) should be within 2 standard deviations of the cumulative mean (n=20). Reference toxicant tests that fall outside of recommended control chart limits are evaluated to determine the validity of associated tests. A reference toxicant test outside of the 2 standard deviations does not invalidate the associated test results.	Used to assess intra-laboratory precision.

Table 2. Laboratory Quality Control Corrective Actions for Acute Marine Water Toxicity Test Methods

Negative Control	Recommended Corrective Action
Laboratory Control Water	Laboratories must begin retesting affected samples and the associated control within 7 days of test failure or after resampling. The laboratory should try to determine the source of the control failure, document the investigation, and record the steps taken to prevent a recurrence.
Additional Control Water	Additional controls for manipulated samples must meet test acceptability criteria for the test to be valid.
Positive Control	Recommended Corrective Action
Reference Toxicant Tests	If the LC50 exceeds ± 2 standard deviations of the running mean of the last 20 reference toxicant tests, the laboratory should investigate sources of variability, take actions to reduce identified sources of variability, and may perform an additional reference toxicant test during the same month.

Table 3. Field Quality Control for Acute Marine Water Toxicity Test Methods

Quality Control	Frequency of Analysis	Measurement Quality Objective	Data Quality Indicator or Reasoning
Field Blanks	Based on project requirements.	No statistical difference between the laboratory control and the field blank within an analytical batch.	Used to measure bias introduced during sample collection and handling.
Bottle Blanks	Based on project requirements.	No statistical difference between the laboratory control and the bottle blank within an analytical batch.	Used to measure bias introduced during washing procedures prior to collection.

Table 4. Field Quality Control Corrective Actions for Acute Marine Water Toxicity Test Methods

Quality Control	Recommended Corrective Action
Field Blanks	If contamination of the field blanks and associated samples is known or suspected, the laboratory should flag the affected data. The project coordinator should be notified so that the sampling team can identify the contamination source(s) and perform corrective action prior to the next sampling event.
Bottle Blanks	If contamination of the bottle blanks and associated samples is known or suspected, the laboratory should flag the affected data. The project coordinator should be notified so that the laboratory or vendor can identify the contamination source(s) and perform corrective action prior to the next sampling event.

Table 5. Sample Handling for Acute Marine Water Toxicity Test Methods

Container	Sample Receipt Temperature	Sample Preservation	Holding Time
Amber glass (recommended)	0 – 6 °C (required)	Wet or blue ice in field; 0 – 6 °C refrigeration in laboratory (do not freeze); dark at all times (required)	<48 hours (required)

Table 6. 96-Hour Acute Marine Water *Americamysis bahia* Survival Toxicity Test Method

Test Acceptability Criteria	≥90% mean survival in the controls (required)
Test Type	Static renewal (required)
Age at Test Initiation	1 – 5 days old; ≤24-hour range in ages (required)
Replication at Test Initiation	4 (required minimum)
Organisms per Replicate	10 (required minimum)
Food Source	Newly-hatched <i>Artemia</i> nauplii (<24 hours old)
Temperature Range	25 °C ± 1 °C (recommended); the maximum temperature must not deviate from the minimum temperature by more than 3 °C (required)
Renewal Frequency	80% at 48 hours (required)
Test Duration	96 hours (required)
Endpoint	Survival (required)
Salinity	5 – 34 ppt ± 2 ppt (recommended)
Light Intensity	10 – 20 µE/m ² /s or 50 – 100 ft-c (recommended)
Photoperiod	16 hours of ambient laboratory light, 8 hours dark (recommended)
Test Chamber Size	250 mL (recommended)
Replicate Volume	200 mL (recommended)
Feeding Regime	0.2 mL daily (recommended)
Minimum Sample Volume	2 L for one-time grab sample (recommended)
Laboratory Control Water	1 µm filtered natural seawater or hyper-saline brine prepared from uncontaminated natural seawater and reagent water (recommended)
Initial Water Chemistry	1 DO, pH, salinity, ammonia, and temperature measurement (required)
Renewal Water Chemistry	2 DO measurements (1 in old solution and 1 in new solution); 1 pH, salinity, and temperature measurement (required)
Final Water Chemistry	1 DO, pH, salinity, ammonia, and temperature measurement (required)
Initial DO Range	4.0 mg/L – 100% saturation (recommended)

Table 7. 96-Hour Acute Marine Water *Atherinops affinis* Larval Survival Toxicity Test Method

Test Acceptability Criteria	≥90% mean survival in the controls (required)
Test Type	Static renewal (required)
Age at Test Initiation	9 – 15 days old, post-hatch (required)
Replication at Test Initiation	5 (required minimum)
Organisms per Replicate	5 (required minimum)
Food Source	Newly-hatched <i>Artemia</i> nauplii (<24 hours old)
Temperature Range	20 °C ± 1 °C (recommended); the maximum temperature must not deviate from the minimum temperature by more than 3 °C (required)
Renewal Frequency	80% at 48 hours (required)
Test Duration	96 hours (required)
Endpoint	Survival (required)
Salinity	5 – 36 ppt ± 2 ppt (recommended)
Light Intensity	10 – 20 µE/m ² /s or 50 – 100 ft-c (recommended)
Photoperiod	16 hours of ambient laboratory light, 8 hours dark (recommended)
Test Chamber Size	600 mL (recommended)
Replicate Volume	200 mL (recommended)
Feeding Regime	40 nauplii per larvae, twice daily (recommended)
Minimum Sample Volume	2 L for one-time grab sample (recommended)
Laboratory Control Water	1 µm filtered natural seawater or hyper-saline brine prepared from uncontaminated natural seawater and reagent water (recommended)
Initial Water Chemistry	1 DO, pH, salinity, ammonia, and temperature measurement (required)
Renewal Water Chemistry	2 DO measurements (1 in old solution and 1 in new solution); 1 pH, salinity, and temperature measurement (required)
Final Water Chemistry	1 DO, pH, salinity, ammonia, and temperature measurement (required)
Initial DO Range	4.0 mg/L – 100% saturation (recommended)