



Federal Register

**Thursday,
May 18, 2000**

Part III

Environmental Protection Agency

40 CFR Part 131

**Water Quality Standards; Establishment of
Numeric Criteria for Priority Toxic
Pollutants for the State of California; Rule**

important to specify design flows in today's rule so that, in the absence of state design flows, the criteria promulgated today would be implemented appropriately. The TSD also recommends the use of three dynamic models to perform wasteload allocations. Dynamic wasteload models do not generally use specific steady state design flows but accomplish the same effect by factoring in the probability of occurrence of stream flows based on the historical flow record.

The low flows specified in the rule explicitly contain duration and frequency of occurrence which represent certain probabilities of occurrence. Likewise, the criteria for priority toxic pollutants are defined with duration and frequency components. Dynamic modeling techniques explicitly predict the effects of variability in receiving water, effluent flow, and pollution variation. Dynamic modeling techniques, as described in the TSD, allow for calculating wasteload allocations that meet the criteria for priority toxic pollutants without using a single, worst-case concentration based on a critical condition. Either dynamic modeling or steady state modeling can be used to implement the criteria promulgated today. For simplicity, only steady state conditions are discussed here. Clearly, if the criteria were implemented using design flows that are too high, the resulting toxic controls would not be adequate, because the resulting ambient concentrations would exceed EPA's criteria.

In the case of aquatic life, assuming exceedences occur more frequently than once in three years on the average, exceedences would result in diminished vitality of stream ecosystems characterized by the loss of desired species. Numeric water quality criteria should apply at all flows that are equal to or greater than flows specified below. The low flow values are:

Type of criteria	Design flow
Acute Aquatic Life (CMC).	1 Q 10 or 1 B 3
Chronic Aquatic Life (CCC).	7 Q 10 or 4 B 3
Human Health	harmonic mean flow

Where:

1 Q 10 is the lowest one day flow with an average recurrence frequency of once in 10 years determined hydrologically;

1 B 3 is biologically based and indicates an allowable exceedence of once every 3 years. It is determined by

EPA's computerized method (DFLOW model);

7 Q 10 is the lowest average 7 consecutive day low flow with an average recurrence frequency of once in 10 years determined hydrologically;

4 B 3 is biologically based and indicates an allowable exceedences for 4 consecutive days once every 3 years. It is determined by EPA's computerized method (DFLOW model);

EPA is requiring that the harmonic mean flow be applied with human health criteria. The harmonic mean is a standard calculated statistical value. EPA's model for human health effects assumes that such effects occur because of a long-term exposure to low concentration of a toxic pollutant, for example, two liters of water per day for seventy years. To estimate the concentrations of the toxic pollutant in those two liters per day by withdrawal from streams with a high daily variation in flow, EPA believes the harmonic mean flow is the correct statistic to use in computing such design flows rather than other averaging techniques. (For a description of harmonic means see "Design Stream Flows Based on Harmonic Means," Lewis A. Rossman, Jr. of Hydraulics Engineering, Vol. 116, No. 7, July, 1990.)

All waters (including lakes, estuaries, and marine waters), whether or not suitable for such hydrologic calculations, are subject to the criteria promulgated today. Such criteria will need to be attained at the end of the discharge pipe, unless the State authorizes a mixing zone. Where the State plans to authorize a mixing zone, the criteria would apply at the locations allowed by the mixing zone. For example, the chronic criteria (CCC) would apply at the defined boundary of the chronic mixing zone. Discussion of and guidance on these factors are included in the revised TSD in Chapter 4.

EPA is aware that the criteria promulgated today for some of the priority toxic pollutants are at concentrations less than EPA's current analytical detection limits. Analytical detection limits have never been an acceptable basis for setting water quality criteria since they are not related to actual environmental impacts. The environmental impact of a pollutant is based on a scientific determination, not a measuring technique which is subject to change. Setting the criteria at levels that reflect adequate protection tends to be a forcing mechanism to improve analytical detection methods. See 1985

Guidelines, page 21. As the methods improve, limits based on the actual criteria necessary to protect aquatic life and human health become measurable. The Agency does not believe it is appropriate to promulgate criteria that are not sufficiently protective. EPA discusses this issue further in its Response to Comment Document for today's final rule.

EPA does believe, however, that the use of analytical detection limits are appropriate for assessing compliance with National Pollutant Discharge Elimination System (NPDES) permit limits. This view of the role of detection limits was first articulated in guidance for translating dioxin criteria into NPDES permit limits. See "Strategy for the Regulation of Discharges of PHDDs and PHDFs from Pulp and Paper Mills to Waters of the U.S." Memorandum from the Assistant Administrator for Water to the Regional Water Management Division Directors, May 21, 1990. This guidance presented a model for addressing toxic pollutants which have criteria less than current detection limits. EPA, in more recent guidance, recommends the use of the "minimum level" or ML for reporting sample results to assess compliance with WQBELs (TSD page 111). The ML, also called the "quantification level," is the level at which the entire analytical system gives recognizable mass spectra and acceptable calibration points, i.e., the point at which the method can reliably quantify the amount of pollutant in the sample. States can use their own procedures to average and otherwise account for monitoring data, e.g., quantifying results below the ML. These results can then be used to assess compliance with WQBELs. (See 40 CFR part 132, Appendix F, Procedure 8.B.) This approach is applicable to priority toxic pollutants with criteria less than current detection limits. EPA's guidance explains that standard analytical methods may be used for purposes of assessing compliance with permit limits, but not for purposes of establishing water quality criteria or permit limits. Under the CWA, analytical methods are appropriately used in connection with NPDES permit limit compliance assessments. Because of the function of water quality criteria, EPA has not considered the sensitivity of analytical methods in deriving the criteria promulgated today.

EPA has promulgated 40 CFR 131.38(c)(3) to determine when freshwater or saltwater aquatic life criteria apply. This provision incorporates a time parameter to better define the critical condition. The structure of the paragraph is to establish

applicable rules and to allow for site-specific exceptions where the rules are not consistent with actual field conditions. Because a distinct separation generally does not exist between freshwater and saltwater aquatic communities, EPA is establishing the following: (1) The freshwater criteria apply at salinities of 1 part per thousand and below at locations where this occurs 95% or more of the time; (2) saltwater criteria apply at salinities of 10 parts per thousand and above at locations where this occurs 95% more of the time; and (3) at salinities between 1 and 10 parts per thousand the more stringent of the two apply unless EPA approves the application of the freshwater or saltwater criteria based on an appropriate biological assessment. The percentiles included here were selected to minimize the chance of overlap, that is, one site meeting both criteria. Determination of these percentiles can be done by any reasonable means such as interpolation between points with measured data or by the application of calibrated and verified mathematical models (or hydraulic models). It is not EPA's intent to require actual data collection at particular locations.

In the brackish water transition zones of estuaries with varying salinities, there generally will be a mix of freshwater and saltwater species. Generally, therefore, it is reasonable for the more stringent of the freshwater or saltwater criteria to apply. In evaluating appropriate data supporting the alternative set of criteria, EPA will focus on the species composition as its preferred method. This assignment of criteria for fresh, brackish and salt waters was developed in consultation with EPA's research laboratories at Duluth, Minnesota and Narragansett, Rhode Island. The Agency believes such an approach is consistent with field experience.

Paragraph (d) in 40 CFR 131.38 lists the designated water and use classifications for which the criteria apply. The criteria are applied to the beneficial use designations adopted by the State of California; EPA has not promulgated any new use classifications in this rule.

Exceedences Frequency: In a water quality criterion for aquatic life, EPA recommends an allowable frequency for excursions of the criteria. See 1985 Guidelines, pages 11–13. This allowable frequency provides an appropriate period of time during which the aquatic community can recover from the effect of an excursion and then function normally for a period of time before the next excursion. An excursion is defined

as an occurrence of when the average concentration over the duration of the averaging period is above the CCC or the CMC. As ecological communities are naturally subjected to a series of stresses, the allowable frequency of pollutant stress may be set at a value that does not significantly increase the frequency or severity of all stresses combined. See also TSD, Appendix D. In addition, providing an allowable frequency for exceeding the criterion recognizes that it is not generally possible to assure that criteria are never exceeded. (TSD, page 36.)

Based on the available data, today's rule requires that the acute criterion for a pollutant be exceeded no more than once in three years on the average. EPA is also requiring that the chronic criterion for a pollutant be exceeded no more than once in three years on the average. EPA acknowledges that States may develop allowable frequencies that differ from these allowable frequencies, so long as they are scientifically supportable, but believes that these allowable frequencies are protective of the designated uses where EPA is promulgating criteria.

The use of aquatic life criteria for developing water quality-based effluent limits in permits requires the permitting official to use an appropriate wasteload allocation model. (TSD, Appendix D–6.) As discussed above, there are generally two methods for determining design flows, the hydrologically-based method and the biologically-based method.

The biologically-based method directly uses the averaging periods and frequencies specified in the aquatic life criteria for determining design flows. (TSD, Appendix. D–8.) Because the biologically-based method calculates the design flow directly from the duration and allowable frequency, it most accurately provides the allowed number of excursions. The hydrologically based method applies the CMC at a design flow equal to or equivalent to the 1Q10 design flow (i.e., the lowest one-day flow with an average recurrence frequency of once in ten years), and applies the CCC at the 7Q10 design flow (i.e., the lowest average seven consecutive day flow with a recurrence frequency of once in ten years).

EPA established a three year allowable frequency in the NTR. In settlement of the litigation on the NTR, EPA stated that it was in the midst of conducting, sponsoring, or planning research aimed at addressing scientific issues related to the basis for and application of water quality criteria and mentioned the issue of allowable frequency. See Partial Settlement Agreement in *American Forest and*

Paper Ass'n, Inc. et al. v. U.S. EPA (Consolidated Case No. 93–0694 (RMU) D.D.C. To that end, EPA is reevaluating issues raised about allowable frequency as part of its work in revising the 1985 Guidelines.

EPA recognizes that additional data concerning (a) the probable frequency of lethal events for an assemblage of taxa covering a range of sensitivities to pollutants, (b) the probable frequency of sublethal effects for such taxa, (c) the differing effects of lethal and sublethal events in reducing populations of such taxa, and (d) the time needed to replace organisms lost as a result of toxicity, may lead to further refinement of the allowable frequency value. EPA has not yet completed this work. Until this work is complete, EPA believes that where EPA promulgates criteria, the three year allowable frequency represents a value in the reasonable range for this parameter.

3. Implementation

Once the applicable designated uses and water quality criteria for a water body are determined, under the National Pollutant Discharge Elimination System (NPDES) program discharges to the water body must be characterized and the permitting authority must determine the need for permit limits. If a discharge causes, or contributes to an excursion of a numeric or narrative water quality criteria, the permitting authority must develop permit limits as necessary to meet water quality standards. These permit limits are water quality-based effluent limitations or WQBELs. The terms "cause," "reasonable potential to cause," and "contribute to" are the terms in the NPDES regulations for conditions under which water quality-based permit limits are required. See 40 CFR 122.44(d)(1).

Since the publication of the proposed CTR, the State of California adopted procedures which detail how water quality criteria will be implemented through NPDES permits, waste discharge requirements, and other regulatory approaches. These procedures entitled, *Policy for Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bays, and Estuaries of California* were adopted on March 2, 2000. Once these procedures are submitted for review under CWA section 303(c), EPA will review them as they relate to water quality standards, and approve or disapprove them.

Several commenters understood the language in the preamble to the proposed rule regarding implementation